

Package 'PWMErich.Dmelanogaster.background'

April 4, 2014

Maintainer Robert Stojnic <robert.stojnic@gmail.com>

License GPL-3

Title D. melanogaster background for PWMErich

Type Package

LazyLoad yes

Author Robert Stojnic

Description PWMErich pre-compiled background objects for Drosophila melanogaster and MotifDb D. melanogaster motifs.

Version 2.1.1

biocViews AnnotationData, Drosophila_melanogaster

Date 2013-08-18

Depends methods, PWMErich

R topics documented:

PWMErich.Dmelanogaster.background-package	2
Index	4

 PWMErich.Drosophila.melanogaster.background-package

PWMErich.Drosophila.melanogaster.background package overview

Description

This package provides a set of pre-compiled genomic background files for the PWMErich package and *D. melanogaster*. The backgrounds were pre-compiled using unique promoters of *Drosophila melanogaster*.

- `MotifDb.Dmel.PFM` - a list of 740 position frequency matrices (PFMs) from `MotifDb`
- `MotifDb.Dmel` - the corresponding PWMs generated by using the background frequencies of A,C,G,T in a set of 10031 2kb promoters in *D. Melanogaster*.
- `PWMLogn.dm3.MotifDb.Dmel` - pre-compiled threshold-free lognormal background for JASPAR insects PWMs. The lognormal distribution is fitted to 1kb fragments of 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).
- `PWMCutoff4.dm3.MotifDb.Dmel`, `PWMCutoff5.dm3.MotifDb.Dmel` - pre-compiled Z-score background with cutoff of 4 and 5 (base e) for JASPAR insects PWMs. The number of hits above the score cutoff is counted in 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).
- `PWMPvalueCutoff1e2.dm3.MotifDb.Dmel`, `PPWMPvalueCutoff1e3.dm3.MotifDb.Dmel`, `PPWMPvalueCutoff1e4.dm3.MotifDb.Dmel` - pre-compiled Z-score background with P-value cutoff of 0.01, 0.001, and 0.0001 for JASPAR insects PWMs. The number of hits with smaller P-value than cutoff is counted in 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).
- `PWMGEV.dm3.MotifDb.Dmel` - pre-compiled generalized extreme value (GEV) distribution with location, scale and shape parameters fitted using linear regression on fragments of size 200-2000bp on all unique 2kb *Drosophila Melanogaster* (dm3) promoters.

Usage

```
data(MotifDb.Dmel.PFM)
data(MotifDb.Dmel)
data(PWMLogn.dm3.MotifDb.Dmel)
data(PWMCutoff4.dm3.MotifDb.Dmel)
data(PWMCutoff5.dm3.MotifDb.Dmel)
data(PWMGEV.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e2.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e3.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e4.dm3.MotifDb.Dmel)
```

Details

All of these objects were created with the appropriate functions available in the PWMErich package (see Section 'See also'). We recommend using these functions to generate backgrounds for a custom set of background sequences and/or DNA motifs.

Author(s)

Robert Stojnic
Cambridge Systems Biology Centre
University of Cambridge, UK
Maintainer: Robert Stojnic <robert.stojnic@gmail.com>

See Also

[makeBackground](#), [makePWMLognBackground](#), [makePWMCutoffBackground](#), [makePWMEmpiricalBackground](#).

Examples

```
data(PWMLogn.dm3.MotifDb.Dmel)

res = motifEnrichment(DNAString("TGCATCAAGTGTAGTGCGATGAATGC"), PWMLogn.dm3.MotifDb.Dmel)

head(motifRankingForGroup(res))
```

Index

*Topic **package**

PWMErich.Dmelanogaster.background-package,
[2](#)

makeBackground, [3](#)
makePWMCutoffBackground, [3](#)
makePWMEmpiricalBackground, [3](#)
makePWMLognBackground, [3](#)
MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMCutoff4.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMCutoff5.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMErich.Dmelanogaster.background
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMErich.Dmelanogaster.background-package,
[2](#)

PWMEV.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMLogn.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMPvalueCutoff1e2.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMPvalueCutoff1e3.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)

PWMPvalueCutoff1e4.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[2](#)