

Package ‘PWMEnrich.Hsapiens.background’

April 4, 2014

Maintainer Robert Stojnic <robert.stojnic@gmail.com>

License GPL-3

Title H. sapiens background for PWMEnrich

Type Package

LazyLoad yes

Author Robert Stojnic

Description PWMEnrich pre-compiled background objects for H. sapiens (human) and MotifDb H. sapiens motifs.

Version 0.99.1

biocViews AnnotationData, Organism, Homo_sapiens

Date 2013-09-18

Depends R (>= 2.10), methods, PWMEnrich

R topics documented:

PWMEnrich.Hsapiens.background-package 2

Index 4

PWMEnrich.Hsapiens.background-package

PWMEnrich.Hsapiens.background package overview

Description

This package provides a set of pre-compiled genomic background files for the PWMEnrich package and H. sapiens (human). The backgrounds were pre-compiled using unique 2kb promoters in human.

- MotifDb.Hsap.PFM - a list of position frequency matrices (PFMs) from MotifDb
- MotifDb.Hsap - the corresponding PWMs generated by using the background frequencies of A,C,G,T in a set of 2kb human (hg19) promoters.
- PWMLogn.hg19.MotifDb.Hsap - pre-compiled threshold-free lognormal background for MotifDb human PWMs. The lognormal distribution is fitted to 500bp chunks of 2kb human (hg19) promoters.
- PWMcutoff4.hg19.MotifDb.Hsap, PWMcutoff5.hg19.MotifDb.Hsap - pre-compiled Z-score background with cutoff of 4 and 5 (base e) for MotifDb human PWMs. The number of hits is counted in 2kb human (hg19) promoters.
- PWPvaluecutoff1e2.hg19.MotifDb.Hsap, PWPvaluecutoff1e3.hg19.MotifDb.Hsap, PWPvaluecutoff1e4.hg19.MotifDb.Hsap - pre-compiled Z-score background with P-value cutoff of 0.01, 0.001, and 0.0001 for MotifDb human PWMs. The number of hits with smaller P-value than cutoff is counted in 2kb human (hg19) promoters.

Usage

```
data(MotifDb.Hsap.PFM)
data(MotifDb.Hsap)
data(PWMLogn.hg19.MotifDb.Hsap)
data(PWMcutoff4.hg19.MotifDb.Hsap)
data(PWMcutoff5.hg19.MotifDb.Hsap)
data(PWPvaluecutoff1e2.hg19.MotifDb.Hsap)
data(PWPvaluecutoff1e3.hg19.MotifDb.Hsap)
data(PWPvaluecutoff1e4.hg19.MotifDb.Hsap)
```

Details

All of these objects were created with the appropriate functions available in the PWMEnrich package (see Section 'See also'). We recommend using these functions to generate backgrounds for a custom set of background sequences and/or DNA motifs.

Author(s)

Robert Stojnic
Cambridge Systems Biology Centre
University of Cambridge, UK
Maintainer: Robert Stojnic <robert.stojnic@gmail.com>

See Also

[makeBackground](#), [makePWMLognBackground](#), [makePWMCutoffBackground](#), [makePWMEmpiricalBackground](#).

Examples

```
data(PWMLogn.hg19.MotifDb.Hsap)

res = motifEnrichment(DNAString("TGCATCAAGTGTGTAGTGCAAGTGAGTGATGAGTAGAAGTTGAGTGAGGTAGATGC"), PWMLogn.hg19.MotifDb.Hsap)

groupReport(res)[1:10]
```

Index

*Topic **package**

- PWMErich.Hsapiens.background-package,
[2](#)

- makeBackground, [3](#)
- makePWMCutoffBackground, [3](#)
- makePWMEmpiricalBackground, [3](#)
- makePWMLognBackground, [3](#)
- MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)

- PWMCutoff4.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMCutoff5.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMErich.Hsapiens.background
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMErich.Hsapiens.background-package,
[2](#)
- PWMEV.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMLogn.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMPvalueCutoff1e2.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMPvalueCutoff1e3.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)
- PWMPvalueCutoff1e4.hg19.MotifDb.Hsap
(PWMErich.Hsapiens.background-package),
[2](#)