

encoDnaseI

March 23, 2012

rawCd4DnaseI	<i>A data frame with information on the UCSC browser track related to DNaseI hypersensitivity</i>
--------------	---

Description

A data frame with information on the UCSC browser track related to DNaseI hypersensitivity; the rawCD4 object is an eSet extension representing the same information; rawHelaDnaseI is like rawCD4 but results on Hela cells.

Usage

```
data(rawCd4DnaseI)
data(rawHelaDnaseI)
data(rawCD4)
```

Details

Obtained from a MySQL representation of the data distributed at the Genome Browser FTP site

Value

a data.frame

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

References

hgdownload.cse.ucsc.edu ... it appears that they do not offer the MYD/MYI representations, just the txt.gz and sql files now. So if you obtain the encodeNhgriDnaseHsChipRawCd4.txt and .sql files at goldenPath/currentGenomes/Homo_Sapiens/encode/database, you can reconstruct the underlying data for this data.frame (hg18, Nov 2007).

Examples

```
data(rawCd4DnaseI)
dim(rawCd4DnaseI)
rawCd4DnaseI[1:5,]
library(lattice)
xyplot(dataValue~chromStart|chrom, data=rawCd4DnaseI, subset=chrom %in%
  c("chr1", "chr10", "chr19", "chr20"), scales=list(x=list(relation="free")))
```

hg18track-class	<i>Class "hg18track" container for hg18 annotation found in genome browser track files; class "chrnum" extends numeric for an indexing application on hg18track objects.</i>
-----------------	--

Description

container for hg18 annotation found in genome browser track files

Objects from the Class

Objects can be created by calls of the form `new("hg18track", assayData, featureData, experimentData, annotation, dataVals, ...)`. These are single-sample `eSet` instances.

Note that `demoTrk19` is a restriction of the `rawCD4` structure to the interval of chromosome 19 that was assayed in the ENCODE project for DnaseI hypersensitivity.

Slots

```
assayData: Object of class "AssayData" ~~
phenoData: Object of class "AnnotatedDataFrame" ~~
featureData: Object of class "AnnotatedDataFrame" ~~
experimentData: Object of class "MIAME" ~~
annotation: Object of class "character" ~~
.__classVersion__: Object of class "Versions" ~~
```

Extends

Class "`eSet`", directly. Class "`VersionedBiobase`", by class "`eSet`", distance 2. Class "`Versioned`", by class "`eSet`", distance 3.

Methods

```
[ signature(x = "hg18track"): select using numeric, logical, or chrnum indices.
chrnum signature(object = "hg18track"): extract numeric tokens for chromosome
  number at which data values are obtained; note that chrnum is also used as name of a class.
dataVals signature(object = "hg18track"): actual data values
getTrkXY signature(object = "hg18track", type = "character"): obtain a
  list with components x, y indicating location and data value respectively; location is within
  chromosome; default type is 'midpoint' of locations given as intervals
```

getTrkXY signature(object = "hg18track", type = "missing"): take default midpoint x values corresponding to data values

rangeLocs signature(object = "hg18track"): if measures from only one chromosome are present, this returns low and high values of chromStart and chromEnd respectively, otherwise error.

clipTrk signature(obj = "hg18track", low="numeric", hi="numeric", attr="ANY"): create a restriction of the track using an interval specification. by default the chromStart featureData component is used for coordinates to clip; if attr is non-missing, the featureData component named by attr will be used.

initialize signature(.Object = "hg18track"): create a new instance

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
showClass("hg18track")
data(rawCD4)
rawCD4
rawCD4.chr1 = rawCD4[ chrnum(1), ]
rangeLocs(rawCD4.chr1)
plot(getTrkXY(rawCD4.chr1), ylab="data value", xlab="interval midpt on chr 1" )
c52 = clipTrk(rawCD4[ chrnum(5), ], 1.30e8, 1.33e8 )
plot(getTrkXY(c52))
```

juxtaPlot

two-panel plot with track info and snp screen t-values

Description

two-panel plot with track info and snp screen t-values

Usage

```
juxtaPlot(trk, ssr, locstr)
```

Arguments

trk	instance of <code>hg18track</code>
ssr	instance of <code>GGtools snpScreenResult</code>
locstr	matrix with 2 rows: rsid (numeric component of dbSNP id) and loc

Details

xyplot of lattice package is used.

Value

xyplot output; use print in Sweave.

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
## Not run:  
# see vignette  
data(sOSR2)  
data(c19g) # track excerpt  
juxtaPlot(c19g, sOSR2)  
  
## End(Not run)
```

Index

*Topic classes

hg18track-class, 2

*Topic models

juxtaPlot, 3

rawCd4DnaseI, 1

[, hg18track, ANY, ANY, ANY-method
(hg18track-class), 2

[, hg18track-method
(hg18track-class), 2

c19g (juxtaPlot), 3

chrnum (hg18track-class), 2

chrnum, hg18track-method
(hg18track-class), 2

chrnum, numeric-method
(hg18track-class), 2

chrnum-class (hg18track-class), 2

chromStarts (hg18track-class), 2

chromStarts, hg18track-method
(hg18track-class), 2

clipTrk (hg18track-class), 2

clipTrk, hg18track, numeric, numeric, ANY-method
(hg18track-class), 2

clipTrk, hg18track, numeric, numeric-method
(hg18track-class), 2

dataVals (hg18track-class), 2

dataVals, hg18track-method
(hg18track-class), 2

demoPGM1ssr (juxtaPlot), 3

demoTrk19 (hg18track-class), 2

eSet, 2

getTrkXY (hg18track-class), 2

getTrkXY, hg18track, character-method
(hg18track-class), 2

getTrkXY, hg18track, missing-method
(hg18track-class), 2

hg18track, 3

hg18track-class, 2

initialize, hg18track-method
(hg18track-class), 2

juxtaPlot, 3

makeHg18track (hg18track-class), 2

rangeLocs (hg18track-class), 2

rangeLocs, hg18track-method
(hg18track-class), 2

rawCD4 (rawCd4DnaseI), 1

rawCd4DnaseI, 1

rawHelaDnaseI (rawCd4DnaseI), 1

sOSR2 (juxtaPlot), 3

Versioned, 2

VersionedBiobase, 2