

rpx: an *R* interface to the ProteomeXchange repository

Laurent Gatto

lg390@cam.ac.uk

Computational Proteomics Unit*

April 16, 2015

1 Introduction

The goal of the *rpx* package is to provide programmatic access to proteomics data from *R*, in particular to the ProteomeXchange¹ (PX) central repository (see <http://www.proteomexchange.org/> and <http://central.proteomexchange.org/>). Additional repositories are likely to be added in the future.

2 The *rpx* package

PXDataset objects

The central object that handles data access is the `PXDataset` class. Such an instance can be generated by passing a valid PX experiment identifier to the `PXDataset` constructor.

```
library("rpx")
id <- "PXD000001"
px <- PXDataset(id)
px

## Object of class "PXDataset"
## Id: PXD000001 with 10 files
## [1] 'F063721.dat' ... [10] 'erwinia_carotovora.fasta'
## Use 'pxfiles(.)' to see all files.
```

*<http://cpu.sysbiol.cam.ac.uk>

¹ Vizcaíno J.A. et al. *ProteomeXchange: globally co-ordinated proteomics data submission and dissemination*, Nature Biotechnology 2014, 32, 223 – 226, doi:10.1038/nbt.2839.

Data and meta-data

Several attributes can be extracted from an PXDataset instance, as described below.

The experiment identifier, that was originally used to create the PXDataset instance can be extracted with the `pxid` method:

```
pxid(px)
## [1] "PXD000001"
```

The file transfer url where the data files can be accessed can be queried with the `pxurl` method:

```
pxurl(px)
## [1] "ftp://ftp.pride.ebi.ac.uk/pride/data/archive/2012/03/PXD000001"
```

The species the data has been generated the data can be obtain calling the `pntax` function:

```
pntax(px)
## [1] "Erwinia carotovora"
```

Relevant bibliographic references can be queried with the `pxref` method:

```
strwrap(pxref(px))
## [1] "Gatto L, Christoforou A. Using R and Bioconductor for proteomics data analysis."
## [2] "Biochim Biophys Acta. 2014 Jan;1844(1 Pt A):42-51. Review"
```

All files available for the PX experiment can be obtained with the `pxfiles` method:

```
pxfiles(px)
## [1] "F063721.dat"
## [2] "F063721.dat-mztab.txt"
## [3] "PRIDE_Exp_Complete_Ac_22134.xml.gz"
## [4] "PRIDE_Exp_mzData_Ac_22134.xml.gz"
## [5] "PXD000001_mztab.txt"
## [6] "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01-20141210.mzML"
## [7] "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01-20141210.mzXML"
## [8] "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.mzXML"
## [9] "TMT_Erwinia_1uLSike_Top10HCD_isol2_45stepped_60min_01.raw"
## [10] "erwinia_carotovora.fasta"
```

The complete or partial data set can be downloaded with the `pxget` function. The function takes an instance of class PXDataset as first mandatory argument.

The next argument, `list`, specifies what files to download. If missing, a menu is printed and the user can select a file. If set to "all", all files of the experiment are downloaded in the working directory. Alternatively, numerics or logicals can also be used to subset the relevant files to be downloaded based on the `pxfiles(.)` output.

The last argument, `force`, can be set to `TRUE` to force the download of files that already exists in the working directory.

```
pxget(px, "erwinia_carotovora.fasta")
## Downloading 1 file
dir(pattern = "fasta")
## [1] "erwinia_carotovora.fasta"
```

By default, `pxget` will not download and overwrite a file if already available. The last argument of `pxget`, `force`, can be set to `TRUE` to force the download of files that already exists in the working directory.

```
(i <- grep("fasta", pxfiles(px)))
## [1] 10
pxget(px, i) ## same as above
## Downloading 1 file
## erwinia_carotovora.fasta already present.
```

Finally, a list of recent PX additions and updates can be obtained using the `pxannounced()` function:

```
pxannounced()
## 15 new ProteomeXchange announcements
```

	Data.Set	Publication.Data	Message
## 1	PXD000298	2015-04-16 12:32:31	Updated information
## 2	PXD000297	2015-04-16 12:32:04	Updated information
## 3	PXD001464	2015-04-15 14:42:05	New
## 4	PXD001711	2015-04-15 12:24:32	New
## 5	PXD001272	2015-04-15 10:08:08	Updated information
## 6	PXD001550	2015-04-15 10:07:35	New
## 7	PXD001546	2015-04-15 09:48:04	New
## 8	PXD001081	2015-04-15 09:34:27	New
## 9	PXD001330	2015-04-15 09:09:46	Updated information
## 10	PXD002068	2015-04-15 03:02:59	New
## 11	PXD001927	2015-04-14 09:02:52	New
## 12	PXD001929	2015-04-13 15:59:51	New
## 13	PXD001871	2015-04-13 13:02:01	New
## 14	PXD001858	2015-04-13 10:42:39	New
## 15	PXD001469	2015-04-13 08:17:23	New

A simple use-case

Below, we show how to automate the extraction of files of interest (fasta and mzTab files), download them and read them using appropriate Bioconductor infrastructure.

```
(mzt <- grep("F0.+mztab", pxfiles(px), value = TRUE))
## [1] "F063721.dat-mztab.txt"

(fas <- grep("fasta", pxfiles(px), value = TRUE))
## [1] "erwinia_carotovora.fasta"

pxget(px, c(mzt, fas))

## Downloading 2 files
## erwinia_carotovora.fasta already present.

library("Biostings")
readAAStringSet(fas)

## A AAStringSet instance of length 4499
##      width seq                                     names
## [1] 147 MADITLISGSTLGS AEYVAEHLAEELLE...EIDITQHQIPEDPAEEWLGSWVNLLK ECA0001 putative
## [2] 153 VAEIYQIDNLD RGILSALMENARTPYA...IQTIDEIQTETLISLQNPIMRTIAP ECA0002 AsnC-fami
## [3] 330 MKKQYIEKQQQISFVKSFSSQLEQLL...LQLPHIGVQCQGVWPQPLRESVSGLL ECA0003 putative
## [4] 492 MITLESLEMLLSIDENELDDLVTLM...IFDHIWRFD TGLKSRLMRRWQH GKAY ECA0004 conserved
## [5] 499 MRQTAALAERISRLSHALEHGLYERQH...PSEWLAKIEASLQQVAEQIQQSEQQD ECA0005 conserved
## ...
## [4495] 634 MSDKIIHLTDDSFDTDLKADGAILVD...EWISVRRKVDPLRVFASDMARRLELL trx-rv3790 trx-rv
## [4496] 93 MTKMNNKARRTARELKHLGASIQTTS...KPALYRELRDEFPMGYLG DYKDDDDK TimBlower TimBlowe
## [4497] 309 MFSNLSKRWAQRTLKSFYSTATGAAS...SIWVKKFKWAGIKTRKFVFNPPKPRK sp|P07143|CY1_YEA
## [4498] 231 FPTDDDDKIVGGYTCAANSIPYQVSLN...AQKNKPGVYTKVCNYVNIQQTIAAN sp|P00761|TRYP_PI
## [4499] 269 GVSGSCNIDVVCPEGNGHRDVIRSVAA...LSDWLDAAGTGAQFIDGLDSTGTPPV sp|Q7M135|LYSC_LY

library("MSnbase")
(x <- readMzTabData(mzt, "PEP"))

## Detected a metadata section
## Detected a peptide section

## MSnSet (storageMode: lockedEnvironment)
## assayData: 1528 features, 6 samples
## element names: exprs
## protocolData: none
## phenoData
## rowNames: sub[1] sub[2] ... sub[6] (6 total)
## varLabels: abundance
## varMetadata: labelDescription
## featureData
```

```
## featureNames: 1 2 ... 1528 (1528 total)
## fvarLabels: sequence accession ... uri (14 total)
## fvarMetadata: labelDescription
## experimentData: use 'experimentData(object)'
## Annotation:
## - - - Processing information - - -
## mzTab read: Thu Apr 16 21:29:18 2015
## MSnbase version: 1.16.0

head(exprs(x))

##      sub[1]  sub[2]  sub[3]  sub[4]  sub[5]  sub[6]
## 1 10630132 11238708 12424917 10997763 9928972 10398534
## 2 11105690 12403253 13160903 12229367 11061660 10131218
## 3 1183431 1322371 1599088 1243715 1306602 1159064
## 4 5384958 5508454 6883086 6136023 5626680 5213771
## 5 18033537 17926487 21052620 19810368 17381162 17268329
## 6 9873585 10299931 11142071 10258214 9664315 9518271

head(fData(x)[, 1:2])

##      sequence accession
## 1    DGVSVAR    ECA0625
## 2    NVVLDK    ECA0625
## 3 VEDALHATR    ECA0625
## 4 LAGGVAVIK    ECA0625
## 5  LIAEAMEK    ECA0625
## 6  SFGAPTITK    ECA0625
```

3 Session information

- R version 3.2.0 RC (2015-04-08 r68161), x86_64-apple-darwin13.4.0
- Base packages: base, datasets, grDevices, graphics, methods, parallel, stats, stats4, utils
- Other packages: Biobase 2.28.0, BiocGenerics 0.14.0, BiocParallel 1.2.0, Biostrings 2.36.0, IRanges 2.2.0, MSnbase 1.16.0, ProtGenerics 1.0.0, Rcpp 0.11.5, S4Vectors 0.6.0, XVector 0.8.0, mzR 2.2.0, rpx 1.4.0
- Loaded via a namespace (and not attached): BiocInstaller 1.18.1, BiocStyle 1.6.0, MALDIquant 1.11, MASS 7.3-40, RCurl 1.95-4.5, XML 3.98-1.1, affy 1.46.0, affyio 1.36.0, bitops 1.0-6, codetools 0.2-11, colorspace 1.2-6, digest 0.6.8, doParallel 1.0.8, evaluate 0.6, foreach 1.4.2, formatR 1.1, futile.logger 1.4, futile.options 1.0.0, ggplot2 1.0.1, grid 3.2.0, gtable 0.1.2, highr 0.4.1, impute 1.42.0, iterators 1.0.7, knitr 1.9, lambda.r 1.1.7, lattice 0.20-31, limma 3.24.0, munsell 0.4.2, mzID 1.6.0, pcaMethods 1.58.0, plyr 1.8.1, preprocessCore 1.30.0, proto 0.3-10, reshape2 1.4.1, scales 0.2.4, stringr 0.6.2, tools 3.2.0, vsn 3.36.0, zlibbioc 1.14.0