

Package ‘RnBeads.rn5’

October 7, 2015

Title RnBeads.rn5

Description Annotation tables and mappings for rn5 used by RnBeads

Date 2013-01-27

Version 1.0.0

Depends R (>= 2.15), GenomicRanges

Suggests RnBeads (>= 0.99.0), BSgenome.Rnorvegicus.UCSC.rn5,

License GPL-3

NeedsCompilation no

Author Yassen Assenov [aut], Pavlo Lutsik [aut], Fabian Mueller [aut,
cre]

Maintainer Fabian Mueller <fmueLLer@mpi-inf.mpg.de>

R topics documented:

rn5	1
Index	3

rn5	<i>RN5 - Annotation tables</i>
-----	--------------------------------

Description

Scaffold of annotation tables for RN5. This structure is automatically loaded upon initialization of the annotation, that is, by the first valid call to any of the following functions: [rnb.get.assemblies](#), [rnb.get.chromosomes](#), [rnb.get.annotation](#), [rnb.set.annotation](#), [rnb.get.mapping](#), [rnb.annotation.size](#). Adding an annotation amounts to attaching its table(s) and mapping structures to this scaffold.

Format

list of four elements - "regions", "sites", "controls" and "mappings". These elements are described below.

"regions" list of NULLs; the names of the elements correspond to the built-in region annotation tables. Once the default annotations are loaded, the attribute "builtin" is a logical vector storing, for each region annotation, whether it is the default (built-in) or custom.

"sites" list of NULLs; the names of the elements correspond to the site annotation tables.

"mappings" list of NULLs; the names of the elements correspond to the built-in region annotation tables.

Author(s)

Yassen Assenov

Index

*Topic **datasets**

rn5, [1](#)

rn5, [1](#)

rn5.annotation.size, [1](#)

rn5.get.annotation, [1](#)

rn5.get.assemblies, [1](#)

rn5.get.chromosomes, [1](#)

rn5.get.mapping, [1](#)

rn5.set.annotation, [1](#)