

Package ‘CTDquerier’

March 4, 2022

Title Package for CTDbase data query, visualization and downstream analysis

Version 2.3.1

Description Package to retrieve and visualize data from the Comparative Toxicogenomics Database (<http://ctdbase.org/>). The downloaded data is formatted as DataFrames for further downstream analyses.

Depends R (>= 4.1)

License MIT + file LICENSE

Encoding UTF-8

LazyData false

Imports RCurl, stringr, S4Vectors, stringdist, ggplot2, igraph, utils, grid, gridExtra, methods, stats, BiocFileCache

VignetteBuilder rmarkdown

Suggests BiocStyle, knitr, rmarkdown

RoxygenNote 7.1.1

biocViews Software, BiomedicalInformatics, Infrastructure, DataImport, DataRepresentation, GeneSetEnrichment, NetworkEnrichment, Pathways, Network, GO, KEGG

git_url <https://git.bioconductor.org/packages/CTDquerier>

git_branch master

git_last_commit 755fb4a

git_last_commit_date 2021-11-20

Date/Publication 2022-03-04

Author Carles Hernandez-Ferrer [aut],
Juan R. Gonzalez [aut],
Xavier Escribà-Montagut [cre]

Maintainer Xavier Escribà-Montagut <xavier.escriba@isglobal.org>

R topics documented:

CTDdata	2
CTDquerier	6
download_ctd_chem	6
download_ctd_dise	7
download_ctd_genes	8
enrich	9
gala	10
get_table	10
get_terms	11
leaf_plot	12
load_ctd_chem	13
load_ctd_dise	14
load_ctd_gene	15
query_ctd_chem	16
query_ctd_dise	16
query_ctd_gene	17
Index	18

CTDdata	<i>Class CTDdata</i>
---------	----------------------

Description

Class resulting of [query_ctd_gene](#), [query_ctd_chem](#) and [query_ctd_dise](#). It is used to encapsulate all the information in *CTDbase* for given set of genes, chemicals or diseases.

Usage

```
## S4 method for signature 'CTDdata'
enrich(x, y, universe, use = "curated", warnings = TRUE, ...)

## S4 method for signature 'CTDdata'
get_table(object, index_name, ...)

## S4 method for signature 'CTDdata'
get_terms(object)

## S4 method for signature 'CTDdata,ANY'
plot(x, y, index_name = "base", representation = "heatmap", ...)
```

Arguments

x	Object of class CTDdata.
y	NOT USED

universe	String vector of genes used as universe. If not provided, all genes in CTDbase are used.
use	Select if all or only curated relations are used.
warnings	Shows or hides warnings.
...	NOT USED
object	Object of class CTDdata.
index_name	Name of the plot to be draw. See CTDdata 's detail section for more information (<code>?CTDdata-class</code>). representation.
representation	Can take values "heatmap" or "network".

Details

CTDdata objects provides with a summarized representation of the downloaded data obtained from the standard show method. For instance, a CTDdata created using `query_ctd_chem` shows:

```
Object of class 'CTDdata'
-----
. Type: CHEMICAL
. Creation (timestamp): 2018-03-13 13:11:50
. Length: 2
. Items: IRON, ..., AIR POLLUTANTS
. Diseases: 1755 ( 203 / 3322 )
. Chemical-gene interactions: 2070 ( 2799 )
. KEGG pathways: 637 ( 637 )
. GO terms: 3641 ( 3641 )
```

The information shows corresponds to:

- **Type:** Indicates the source (chemical, gene or disease) used to create the object.
- **Creation:** Shows the time-stamp from the creation time.
- **Length:** Shows the number of terms used to create the object.
- **Items:** Shows some of the terms used to create the object.
- **Diseases:** Corresponds to the unique number of diseases obtained in the query. In parenthesis: number of curated chemical-diseases and total number of chemical-diseases association.
- **Chemical-gene interactions:** Indicates the unique number of chemical-gene interactions. In parenthesis the total number of chemical-gene interactions.
- **KEGG pathways:** Shows the unique number of KEGG pathway versus chemical associations. In parenthesis the total number of associations.
- **GO terms:** Shows the unique number of GO terms versus chemical associations. In parenthesis the total number of associations.

CTDdata objects allows many types of representation according to the different sources (chemical, gene or disease). The used method is `plot`, matching the argument `x` with a CTDdata object. The argument `index_name` indicates the type of plot to be draw. The default value of `index_name` is "base".

- "base": shows a bar-plot indicating the number of lost & found terms for the given object.

For *gene* queries, `index_name` can take values:

- "disease": (argument representation must be "heatmap") shows shows the inference score that associates the given genes with diseases according to CTDbase.
- "chemical interactions": (argument representation must be "heatmap") shows the number of reference that cites the association between the given genes and chemicals.
- "gene-gene interaction": (argument representation can be "network" and "heatmap") in the network representation teh original genes are dark-colored while the other genes are light-colored. Both plots allows to to explore the gene-gene interactions.
- "kegg pathways": (argument representation must be "network") shows the linked between genes and KEGG pathways.
- "go terms": (argument representation must be "network") shows the links between genes and GO terms.

For *chemical* queries, `index_name` can take values:

- "gene interactions": (argument representation can be "network" and "heatmap") shows the gene-chemical interactions. Network representation includes the "mechanism" of the interactions.
- "disease": (argument representation can be "network" and "heatmap") shows the inference score of the link between chemicals and diseases.
- "kegg pathways": (argument representation must be "network") shows the P-Value of relation between KEGG pathways and chemicals.
- "go terms": (argument representation must be "network") shows the P-Value of relation between GO terms and chemicals.

For *disease* queries, `index_name` can take values:

- "gene": (argument representation must be "heatmap") shows the number of references linking a set of genes with a set of diseases.
- "chemical": (argument representation must be "heatmap"): shows the inference-score linking diseases with chemicals.
- "kegg pathways": (argument representation must be "network") shows the pathways linked to a set of diseases.

The other arguments of `plot` functions follows:

- `subset.chemical`: filters the chemicals to be include into the plot.
- `subset.gene`: filters the genes to be include into the plot.
- `subset.pathway`: filters the KEGG pathways or GO terms included into the plot.
- `subset.source`: filters the origin in gene-gene interaction network.
- `subset.target`: filters the end in gene-gene interaction network.
- `field.score`: can take values "Inference" or "Reference" depending of the used source and representation.

- `filter.score`: allows to filter the relations to be included into the plot in base of the set of `field.score`.
- `max.length`: indicates the maximum number of characters of the names of each "item" in the plot.
- `ontology`: for the KEGG pathways, allows to filter the pathways in base of their ontology. By default: `c("Biological Process", "Cellular Component", "Molecular Function")`.
- `main`: title to be displayed in network representations. For heatmap representations use: `+ ggtitle("TITLE")`.

Value

An object of class CTDdata

Methods (by generic)

- `enrich`: Method to perform enrichment analysis given two object of class CTDdata.
- `get_table`: Method to obtain a specific inner table from an CTDdata object.
- `get_terms`: Return a list with the terms found to create the object.
- `plot`: Generates a basic plot showing the number of terms that can be used to query CTDbase.

Slots

`timestamp` Character with the timestamp.

`type` Character saving "GENE", "CHEMICAL" or "DISEASE" depending if it was created using [query_ctd_gene](#), [query_ctd_chem](#) or [query_ctd_dise](#)

`terms` DataFrame with the genes, chemicals or diseases used to create the object.

`losts` Character with the terms used to create the object but that were nor present in CTDbase.

`gene_interactions` (Only for chemicals) Table with a relation of the genes interacting with the given chemicals.

`chemicals_interactions` (Only for genes) Table with a relation of the chemicals interacting with the given genes.

`diseases` Table with a relation of the diseases associated with given genes or chemicals.

`gene_gene_interactions` (Only for genes) Table with a relation of the genes interacting with the given genes.

`kegg` Table with a relation of the KEGG pathways affected by the given chemicals or where the given genes play a role.

`go` Table with a relation of the GO terms affected by the given chemicals or where the given genes play a role.

See Also

[query_ctd_gene](#) to create a CTDdata from a set of genes, [query_ctd_chem](#) to create a CTDdata from a set of chemicals, [query_ctd_dise](#) to create a CTDdata from a set of diseases, [get_table](#) to retrieve encapsulated data and [plot](#) to get nice plots from stored data.

CTDquerier	<i>Package for CTDBase data query, data visualization and data analysis.</i>
------------	--

Description

It can retrieve information related to genes, chemicals and diseases.

Data Download

CTDquerier offers two functions to query CTDBase (<http://ctdbase.org>): [query_ctd_gene](#) to query CTDBase given a set of genes; and [query_ctd_chem](#) to query CTDBase given a set of chemicals. Both functions returns [CTDdata](#) objects. Raw downloaded information can be retrieved from [CTDdata](#) using method [get_table](#).

Data Visualization

[CTDdata](#) objects offers basic visualization of the downloaded information using standard plot method.

download_ctd_chem	<i>Function to download checmicals available in CTDBase</i>
-------------------	---

Description

This function download the "Chemical vocabulary" file (`CTD_chemicals.tsv.gz`) from <http://ctdbase.org/downloads>.

Usage

```
download_ctd_chem(verbose = FALSE, ask = TRUE)
```

Arguments

verbose	(default FALSE) If set to TRUE is shows relevant information of each step.
ask	(default TRUE) If TRUE it asks the the persistent location must be used.

Details

The field included in the file (`CTD_chemicals.tsv.gz`) are:

1. ChemicalName
2. ChemicalID (MeSH identifier)
3. CasRN (CAS Registry Number, if available)
4. Definition
5. ParentIDs (identifiers of the parent terms; '|'-delimited list),

6. TreeNumbers (identifiers of the chemical's nodes; '|'-delimited list),
7. ParentTreeNumbers (identifiers of the parent nodes; '|'-delimited list),
8. Synonyms ('|'-delimited list)
9. DrugBankIDs ('|'-delimited list)

Value

Passed name into filename argument if it could be download 1 otherwise.

Examples

```
download_ctd_chem()  
file.exists( "CTD_chemicals.tsv.gz" )
```

download_ctd_dise *Function to download diseases available in CTDBase*

Description

This function download the "Disease vocabulary" file (CTD_diseases.tsv.gz) from <http://ctdbase.org/downloads>.

Usage

```
download_ctd_dise(verbose = FALSE, ask = TRUE)
```

Arguments

verbose (default FALSE) If set to TRUE is shows relevant information of each step.
ask (default TRUE) If TRUE it asks the the persistent location must be used.

Details

The field included in the file (CTD_diseases.tsv.gz) are:

1. DiseaseName
2. DiseaseID (MeSH or OMIM identifier)
3. Definition
4. AltDiseaseIDs (alternative identifiers; '|'-delimited list)
5. ParentIDs (identifiers of the parent terms; '|'-delimited list)
6. TreeNumbers (identifiers of the disease's nodes; '|'-delimited list)
7. ParentTreeNumbers (identifiers of the parent nodes; '|'-delimited list)
8. Synonyms ('|'-delimited list)
9. SlimMappings (MEDIC-Slim mappings; '|'-delimited list)

Value

Passed name into filename argument if it could be download 1 otherwise.

Examples

```
download_ctd_dise()  
file.exists( "CTD_diseases.tsv.gz" )
```

download_ctd_genes *Function to download genes available in CTDbase*

Description

This function download the "Gene vocabulary" file (CTD_genes.tsv.gz) from <http://ctdbase.org/downloads>.

Usage

```
download_ctd_genes(verbose = FALSE, ask = TRUE)
```

Arguments

verbose (default FALSE) If set to TRUE is shows relevant information of each step.
ask (default TRUE) If TRUE it asks the the persistent location must be used.

Details

The field included in the file (CTD_genes.tsv.gz) are:

1. GeneSymbol
2. GeneName
3. GeneID (NCBI Gene identifier)
4. AltGeneIDs (alternative NCBI Gene identifiers; '|' -delimited list)
5. Synonyms ('|' -delimited list)
6. BioGRIDIDs ('|' -delimited list)
7. PharmGKBIDs ('|' -delimited list)
8. UniprotIDs ('|' -delimited list)

Value

Passed name into filename argument if it could be download 1 otherwise.

Examples

```
download_ctd_genes()
```

enrich	<i>Method to perform enrichment analysis using two CTDdata objects</i>
--------	--

Description

This methods performs a fisher test using the genes in two objects of class `CTDdata`. The object in 'x' is used as source while the object on 'y' is used as universe. When object 'x' corresponds to an object created with `query_ctd_gene`, the used genes are the found terms in CTDBase. In the other cases (chemicals and disease `CTDdata`), the genes from the 'gene interactions' table are used. If universe is missing, all genes in CTDBase are used as universe.

Usage

```
enrich(x, y, universe, use = "curated", warnings = TRUE, ...)
```

Arguments

x	Object of class <code>CTDdata</code> .
y	Object of class <code>CTDdata</code> .
universe	Vector of strings corresponding to the genes to be used as universe.
use	(default: "curated") It can take values "curated" or "all" to filter or not filter for curated the genes into the <code>CTDdata</code> objects.
warnings	(default: TRUE).
...	NOT USED

Value

A list with class `htest`. Check `fisher.test` for more information.

Examples

```
data("gala")
air <- query_ctd_chem( terms = "Air Pollutants" )
hgnc_universe <- readRDS(paste0(path.package("CTDquerier"),"/extdata/universe.RDS"))
enrich(gala, air, hgnc_universe)
```

gala	CTDdata <i>for illustrative purposes</i>
------	--

Description

CTDdata with information of 258 genes downloaded from CTDBase. The object was created from from the genes obtained from the scientific article entitled "Case-control admixture mapping in Latino populations enriches for known asthma-associated genes" (Table E1) by Torgerson et. al. The genes were used to query CTDBase using query_ctd_genes function.

Usage

```
data("gala")
```

Format

An object of class CTDdata of length 1.

Value

An CTDdata object.

Examples

```
data("gala")
gala
```

get_table	<i>Method to obtain a specific inner table from a CTDdata object.</i>
-----------	---

Description

Obtain the raw data from a CTDdata object, result from a query to CTDBase.

Usage

```
get_table(object, index_name, ...)
```

Arguments

object	Object of class CTDdata.
index_name	String indicating the type of data to obtain.
...	NOT USED

Details

Available tables are (index_name):

1. "gene interactions": (Only for chemicals) Table with a relation of the genes interacting with the given chemicals.
2. "chemical interactions": (Only for genes) Table with a relation of the chemicals interacting with the given genes.
3. "diseases": Table with a relation of the diseases associated with given genes or chemicals.
4. "gene-gene interactions": (Only for genes) Table with a relation of the genes interacting with the given genes.
5. "kegg pathways": Table with a relation of the KEGG pathways affected by the given chemicals or where the given genes play a role.
6. "go terms": Table with a relation of the GO terms affected by the given chemicals or where the given genes play a role.

Value

A DataFrame containing the raw result from CTDData.

Examples

```
data("gala")
get_table(gala, "diseases")[1:3, ]
```

get_terms

Getter to obtain the terms used to perform a query into CTDBase

Description

Getter to obtain the terms used to perform a query into CTDBase

Usage

```
get_terms(object)
```

Arguments

object Object of class [CTDData](#).

Value

A list with two accessors: "used" for the terms that exists in CTDBase, and "lost" with the terms that do not exists in CTDBase.

Examples

```
data("gala")
get_terms(gala)[["lost"]]
```

leaf_plot	<i>Function to create a leaf plot</i>
-----------	---------------------------------------

Description

This functions takes a data.frame and returns a gtable with three plots. The left-leafes, the axis names and the right-leafes.

Usage

```
leaf_plot(  
  dta,  
  label = "name",  
  valueLeft = "var1",  
  valueRight = "var2",  
  titleLeft = NULL,  
  titleRight = NULL,  
  colorLeft = "#FF7F50",  
  colorRight = "#20B2AA"  
)
```

Arguments

dta	data.frame with, at last, three columns corresponding to the axis labels, the left values and the right values.
label	(default "name") Name of the column in dta with the labels.
valueLeft	(default "var1") Name of the column with the values for the left plot.
valueRight	(default "var2") Name of the column with the values for the right plot.
titleLeft	(default NULL) Character used as a title for the left plot.
titleRight	(default NULL) Character used as a title for the right plot.
colorLeft	(default "#FF7F50") Color for left plot bars.
colorRight	(default "#20B2AA") Color for right plot bars.

Value

A ggplot2 object.

Examples

```
data <- data.frame(  
  labels = LETTERS[1:15],  
  right = runif(n = 15) * 11,  
  left = runif(n = 15) * 9  
)  
leaf_plot( data, "labels", "left", "right", "runif09", "runif11")
```

load_ctd_chem	<i>Function to load the .tsv.gz file for chemicals</i>
---------------	--

Description

Function to load the .tsv.gz file for chemicals

Usage

```
load_ctd_chem(verbose = FALSE)
```

Arguments

verbose (default FALSE) If set to TRUE messages and warnings are raised.

Details

The field included in the file (CTD_chemicals.tsv.gz) are:

1. ChemicalName
2. ChemicalID (MeSH identifier)
3. CasRN (CAS Registry Number, if available)
4. Definition
5. ParentIDs (identifiers of the parent terms; '|' -delimited list),
6. TreeNumbers (identifiers of the chemical's nodes; '|' -delimited list),
7. ParentTreeNumbers (identifiers of the parent nodes; '|' -delimited list),
8. Synonyms ('|' -delimited list)
9. DrugBankIDs ('|' -delimited list)

Value

A data.frame with the content of the file "CTD_genes.tsv.gz"

Examples

```
if(download_ctd_chem()){  
  fd1 <- load_ctd_chem()  
  dim( fd1 )  
}
```

load_ctd_dise	<i>Function to load the .tsv.gz file for disease</i>
---------------	--

Description

Function to load the .tsv.gz file for disease

Usage

```
load_ctd_dise(verbose = FALSE)
```

Arguments

verbose (default FALSE) If set to TRUE messages and warnings are raised.

Details

The field included in the file (CTD_diseases.tsv.gz) are:

1. DiseaseName
2. DiseaseID (MeSH or OMIM identifier)
3. Definition
4. AltDiseaseIDs (alternative identifiers; '|' -delimited list)
5. ParentIDs (identifiers of the parent terms; '|' -delimited list)
6. TreeNumbers (identifiers of the disease's nodes; '|' -delimited list)
7. ParentTreeNumbers (identifiers of the parent nodes; '|' -delimited list)
8. Synonyms ('|' -delimited list)
9. SlimMappings (MEDIC-Slim mappings; '|' -delimited list)

Value

A data.frame with the content of the file "CTD_genes.tsv.gz"

Examples

```
if(download_ctd_dise()){  
  fd1 <- load_ctd_dise()  
  dim( fd1 )  
}
```

load_ctd_gene	<i>Function to load the .tsv.gz file for genes</i>
---------------	--

Description

This function works in pair with [download_ctd_genes](#). This function loads into the R session the downloaded "CTD_genes.tsv.gz" file.

Usage

```
load_ctd_gene(verbose = FALSE)
```

Arguments

verbose (default FALSE) If set to TRUE messages and warnings are raised.

Details

The field included in the file (CTD_genes.tsv.gz) are:

1. GeneSymbol
2. GeneName
3. GeneID (NCBI Gene identifier)
4. AltGeneIDs (alternative NCBI Gene identifiers; '|'-delimited list)
5. Synonyms ('|'-delimited list)
6. BioGRIDIDs ('|'-delimited list)
7. PharmGKBIDs ('|'-delimited list)
8. UniprotIDs ('|'-delimited list)

Value

A data.frame with the content of the file "CTD_genes.tsv.gz"

Examples

```
if(download_ctd_genes()){  
  fd1 <- load_ctd_gene()  
  dim( fd1 )  
}
```

query_ctd_chem	<i>Function to query CTDbase using chemical terminology (Chemical Name)</i>
----------------	---

Description

This function checks for CTDbase gene vocabulary and query CTDbase for each one, downloading chemical-genes interactions, associated diseases, associated KEGG pathways and associated GO terms.

Usage

```
query_ctd_chem(terms, max.distance = 10, ask = FALSE, verbose = FALSE)
```

Arguments

terms	Character vector with the chemicals used in the query.
max.distance	(default 10) Maximum distance allowed between a given element in terms argument and a possible match in CTDbase.
ask	(default TRUE) If TRUE it asks the the persistent location must be used to save the vocabulary if it was not downloaded previously.
verbose	(default FALSE) If set to TRUE is shows relevant information of each step.

Value

An object of class [CTDdata](#).

Examples

```
rst <- query_ctd_chem( terms = c( "Iron", "Air Pollutants" ), verbose = TRUE )
```

query_ctd_dise	<i>Function to query CTDbase using disease terminology</i>
----------------	--

Description

This function checks for CTDbase disease vocabulary and query CTDbase for each one, downloading disease-gene interactions, chemicals interactions, associated diseases, associated KEGG pathways and associated GO terms.

Usage

```
query_ctd_dise(terms, ask = TRUE, verbose = FALSE)
```


Arguments

terms	Character vector with the diseases used in the query.
ask	(default TRUE) If TRUE it asks the the persistent location must be used to save the vocabulary if it was not downloaded previously.
verbose	(default FALSE) If set to TRUE is shows relevant information of each step.

Value

An object of class `CTDdata`.

Examples

```
rst <- query_ctd_dise( terms = "Asthma", verbose = TRUE )
```

query_ctd_gene	<i>Function to query CTDbase using gene terminology (Gene Symbol)</i>
----------------	---

Description

This function checks for CTDbase gene vocabulary and query CTDbase for each one, downloading gene-gene interactions, chemicals interactions, associated disease, associated KEGG pathways and associated GO terms.

Usage

```
query_ctd_gene(terms, ask = TRUE, verbose = FALSE)
```

Arguments

terms	Character vector with the genes used in the query.
ask	(default TRUE) If TRUE it asks the the persistent location must be used to save the vocabulary if it was not downloaded previously.
verbose	(default FALSE) If set to TRUE is shows relevant information of each step.

Value

An object of class `CTDdata`.

Examples

```
rst <- query_ctd_gene( terms = c( "APP", "HMOX1A", "hmox1" ), verbose = TRUE )
```

Index

* datasets

gala, [10](#)

CTDdata, [2](#), [3](#), [6](#), [9](#), [11](#), [16](#), [17](#)

CTDdata-class (CTDdata), [2](#)

CTDquerier, [6](#)

download_ctd_chem, [6](#)

download_ctd_dise, [7](#)

download_ctd_genes, [8](#), [15](#)

enrich, [9](#)

enrich,CTDdata-method (CTDdata), [2](#)

gala, [10](#)

get_table, [5](#), [6](#), [10](#)

get_table,CTDdata-method (CTDdata), [2](#)

get_terms, [11](#)

get_terms,CTDdata-method (CTDdata), [2](#)

leaf_plot, [12](#)

load_ctd_chem, [13](#)

load_ctd_dise, [14](#)

load_ctd_gene, [15](#)

plot,CTDdata,ANY-method (CTDdata), [2](#)

query_ctd_chem, [2](#), [5](#), [6](#), [16](#)

query_ctd_dise, [2](#), [5](#), [16](#)

query_ctd_gene, [2](#), [5](#), [6](#), [9](#), [17](#)