Package 'IsoCorrectoR'

October 18, 2022

Title Correction for natural isotope abundance and tracer purity in MS and MS/MS data from stable isotope labeling experiments

Version 1.14.0

Imports dplyr, magrittr, methods, quadprog, readr, readxl, stringr, tibble, tools, utils, pracma, WriteXLS

Description IsoCorrectoR performs the correction of mass spectrometry data from stable isotope labeling/tracing metabolomics experiments with regard to natural isotope abundance and tracer impurity. Data from both MS and MS/MS measurements can be corrected (with any tracer isotope: 13C, 15N, 18O...), as well as ultra-high resolution MS data from multiple-tracer experiments (e.g. 13C and 15N used simultaneously). See the Bioconductor package IsoCorrectoRGUI for a graphical user interface to IsoCorrectoR. NOTE: With R version 4.0.0, writing correction results to Excel files may currently not work on Windows. However, writing results to csv works as before.

Depends R (>= 3.5)

URL https://genomics.ur.de/files/IsoCorrectoR/

License GPL-3 LazyData TRUE

NeedsCompilation no

biocViews Software, Metabolomics, MassSpectrometry, Preprocessing, ImmunoOncology

RoxygenNote 6.1.1

Suggests IsoCorrectoRGUI, knitr, rmarkdown, testthat

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/IsoCorrectoR

git_branch RELEASE_3_15

git_last_commit e90ecec

git_last_commit_date 2022-04-26

Date/Publication 2022-10-18

Author Christian Kohler [cre, aut],

Paul Heinrich [aut]

Maintainer Christian Kohler < christian.kohler@ur.de>

2 IsoCorrection

R topics documented:

	IsoCorrection IsoCorrectoR																						
Index																							6
IsoCorrection				lgo						•							ur	ity	, (— Со	rre	ec-	_

Description

IsoCorrection is the main function of the IsoCorrectoR package. It performs the correction of mass spectrometry data from stable isotope labeling experiments with regard to natural abundance and tracer purity. Data from both MS and MS/MS experiments can be corrected (with any tracer isotope: 13C, 15N, 18O...), as well as high resolution data from multiple-tracer experiments (e.g. 13C and 15N used simultaneously).

Usage

```
IsoCorrection(MeasurementFile = NA, ElementFile = NA, MoleculeFile = NA,
   CorrectTracerImpurity = FALSE, CorrectTracerElementCore = TRUE,
   CalculateMeanEnrichment = TRUE, UltraHighRes = FALSE, DirOut = ".",
   FileOut = "result", FileOutFormat = "csv", ReturnResultsObject = TRUE,
   CorrectAlsoMonoisotopic = FALSE, CalculationThreshold = 10^-8,
   CalculationThreshold_UHR = 8, verbose = FALSE, Testmode = FALSE)
```

Arguments

 ${\tt MeasurementFile}$

Required. The file that contains the measured data to be corrected. Only ".xls", ".xlsx" and ".csv" file formats are supported.

ElementFile Required. The file that contains the element information required for correction.

Only ".xls", ".xlsx" and ".csv" file formats are supported.

MoleculeFile Required. The file that contains the information on the molecules for which data is to be corrected. Only ".xls", ".xlsx" and ".csv" file formats are supported.

CorrectTracerImpurity

Logical. If TRUE, correction for isotopic impurity of the tracer substrate is performed.

CorrectTracerElementCore

Logical. If TRUE (recommended!), the tracer element atoms in the core module (usually the part of the molecule that does not come from derivatization) are considered when correcting.

CalculateMeanEnrichment

Logical. If TRUE, the mean isotopic enrichment is calculated for each molecule.

IsoCorrection 3

UltraHighRes Logical. If TRUE, high resolution correction is performed on the data. Should

only be set to TRUE, if you know that you have high resolution data.

DirOut Character String. Defines the directory the corrected data and log-file should be

written to. Default directory is set to current working directoy ('.').

FileOut Character String. Defines the name of the file that contains the corrected data.

The name of the fill will be IsoCorrectoR_<FileOut>.<FileFormat>. If the format is set to "csv", the name will also contain the type of the corrected data in

the respective file.

FileOutFormat Character String. Defines the format of the files that contain the corrected data.

Can either be "csv" or "xls". If set to "csv", multiple files will be generated, one for each type of corrected data (eg. corrected data, fractions, mean enrichment...). If set to "xls", all correction results are provided in one excel file in

different sheets.

ReturnResultsObject

Logical. If TRUE, the correction results are returned as a list in the current R_session in addition to writing the results to a file. This is useful if the corrected

data has to be further processed directly in R.

CorrectAlsoMonoisotopic

Logical. If TRUE, monoisotopic correction results are also provided.

CalculationThreshold

(Advanced Option) Numeric. Defines a threshold to stop probability calculations at for making correction faster (normal resolution mode). Should be left at

the default value.

CalculationThreshold_UHR

(Advanced Option) Numeric. Defines a threshold to stop probability calculations at for making correction faster (high resolution mode). Should be left at

the default value.

verbose Logical. If TRUE, status messages are sent to standard output.

Testmode Logical. If TRUE, starts a testmode for development purposes. Not required for

users of IsoCorrectoR.

Value

The function returns a list with 4 elements

success: string that is "TRUE" if the correction was successful, "FALSE" if an error occured and "WARNINGS" if warnings occured

results: a list containing a dataframe for each type of corrected data (normal, fractions, mean enrichment ...). Will be NA if ReturnResultsObject is set to FALSE

log: list containing log information on the correction run (parameters, file names and paths, warnings and errors)

error: contains a string with the associated error message if an error occurred, empty otherwise

References

See Reference 1 LinktoIsoCorrectoR-Paper

4 IsoCorrectoR

Examples

```
# Normal resolution data
   # 1) get path of example files
  path.molecule <- system.file("extdata","normal_resolution","MoleculeFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  path.element <- system.file("extdata", "normal_resolution", "ElementFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  path.measurement <- system.file("extdata", "normal_resolution", "MeasurementFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  # 2) run correction algorithm and save results in variable
  correctionResults <- IsoCorrection(MeasurementFile=path.measurement,</pre>
      ElementFile=path.element,
     MoleculeFile=path.molecule)
# High resolution data
  # 1) get path of example files
  path.molecule <- system.file("extdata","high_resolution","MoleculeFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  path.element <- system.file("extdata", "high_resolution", "ElementFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  path.measurement <- system.file("extdata","high_resolution","MeasurementFile.csv",</pre>
      package = "IsoCorrectoR", mustWork = TRUE);
  # 2) run correction algorithm and save results in variable
  correctionResults <- IsoCorrection(MeasurementFile=path.measurement,</pre>
      ElementFile=path.element,
     MoleculeFile=path.molecule,UltraHighRes=TRUE)
```

IsoCorrectoR

IsoCorrectoR example data

Description

Example data for the IsoCorrectoR package

Usage

data(IsoCorrectoR)

Format

A list with four elements, namely

tool_features: overview of correction features as provided by various tools IsoCorrectoR is compared with.

IsoCorrectoR 5

element_file: example data for an Element file. This information is independent of the resolution type (normal or high)

normal_resolution: list with two elements, containing examples for normal resolution data: molecule information and measurement data

high_resolution: list with two elements, containing examples for high resolution data: molecule information and measurement data

Author(s)

Paul Heinrich, Christian Kohler

Index