

# Package ‘MultiAssayExperiment’

October 18, 2022

**Title** Software for the integration of multi-omics experiments in Bioconductor

**Version** 1.22.0

**Description** MultiAssayExperiment harmonizes data management of multiple experimental assays performed on an overlapping set of specimens. It provides a familiar Bioconductor user experience by extending concepts from SummarizedExperiment, supporting an open-ended mix of standard data classes for individual assays, and allowing subsetting by genomic ranges or rownames. Facilities are provided for reshaping data into wide and long formats for adaptability to graphing and downstream analysis.

**Depends** R (>= 4.2.0), SummarizedExperiment (>= 1.3.81)

**Imports** methods, GenomicRanges (>= 1.25.93), BiocGenerics, S4Vectors (>= 0.23.19), IRanges, Biobase, stats, tidy, utils

**Suggests** BiocStyle, HDF5Array (>= 1.19.17), knitr, maftools (>= 2.7.10), rmarkdown, R.rsp, RaggedExperiment, UpSetR, survival, survminer, testthat

**biocViews** Infrastructure, DataRepresentation

**License** Artistic-2.0

**Encoding** UTF-8

**VignetteBuilder** knitr, R.rsp

**URL** <http://waldronlab.io/MultiAssayExperiment/>

**Video** <https://youtu.be/w6HWAHaDpyk>, <https://youtu.be/Vh0hVVUKKFM>

**BugReports** <https://github.com/waldronlab/MultiAssayExperiment/issues>

**Collate** 'ExperimentList-class.R' 'MultiAssayExperiment-class.R'  
'MatchedAssayExperiment-class.R' 'subsetBy-methods.R'  
'MultiAssayExperiment-subset.R'  
'MultiAssayExperiment-methods.R'  
'MultiAssayExperiment-helpers.R' 'MultiAssayExperiment-pkg.R'  
'MultiAssayExperimentToMAFR.R' 'assay-methods.R' 'data.R'  
'hasAssay.R' 'listToMap.R' 'mapToList.R' 'prepMultiAssay.R'  
'reexports.R' 'saveHDF5MultiAssayExperiment.R' 'upsetSamples.R'  
'utilities.R'

**RoxygenNote** 7.1.2

**git\_url** <https://git.bioconductor.org/packages/MultiAssayExperiment>

**git\_branch** RELEASE\_3\_15

**git\_last\_commit** e1aeb73

**git\_last\_commit\_date** 2022-04-26

**Date/Publication** 2022-10-18

**Author** Marcel Ramos [aut, cre] (<<https://orcid.org/0000-0002-3242-0582>>),  
Levi Waldron [aut],  
MultiAssay SIG [ctb]

**Maintainer** Marcel Ramos <[marcel.ramos@roswellpark.org](mailto:marcel.ramos@roswellpark.org)>

## R topics documented:

MultiAssayExperiment-package . . . . .	2
ExperimentList . . . . .	3
ExperimentList-class . . . . .	5
hasAssay . . . . .	7
listToMap . . . . .	7
MatchedAssayExperiment-class . . . . .	8
miniACC . . . . .	9
MultiAssayExperiment . . . . .	10
MultiAssayExperiment-class . . . . .	12
MultiAssayExperiment-helpers . . . . .	16
MultiAssayExperiment-methods . . . . .	21
MultiAssayExperimentToMAF . . . . .	24
prepMultiAssay . . . . .	25
reexports . . . . .	26
saveHDF5MultiAssayExperiment . . . . .	26
subsetBy . . . . .	28
upsetSamples . . . . .	31
<b>Index</b>	<b>33</b>

---

MultiAssayExperiment-package

*MultiAssayExperiment: Build an integrative multi-assay container*

---

## Description

MultiAssayExperiment allows the manipulation of related multiassay datasets with partially overlapping samples, associated metadata at the level of an entire study, and at the level of the "biological unit". The biological unit may be a patient, plant, yeast strain, etc.

## Details

The package hierarchy of information:

- study
- experiments
- samples

## Author(s)

**Maintainer:** Marcel Ramos <marcel.ramos@roswellpark.org>

Authors:

- Levi Waldron <lwaldron.research@gmail.com>

Other contributors:

- MultiAssay SIG <biocmultiassay@googlegroups.com> [contributor]

## See Also

Useful links:

- <http://waldronlab.io/MultiAssayExperiment/>
- Report bugs at <https://github.com/waldronlab/MultiAssayExperiment/issues>

---

ExperimentList

*Represent multiple experiments as a List-derivative ExperimentList*

---

## Description

The ExperimentList class can contain several different types of data. The only requirements for an ExperimentList class are that the objects contained have the following set of methods: dim, [, dimnames

## Usage

```
ExperimentList(...)
```

## Arguments

...                    A named list class object

## Value

A ExperimentList class object of experiment data

**Examples**

```

## Create an empty ExperimentList instance
ExperimentList()

## Create array matrix and AnnotatedDataFrame to create an ExpressionSet class
arraydat <- matrix(data = seq(101, length.out = 20), ncol = 4,
  dimnames = list(
    c("ENST00000294241", "ENST00000355076",
      "ENST00000383706", "ENST00000234812", "ENST00000383323"),
    c("array1", "array2", "array3", "array4")
  ))

colDat <- data.frame(slope53 = rnorm(4),
  row.names = c("array1", "array2", "array3", "array4"))

## SummarizedExperiment constructor
exprdat <- SummarizedExperiment::SummarizedExperiment(arraydat,
  colData = colDat)

## Create a sample methylation dataset
methyldat <- matrix(data = seq(1, length.out = 25), ncol = 5,
  dimnames = list(
    c("ENST00000355076", "ENST00000383706",
      "ENST00000383323", "ENST00000234812", "ENST00000294241"),
    c("methyl1", "methyl2", "methyl3",
      "methyl4", "methyl5")
  ))

## Create a sample RNASeqGene dataset
rnadat <- matrix(
  data = sample(c(46851, 5, 19, 13, 2197, 507,
    84318, 126, 17, 21, 23979, 614), size = 20, replace = TRUE),
  ncol = 4,
  dimnames = list(
    c("XIST", "RPS4Y1", "KDM5D", "ENST00000383323", "ENST00000234812"),
    c("samparray1", "samparray2", "samparray3", "samparray4")
  ))

## Create a mock RangedSummarizedExperiment from a data.frame
rangedat <- data.frame(chr="chr2", start = 11:15, end = 12:16,
  strand = c("+", "-", "+", "*", "."),
  samp0 = c(0,0,1,1,1), samp1 = c(1,0,1,0,1), samp2 = c(0,1,0,1,0),
  row.names = c(paste0("ENST", "00000", 135411:135414), "ENST00000383323"))

rangeSE <- SummarizedExperiment::makeSummarizedExperimentFromDataFrame(rangedat)

## Combine to a named list and call the ExperimentList constructor function
assayList <- list(Affy = exprdat, Methy1450k = methyldat, RNASeqGene = rnadat,
  GISTIC = rangeSE)

## Use the ExperimentList constructor
ExpList <- ExperimentList(assayList)

```

---

ExperimentList-class *ExperimentList* - A container for multi-experiment data The ExperimentList class is a container that builds on the SimpleList with additional checks for consistency in experiment names and length. It contains a SimpleList of experiments with sample identifiers. One element present per experiment performed. Convert from SimpleList or list to the multi-experiment data container. When using the **mergeReplicates** method, additional arguments are passed to the given simplify function argument (e.g., na.rm = TRUE)

---

## Description

ExperimentList - A container for multi-experiment data

The ExperimentList class is a container that builds on the SimpleList with additional checks for consistency in experiment names and length. It contains a SimpleList of experiments with sample identifiers. One element present per experiment performed.

Convert from SimpleList or list to the multi-experiment data container. When using the **mergeReplicates** method, additional arguments are passed to the given simplify function argument (e.g., na.rm = TRUE)

## Usage

```
## S4 method for signature 'ExperimentList'
show(object)

## S4 method for signature 'ExperimentList'
isEmpty(x)

## S4 method for signature 'ExperimentList'
dimnames(x)

## S4 method for signature 'ExperimentList'
mergeReplicates(x, replicates = list(), simplify = BiocGenerics::mean, ...)

## S4 method for signature 'ANY,missing'
assay(x, i, withDimnames = TRUE, ...)

## S4 method for signature 'ExperimentList'
assays(x, withDimnames = TRUE, ...)

## S4 method for signature 'ExperimentList,missing'
assay(x, i, withDimnames = TRUE, ...)

## S4 method for signature 'ExperimentList,numeric'
assay(x, i, withDimnames = TRUE, ...)
```

```
## S4 method for signature 'ExperimentList,character'
assay(x, i, withDimnames = TRUE, ...)
```

### Arguments

object, x	An <a href="#">ExperimentList</a> object
replicates	mergeReplicates: A list or <a href="#">LogicalList</a> where each element represents a sample and a vector of repeated measurements for the sample
simplify	A function for merging columns where duplicates are indicated by replicates
...	Additional arguments. See details for more information.
i	A scalar character or integer index
withDimnames	logical (default TRUE) whether to return dimension names

### Value

An [ExperimentList](#) class object

### Methods (by generic)

- show: Show method for [ExperimentList](#) class
- isEmpty: check for zero length across all experiments
- dimnames: Get the dimension names for an [ExperimentList](#) using [CharacterList](#)
- mergeReplicates: Apply the mergeReplicates method on the [ExperimentList](#) elements
- assay: Obtain the specified assay with a numeric or character reference
- assays: Get the assay data from each element in the [ExperimentList](#)

### coercion

Convert a list or S4 List to an [ExperimentList](#) using the `as()` function.

In the following example, x is either a list or [List](#):

```
\code{as(x, "ExperimentList")}
```

### Examples

```
ExperimentList()
```

---

hasAssay	<i>Checking assay method for any class</i>
----------	--

---

**Description**

The hasAssay function is intended for developers who would like to include new classes into a MultiAssayExperiment instance. It checks the methods tables of the assay function for the specified class of the argument.

**Usage**

```
hasAssay(object)
```

**Arguments**

object	A MultiAssayExperiment or named list object instance
--------	--

**Value**

A logical value indicating method availability

**Examples**

```
lst <- structure(list(), .Names=character())  
hasAssay(lst)
```

---

listToMap	<i>Convert map from data.frame or DataFrame to list and vice versa</i>
-----------	--

---

**Description**

The mapToList function provides a convenient way of reordering a data.frame to a list. The listToMap function does the opposite by taking a list and converting it to DataFrame.

**Usage**

```
listToMap(listmap)
```

```
mapToList(dfmap, assayCol = "assay")
```

**Arguments**

listmap	A named list object containing DataFrames with "primary" and "colname" columns
dfmap	A data.frame or DataFrame object with identifiers in the first column
assayCol	A character vector of length one indicating the assay names column

**Value**

A [DataFrame](#) class object of names  
A list object of DataFrames for each assay

**Functions**

- `listToMap`: The inverse of the `listToMap` operation

**Examples**

```
example("MultiAssayExperiment")

## Create a sampleMap from a list using the listToMap function
sampMap <- listToMap(maplist)

## The inverse operation is also available
maplist <- mapToList(sampMap)
```

---

MatchedAssayExperiment-class

*MatchedAssayExperiment - A matched-samples MultiAssayExperiment class*

---

**Description**

This class supports the use of matched samples where an equal number of observations per biological unit are present in all assays.

**Usage**

```
MatchedAssayExperiment(...)
```

**Arguments**

... Either a single `MultiAssayExperiment` or the components to create a valid `MultiAssayExperiment`

**Value**

A `MatchedAssayExperiment` object

**Functions**

- `MatchedAssayExperiment`: Construct a `MatchedAssayExperiment` class from [MultiAssayExperiment](#)

**See Also**

[MultiAssayExperiment](#)



## Examples

```
data("miniACC")
acc <- as(miniACC, "MatchedAssayExperiment")
acc
```

---

miniACC

*Adrenocortical Carcinoma (ACC) MultiAssayExperiment*

---

## Description

A [MultiAssayExperiment](#) object providing a reduced version of the TCGA ACC dataset for all 92 patients. RNA-seq, copy number, and somatic mutations are included only for genes whose proteins are included in the reverse-phase protein array. The MicroRNA-seq dataset is also included, with infrequently expressed microRNA removed. Clinical, pathological, and subtype information are provided by `colData(miniACC)`, and some additional details are provided by `metadata(miniACC)`.

## Usage

```
miniACC
```

## Format

A `MultiAssayExperiment` with 5 experiments, providing:

**RNASeq2GeneNorm** RNA-seq count data: an `ExpressionSet` with 198 rows and 79 columns

**gistic2** Recurrent copy number lesions identified by GISTIC2: a `SummarizedExperiment` with 198 rows and 90 columns

**RPPAArray** Reverse Phase Protein Array: an `ExpressionSet` with 33 rows and 46 columns.

Rows are indexed by genes, but protein annotations are available from `featureData(miniACC[["RPPAArray"]])`.

The source of these annotations is noted in `abstract(miniACC[["RPPAArray"]])`

**Mutations** Somatic mutations: a matrix with 223 rows and 90 columns. 1 for any kind of non-silent mutation, zero for silent (synonymous) or no mutation.

**miRNASeqGene** microRNA sequencing: an `ExpressionSet` with 471 rows and 80 columns. Rows not having at least 5 counts in at least 5 samples were removed.

## Author(s)

Levi Waldron <lwaldron.research@gmail.com>

## Source

<https://github.com/waldronlab/multiassayexperiment-tcga>

## References

Zheng S \*et al.\*: Comprehensive Pan-Genomic Characterization of Adrenocortical Carcinoma. *Cancer Cell* 2016, 29:723-736.

**Examples**

```

data("miniACC")
metadata(miniACC)
colnames(colData(miniACC))
table(miniACC$vital_status)
longFormat(
  miniACC["MAPK3", , ],
  colDataCols = c("vital_status", "days_to_death")
)

wideFormat(
  miniACC["MAPK3", , ],
  colDataCols = c("vital_status", "days_to_death")
)

```

---

MultiAssayExperiment *Construct an integrative representation of multi-omic data with MultiAssayExperiment*

---

**Description**

The constructor function for the [MultiAssayExperiment-class](#) combines multiple data elements from the different hierarchies of data (study, experiments, and samples). It can create instances where neither a `sampleMap` or a `colData` set is provided. Please see the `MultiAssayExperiment` API documentation for more information.

**Usage**

```

MultiAssayExperiment(
  experiments = ExperimentList(),
  colData = S4Vectors::DataFrame(),
  sampleMap = S4Vectors::DataFrame(assay = factor(), primary = character(), colname =
    character()),
  metadata = list(),
  drops = list()
)

```

**Arguments**

<code>experiments</code>	A list or <a href="#">ExperimentList</a> of all combined experiments
<code>colData</code>	A <a href="#">DataFrame</a> or <code>data.frame</code> of characteristics for all biological units
<code>sampleMap</code>	A <code>DataFrame</code> or <code>data.frame</code> of assay names, sample identifiers, and <code>colname</code> samples
<code>metadata</code>	An optional argument of "ANY" class (usually list) for content describing the experiments
<code>drops</code>	A list of unmatched information (included after subsetting)

**Value**

A MultiAssayExperiment object that can store experiment and phenotype data

**colData**

The 'colData' input can be either 'DataFrame' or 'data.frame' with subsequent coercion to DataFrame. The rownames in the 'colData' must match the colnames in the experiments if no sampleMap is provided.

**experiments**

The 'experiments' input can be of class [SimpleList](#) or 'list'. This input becomes the [ExperimentList](#). Each element of the input 'list' or 'List' must be named, rectangular with two dimensions, and have 'dimnames'.

**sampleMap**

The [sampleMap](#) can either be input as 'DataFrame' or 'data.frame' with eventual coercion to 'DataFrame'. The 'sampleMap' relates biological units and biological measurements within each assay. Each row in the 'sampleMap' is a single such link. The standard column names of the 'sampleMap' are "assay", "primary", and "colname". Note that the "assay" column is a factor corresponding to the names of each experiment in the 'ExperimentList'. In the case where these names do not match between the 'sampleMap' and the experiments, the documented experiments in the 'sampleMap' take precedence and experiments are dropped by the harmonization procedure. The constructor function will generate a 'sampleMap' in the case where it is not provided and this method may be a 'safer' alternative for creating the 'MultiAssayExperiment' (so long as the rownames are identical in the 'colData', if provided). An empty 'sampleMap' may produce empty experiments if the levels of the "assay" factor in the 'sampleMap' do not match the names in the 'ExperimentList'.

**See Also**

[MultiAssayExperiment-class](#)

**Examples**

```
## Run the example ExperimentList
example("ExperimentList")

## Create sample maps for each experiment
exprmap <- data.frame(
  primary = c("Jack", "Jill", "Barbara", "Bob"),
  colname = c("array1", "array2", "array3", "array4"),
  stringsAsFactors = FALSE)

methylmap <- data.frame(
  primary = c("Jack", "Jack", "Jill", "Barbara", "Bob"),
  colname = c("methyl1", "methyl2", "methyl3", "methyl4", "methyl5"),
  stringsAsFactors = FALSE)

rnamap <- data.frame(
```

```

primary = c("Jack", "Jill", "Bob", "Barbara"),
colname = c("sampparray1", "sampparray2", "sampparray3", "sampparray4"),
stringsAsFactors = FALSE)

gistmap <- data.frame(
  primary = c("Jack", "Bob", "Jill"),
  colname = c("samp0", "samp1", "samp2"),
  stringsAsFactors = FALSE)

## Combine as a named list and convert to a DataFrame
maplist <- list(Affy = exprmap, Methyl450k = methylmap,
  RNASeqGene = rnamap, GISTIC = gistmap)

## Create a sampleMap
sampMap <- listToMap(maplist)
## Create an example phenotype data
colDat <- data.frame(sex = c("M", "F", "M", "F"), age = 38:41,
  row.names = c("Jack", "Jill", "Bob", "Barbara"))

## Create a MultiAssayExperiment instance
mae <- MultiAssayExperiment(experiments = ExpList, colData = colDat,
  sampleMap = sampMap)

```

---

MultiAssayExperiment-class

*MultiAssayExperiment - An integrative multi-assay class for experiment data*

---

## Description

The `MultiAssayExperiment` class can be used to manage results of diverse assays on a collection of specimen. Currently, the class can handle assays that are organized instances of `SummarizedExperiment`, `ExpressionSet`, `matrix`, `RaggedExperiment` (inherits from `GRangesList`), and `RangedVcfStack`. Create new `MultiAssayExperiment` instances with the homonymous constructor, minimally with the argument `ExperimentList`, potentially also with the arguments `colData` (see section below) and `sampleMap`.

## Usage

```

## S4 method for signature 'MultiAssayExperiment'
show(object)

## S4 method for signature 'MultiAssayExperiment'
length(x)

## S4 method for signature 'MultiAssayExperiment'
names(x)

## S4 method for signature 'MultiAssayExperiment'

```

```

updateObject(object, ..., verbose = FALSE)

## S4 method for signature 'MultiAssayExperiment'
dimnames(x)

## S4 method for signature 'MultiAssayExperiment'
c(x, ..., sampleMap = NULL, mapFrom = NULL)

## S4 method for signature 'MultiAssayExperiment'
exportClass(
  object,
  dir = tempdir(),
  fmt,
  ext,
  match = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'MultiAssayExperiment'
assays(x, withDimnames = TRUE, ...)

## S4 method for signature 'MultiAssayExperiment,missing'
assay(x, i, withDimnames = TRUE, ...)

## S4 method for signature 'MultiAssayExperiment,numeric'
assay(x, i, withDimnames = TRUE, ...)

## S4 method for signature 'MultiAssayExperiment,character'
assay(x, i, withDimnames = TRUE, ...)

```

### Arguments

object, x	A MultiAssayExperiment object
...	Additional arguments for supporting functions. See details.
verbose	logical(1) Whether to print additional information (default TRUE)
sampleMap	c method: a sampleMap list or DataFrame to guide merge
mapFrom	Either a logical, character, or integer vector indicating the experiment(s) that have an identical colname order as the experiment input(s). If using a character input, the name must match exactly.
dir	character(1) A directory for saving exported data (default: 'tempdir()')
fmt	character(1) or function() Either a format character atomic as supported by 'write.table' either ('csv', or 'tsv') or a function whose first two arguments are 'object to save' and 'file location'
ext	character(1) A file extension supported by the format argument
match	logical(1) Whether to coerce the current object to a 'MatchedAssayExperiment' object (default: FALSE)

withDimnames	logical (default TRUE) whether to return dimension names included in the object
i	An integer or character scalar indicating the assay to return

### Details

The dots (...) argument allows the user to specify additional arguments in several instances.

- `subsetting []`: additional arguments sent to [findOverlaps](#).
- `mergeReplicates`: used to specify arguments for the `simplify` functional argument
- `assay`: may contain `withDimnames`, which is forwarded to assays
- `combining c`: compatible `MultiAssayExperiment` classes passed on to the [ExperimentList](#) constructor, can be a list, [List](#), or a series of named arguments. See the examples below.

### Value

A `MultiAssayExperiment` object

### Methods (by generic)

- `show`: Show method for a `MultiAssayExperiment`
- `length`: Get the length of `ExperimentList`
- `names`: Get the names of the `ExperimentList`
- `updateObject`: Update old serialized `MultiAssayExperiment` objects to new API
- `dimnames`: Get the dimension names for a `MultiAssayExperiment` object
- `c`: Add a supported data class to the `ExperimentList`
- `exportClass`: Export data from class to a series of text files
- `assays`: Obtain a [SimpleList](#) of assay data for all available experiments in the object
- `assay`: Convenience function for extracting the assay of the first element (default) in the `ExperimentList`. A numeric or character index can also be provided

### Slots

`ExperimentList` A [ExperimentList](#) class object for each assay dataset  
`colData` A `DataFrame` of all clinical/specimen data available across experiments  
`sampleMap` A `DataFrame` of translatable identifiers of samples and participants  
`metadata` Additional data describing the `MultiAssayExperiment` object  
`drops` A metadata list of dropped information

### colData

The `colData` slot is a collection of primary specimen data valid across all experiments. This slot is strictly of class `DataFrame` but arguments for the constructor function allow arguments to be of class `data.frame` and subsequently coerced.

## ExperimentList

The `ExperimentList` slot is designed to contain results from each experiment/assay. It contains a `SimpleList`.

## sampleMap

The `sampleMap` contains a `DataFrame` of translatable identifiers of samples and participants or biological units. The standard column names of the `sampleMap` are "assay", "primary", and "col-name". Note that the "assay" column is a factor corresponding to the names of each experiment in the `ExperimentList`. In the case where these names do not match between the `sampleMap` and the experiments, the documented experiments in the `sampleMap` take precedence and experiments are dropped by the harmonization procedure. The constructor function will generate a `sampleMap` in the case where it is not provided and this method may be a 'safer' alternative for creating the `MultiAssayExperiment` (so long as the rownames are identical in the `colData`, if provided). An empty `sampleMap` may produce empty experiments if the levels of the "assay" factor in the `sampleMap` do not match the names in the `ExperimentList`.

## coercion

Convert a list or `S4 List` to a `MultiAssayExperiment` object using the `as` function.

In the following example, `x` is either a list or `List`:

```
`as(x, "MultiAssayExperiment")`
```

Convert a `MultiAssayExperiment` to MAF class object using the `as` function.

In the following example, `x` is a `MultiAssayExperiment`:

```
`MultiAssayExperimentToMAF(x)`
```

## See Also

[MultiAssayExperiment-methods](#) for slot modifying methods, [MultiAssayExperiment API](#)

## Examples

```
example("MultiAssayExperiment")

## Subsetting
# Rows (i) Rows/Features in each experiment
mae[1, , ]
mae[c(TRUE, FALSE), , ]

# Columns (j) Rows in colData
mae[, rownames(colData(mae))[3:2], ]

# Assays (k)
mae[, , "Affy"]

## Complete cases (returns logical vector)
completes <- complete.cases(mae)
```

```

compMAE <- mae[, completes, ]
compMAE
colData(compMAE)

example("MultiAssayExperiment")

## Add an experiment
test1 <- mae[[1L]]
colnames(test1) <- rownames(colData(mae))

## Combine current MultiAssayExperiment with additional experiment
## (no sampleMap)
c(mae, newExperiment = test1)

test2 <- mae[[3L]]
c(mae, newExp = test2, mapFrom = 3L)

## Add experiment using experiment name in mapFrom
c(mae, RNASeqGeneV2 = test2, mapFrom = "RNASeqGene")

```

---

## MultiAssayExperiment-helpers

*A group of helper functions for manipulating and cleaning a MultiAssayExperiment*

---

### Description

A set of helper functions were created to help clean and manipulate a MultiAssayExperiment object. intersectRows also works for ExperimentList objects.

- `complete.cases`: Returns a logical vector corresponding to 'colData' rows that have data across all experiments
- `isEmpty`: Returns a logical TRUE value for zero length MultiAssayExperiment objects
- `intersectRows`: Takes all common rows across experiments, excludes experiments with empty rownames
- `intersectColumns`: A wrapper for `complete.cases` to return a MultiAssayExperiment with only those biological units that have measurements across all experiments
- `replicated`: A function that identifies multiple samples that originate from a single biological unit within each assay
- `anyReplicated`: Displays which assays have replicate measurements
- `mergeReplicates`: A function that combines replicated / repeated measurements across all experiments and is guided by the replicated return value
- `longFormat`: A MultiAssayExperiment method that returns a small and skinny [DataFrame](#). The `colDataCols` arguments allows the user to append colData columns to the data.



- wideFormat: A function to return a wide [DataFrame](#) where each row represents an observation. Optional colDataCols can be added when using a MultiAssayExperiment.
- hasRowRanges: A function that identifies ExperimentList elements that have a [rowRanges](#) method
- getWithColData: A convenience function for extracting an assay and associated colData
- renamePrimary: A convenience function to rename the primary biological units as represented in the rownames(colData)
- renameColname: A convenience function to rename the colnames of a particular assay

## Usage

```
## S4 method for signature 'MultiAssayExperiment'
complete.cases(...)

## S4 method for signature 'MultiAssayExperiment'
isEmpty(x)

intersectRows(x)

intersectColumns(x)

replicated(x)

## S4 method for signature 'MultiAssayExperiment'
replicated(x)

anyReplicated(x)

## S4 method for signature 'MultiAssayExperiment'
anyReplicated(x)

mergeReplicates(x, replicates = list(), simplify = BiocGenerics::mean, ...)

## S4 method for signature 'MultiAssayExperiment'
mergeReplicates(
  x,
  replicates = replicated(x),
  simplify = BiocGenerics::mean,
  ...
)

## S4 method for signature 'ANY'
mergeReplicates(x, replicates = list(), simplify = BiocGenerics::mean, ...)

longFormat(object, colDataCols = NULL, i = 1L)

wideFormat(
  object,
```

```

    colDataCols = NULL,
    check.names = TRUE,
    collapse = "_",
    i = 1L
)

hasRowRanges(x)

## S4 method for signature 'MultiAssayExperiment'
hasRowRanges(x)

## S4 method for signature 'ExperimentList'
hasRowRanges(x)

getWithColData(x, i, mode = c("append", "replace"), verbose = FALSE)

renamePrimary(x, value)

renameColname(x, i, value)

splitAssays(x, hitList)

## S4 method for signature 'MultiAssayExperiment'
splitAssays(x, hitList)

makeHitList(x, patternList)

```

### Arguments

...	Additional arguments. See details for more information.
x	A MultiAssayExperiment or ExperimentList
replicates	A list of <a href="#">LogicalLists</a> indicating multiple / duplicate entries for each biological unit per assay, see replicated (default replicated(x)).
simplify	A function for merging repeat measurements in experiments as indicated by the replicated method for MultiAssayExperiment
object	Any supported class object
colDataCols	A character, logical, or numeric index for colData columns to be included
i	longFormat: The i-th assay in <a href="#">SummarizedExperiment</a> -like objects. A vector input is supported in the case that the SummarizedExperiment object(s) has more than one assay (default 1L), renameColname: Either a numeric or character index indicating the assay whose colnames are to be renamed
check.names	(logical default TRUE) Column names of the output DataFrame will be checked for syntactic validity and made unique, if necessary
collapse	(character default "_") A single string delimiter for output column names. In wideFormat, experiments and rownames (and when replicate samples are present, colnames) are separated by this delimiter

mode	String indicating how <a href="#">MultiAssayExperiment</a> column-level metadata should be added to the <a href="#">SummarizedExperiment</a> colData.
verbose	logical(1) Whether to ‘suppressMessages’ on subsetting operations in ‘getWithColData’ (default FALSE)
value	renamePrimary: A character vector of the same length as the existing rownames(colData) to use for replacement, renameColname: A CharacterList or list with matching lengths to replace colnames(x)
hitList	a named list or List of logical vectors that indicate groupings in the assays
patternList	a named list or List of atomic character vectors that are the input to grep1 for identifying groupings in the assays

## Details

The replicated function finds replicate measurements in each assay and returns a list of [LogicalLists](#). Each element in a single [LogicalList](#) corresponds to a biological or *primary* unit as in the sampleMap. Below is a small graphic for one particular biological unit in one assay, where the logical vector corresponds to the number of measurements/samples in the assay:

```
> replicated(MultiAssayExperiment)
(list str)      '-- $ AssayName
(LogicalList str)  '-- [[ "Biological Unit" ]]
Replicated if sum(...) > 1      '-- TRUE TRUE FALSE FALSE
```

anyReplicated determines if any of the assays have at least one replicate. *Note.* These methods are not available for the ExperimentList class due to a missing sampleMap structure (by design).

The mergeReplicates function is a house-keeping method for a MultiAssayExperiment where only complete.cases are returned. This by-assay operation averages replicate measurements (by default) and columns are aligned by the row order in colData. Users can provide their own function for merging replicates with the simplify functional argument. Additional inputs ... are sent to the ‘simplify’ function.

The mergeReplicates "ANY" method consolidates duplicate measurements for rectangular data structures, returns object of the same class (endomorph). The ellipsis or ... argument allows the user to provide additional arguments to the simplify functional argument.

The longFormat "ANY" class method, works with classes such as [ExpressionSet](#) and [SummarizedExperiment](#) as well as matrix to provide a consistent long and skinny [DataFrame](#).

The hasRowRanges method identifies assays that support a [rowRanges](#) method *and* return a [GRanges](#) object.

## Value

See the itemized list in the description section for details.

## mergeReplicates

The mergeReplicates function makes use of the output from replicated which will point out the duplicate measurements by biological unit in the MultiAssayExperiment. This function will return a MultiAssayExperiment with merged replicates. Additional arguments can be provided to

the `simplify` argument via the ellipsis (...). For example, when replicates "TCGA-B" and "TCGA-A" are found in the assay, the name of the first appearing replicate is taken (i.e., "B"). Note that a typical use case of merging replicates occurs when there are multiple measurements on the **same** sample (within the same assay) and can therefore be averaged.

### longFormat

The `longFormat` method takes data from the `ExperimentList` in a `MultiAssayExperiment` and returns a uniform `DataFrame`. The resulting `DataFrame` has columns indicating primary, rowname, colname and value. This method can optionally include columns of the `MultiAssayExperiment` colData named by `colDataCols` character vector argument. (`MultiAssayExperiment` method only). The `i` argument allows the user to specify the assay value for the `SummarizedExperiment` assay function's `i` argument.

### wideFormat

The `wideFormat` function returns standardized wide `DataFrame` where each row represents a biological unit as in the `colData`. Depending on the data and setup, biological units can be patients, tumors, specimens, etc. Metadata columns are generated based on the names produced in the wide format `DataFrame`. These can be accessed via the `mcols` function. See the `wideFormat` section for description of the `colDataCols` and `i` arguments.

### hasRowRanges

The `hasRowRanges` method identifies assays with associated ranged row data by directly testing the method on the object. The result from the test must be a `GRanges` class object to satisfy the test.

### getWithColData

The `getWithColData` function allows the user to conveniently extract a particular assay as indicated by the `i` index argument. It will also attempt to provide the `colData` along with the extracted object using the `colData<-` replacement method when possible. Typically, this method is available for `SummarizedExperiment` and `RaggedExperiment` classes.

The setting of `mode` determines how the `colData` is added. If `mode="append"`, the `MultiAssayExperiment` metadata is appended onto that of the `SummarizedExperiment`. If any fields are duplicated by name, the values in the `SummarizedExperiment` are retained, with a warning emitted if the values are different. For `mode="replace"`, the `MultiAssayExperiment` metadata replaces that of the `SummarizedExperiment`, while for `mode="none"`, no replacement or appending is performed.

### rename\*

The `renamePrimary` function allows the user to conveniently change the actual names of the primary biological units as seen in `rownames(colData)`. `renameColname` allows the user to change the names of a particular assay based on index `i`. `i` can either be a single numeric or character value. See `colnames<-` method for renaming multiple colnames in a `MultiAssayExperiment`.

## splitAssays

The `splitAssays` method separates columns in each of the assays based on the `hitList` input. The `hitList` can be generated using the `makeHitList` helper function. To use the `makeHitList` helper, the user should input a list of patterns that will match on the column names of each assay. These matches should be mutually exclusive as to avoid repetition of columns across assays. See the examples section.

## Examples

```
example(MultiAssayExperiment)

complete.cases(mae)

isEmpty(MultiAssayExperiment())

## renaming biological units (primary)

mae2 <- renamePrimary(mae, paste0("pt", 1:4))
colData(mae2)
sampleMap(mae2)

## renaming observational units (colname)

mae2 <- renameColname(mae, i = "Affy", paste0("ARRAY", 1:4))
colnames(mae2)
sampleMap(mae2)

patts <- list(
  normals = "TCGA-OR-[A-Z0-9]{4}-11",
  tumors = "TCGA-OR-[A-Z0-9]{4}-01"
)

data("miniACC")

hits <- makeHitList(miniACC, patts)

splitAssays(miniACC, hits)
```

**Description**

A set of accessor and setter generic functions to extract either the `sampleMap`, the `ExperimentList`, `colData`, or metadata slots of a `MultiAssayExperiment` object

**Usage**

```
## S4 method for signature 'MultiAssayExperiment'
sampleMap(x)

## S4 method for signature 'MultiAssayExperiment'
experiments(x)

## S4 method for signature 'MultiAssayExperiment'
colData(x, ...)

## S4 method for signature 'MultiAssayExperiment'
metadata(x)

## S4 replacement method for signature 'MultiAssayExperiment,DataFrame'
sampleMap(object) <- value

## S4 replacement method for signature 'MultiAssayExperiment,ANY'
sampleMap(object) <- value

## S4 replacement method for signature 'MultiAssayExperiment,ExperimentList'
experiments(object) <- value

## S4 replacement method for signature 'MultiAssayExperiment,List'
experiments(object) <- value

## S4 replacement method for signature 'MultiAssayExperiment,DataFrame'
colData(x) <- value

## S4 replacement method for signature 'MultiAssayExperiment,ANY'
colData(x) <- value

## S4 replacement method for signature 'MultiAssayExperiment'
metadata(x, ...) <- value

## S4 replacement method for signature 'MultiAssayExperiment'
x$name <- value

## S4 replacement method for signature 'MultiAssayExperiment'
names(x) <- value

## S4 replacement method for signature 'MultiAssayExperiment,List'
colnames(x) <- value
```

```
## S4 replacement method for signature 'MultiAssayExperiment,list'
colnames(x) <- value
```

```
## S4 method for signature 'MultiAssayExperiment'
x$name
```

### Arguments

...	Argument not in use
object, x	A MultiAssayExperiment object
value	See details.
name	A column in colData

### Value

Accessors: Either a sampleMap, ExperimentList, or DataFrame object

Setters: A MultiAssayExperiment object

### Accessors

Eponymous names for accessing MultiAssayExperiment slots with the exception of the [ExperimentList](#) accessor named experiments.

- colData: Access the colData slot
- sampleMap: Access the sampleMap slot
- experiments: Access the [ExperimentList](#) slot
- '[': Access the [ExperimentList](#) slot
- '\$': Access a column in colData

### Setters

Setter method values (i.e., 'function(x) <- value'):

- experiments<-: An [ExperimentList](#) object containing experiment data of supported classes
- sampleMap<-: A [DataFrame](#) object relating samples to biological units and assays
- colData<-: A [DataFrame](#) object describing the biological units
- metadata<-: A list object of metadata
- '['<-: Equivalent to the experiments<- setter method for convenience
- '\$<-: A vector to replace the indicated column in colData

## Examples

```
## Load example MultiAssayExperiment
example(MultiAssayExperiment)

## Access the sampleMap
sampleMap(mae)

## Replacement method for a MultiAssayExperiment sampleMap
sampleMap(mae) <- S4Vectors::DataFrame()

## Access the ExperimentList
experiments(mae)

## Replace with an empty ExperimentList
experiments(mae) <- ExperimentList()

## Access the metadata
metadata(mae)

## Replace metadata with a list
metadata(mae) <- list(runDate =
  format(Sys.time(), "%B %d, %Y"))

## Access the colData
colData(mae)

## Access a column in colData
mae$age

## Replace a column in colData
mae$age <- mae$age + 1
```

---

MultiAssayExperimentToMAF

*Convert MultiAssayExperiment to MAF class*

---

## Description

Take a MultiAssayExperiment object with specific mutation assays and convert these into a maftools representation.

## Usage

```
MultiAssayExperimentToMAF(x, synAssay = "maf_syn", nonSynAssay = "maf_nonSyn")
```

## Arguments

x	A MultiAssayExperiment object
synAssay	character(1) The name of the synonymous variant classifications.



nonSynAssay      character(1) The name of the assay with non-synonymous variant classifications.

---

prepMultiAssay      *Prepare a MultiAssayExperiment instance*

---

## Description

The purpose of this helper function is to facilitate the creation of a [MultiAssayExperiment](#) object by detecting any inconsistencies with all types of names in either the [ExperimentList](#), the `colData`, or `sampleMap`.

## Usage

```
prepMultiAssay(ExperimentList, colData, sampleMap, ...)
```

## Arguments

`ExperimentList` A list of all combined experiments

`colData` A [DataFrame](#) of the phenotype data for all participants

`sampleMap` A [DataFrame](#) of sample identifiers, assay samples, and assay names

... Optional arguments for the `MultiAssayExperiment` constructor function such as metadata and drops.

## Value

A list containing all the essential components of a [MultiAssayExperiment](#) as well as a "drops" metadata element that indicates non-matched names. The names of the resulting list correspond to the arguments of the `MultiAssayExperiment` constructor function.

## Checks

The `prepMultiAssay` function checks that all columns in the `sampleMap` are character.

It checks that all names and lengths match in both the [ExperimentList](#) and in the unique assay names of the `sampleMap`.

If [ExperimentList](#) names and assay names only differ by case and are not duplicated, the function will standardize all names to lowercase.

If names cannot be matched between the `colname` column of the `sampleMap` and the colnames of the `ExperimentList`, those unmatched will be dropped and found in the "drops" element of the resulting list.

Names in the "primary" column of the `sampleMap`, will be matched to those in the `colData`. Unmatched "primary" column rows will be dropped from the `sampleMap`. Suggestions for name fixes in either the [ExperimentList](#) or colnames will be made when necessary.

**Examples**

```
## Run example
example("MultiAssayExperiment")

## Check if there are any inconsistencies within the different names
preparedMAE <- prepMultiAssay(ExpList, colDat, sampMap)

## Results in a list of components for the MultiAssayExperiment constructor
## function
MultiAssayExperiment(preparedMAE$experiments, preparedMAE$colData,
preparedMAE$sampleMap)

## Alternatively, use the do.call function
do.call(MultiAssayExperiment, preparedMAE)
```

---

reexports

*Objects exported from other packages*


---

**Description**

These objects are imported from other packages. Click on the function name to see their documentation.

- S4Vectors: [DataFrame](#)

**Examples**

```
DataFrame()
```

---

saveHDF5MultiAssayExperiment

*Save a MultiAssayExperiment class object to HDF5 and Rds files*


---

**Description**

This function takes a `MultiAssayExperiment` object and uses the `assays` functionality to obtain data matrices out of the experiments. These are then saved into the `.h5` file format. This function relies heavily on the `HDF5Array` package whose installation is required before use. `saveHDF5MultiAssayExperiment` preserves the classes contained in the `\linkS4class{ExperimentList}` with the exception of `matrix` which is converted to `HDF5Matrix`. Internal `SummarizedExperiment` assays are converted to HDF5-backed assays as in `HDF5Array::saveHDF5SummarizedExperiment`. `SummarizedExperiment`

objects with multiple `i`-th assays will have the first assay take precedence and others assays will be dropped with a warning. If the first assay in a `SummarizedExperiment` contains an array, the array is preserved in the process of saving and loading the HDF5-backed `MultiAssayExperiment`.

### Usage

```
saveHDF5MultiAssayExperiment(
  x,
  dir = "h5_mae",
  prefix = NULL,
  replace = FALSE,
  chunkdim = NULL,
  level = NULL,
  as.sparse = NA,
  verbose = NA
)

loadHDF5MultiAssayExperiment(dir = "h5_mae", prefix = NULL)
```

### Arguments

<code>x</code>	A <a href="#">MultiAssayExperiment</a> object or derivative
<code>dir</code>	The path (as a single string) to the directory where to save the HDF5-based <a href="#">MultiAssayExperiment</a> object or to load it from.  When saving, the directory will be created if it doesn't already exist. If the directory already exists and no prefix is specified and <code>replace</code> is set to <code>TRUE</code> , then it's replaced with an empty directory.
<code>prefix</code>	An optional prefix to add to the names of the files created inside <code>dir</code> . Allows saving more than one object in the same directory. When the prefix is <code>NULL</code> , the name of the <code>MultiAssayExperiment</code> object is used. To avoid the default setting use an empty character string i.e., <code>""</code> .
<code>replace</code>	When no prefix is specified, should a pre-existing directory be replaced with a new empty one? The content of the pre-existing directory will be lost!
<code>chunkdim</code>	The dimensions of the chunks and the compression level to use for writing the assay data to disk.  Passed to the internal calls to <code>writeHDF5Array</code> . See <a href="#">?writeHDF5Array</a> for more information.
<code>level</code>	The dimensions of the chunks and the compression level to use for writing the assay data to disk.  Passed to the internal calls to <code>writeHDF5Array</code> . See <a href="#">?writeHDF5Array</a> for more information.
<code>as.sparse</code>	Whether the assay data should be flagged as sparse or not. If set to <code>NA</code> (the default), then the specific <code>as.sparse</code> value to use for each assay is determined by calling <code>is_sparse()</code> on them.

Passed to the internal calls to `writeHDF5Array`. See `?writeHDF5Array` for more information and an IMPORTANT NOTE.

`verbose` Set to TRUE to make the function display progress.

In the case of `saveHDF5MultiAssayExperiment()`, `verbose` is set to `NA` by default, in which case verbosity is controlled by `DelayedArray::get_verbose_block_processing()`. Setting `verbose` to `TRUE` or `FALSE` overrides this.

## Examples

```
data("miniACC")

testDir <- file.path(tempdir(), "test_mae")

saveHDF5MultiAssayExperiment(
  miniACC, dir = testDir, verbose = TRUE, replace = TRUE
)

## inspect the files in the dir
list.files(testDir)

loadHDF5MultiAssayExperiment(
  dir = testDir
)

## remove example files
unlink(testDir, recursive = TRUE)
```

---

subsetBy                      *Subsetting a MultiAssayExperiment object*

---

## Description

A set of functions for extracting and dividing a `MultiAssayExperiment`

## Usage

```
subsetByRow(x, y, ...)

subsetByColData(x, y)

subsetByColumn(x, y)

subsetByAssay(x, y)

## S4 method for signature 'ExperimentList,ANY'
subsetByRow(x, y, ...)
```

```
## S4 method for signature 'ExperimentList,list'  
subsetByRow(x, y)  
  
## S4 method for signature 'ExperimentList,List'  
subsetByRow(x, y)  
  
## S4 method for signature 'ExperimentList,logical'  
subsetByRow(x, y)  
  
## S4 method for signature 'ExperimentList,list'  
subsetByColumn(x, y)  
  
## S4 method for signature 'ExperimentList,List'  
subsetByColumn(x, y)  
  
## S4 method for signature 'ExperimentList,logical'  
subsetByColumn(x, y)  
  
## S4 method for signature 'ExperimentList'  
subsetByAssay(x, y)  
  
## S4 method for signature 'MultiAssayExperiment,ANY'  
subsetByColData(x, y)  
  
## S4 method for signature 'MultiAssayExperiment,character'  
subsetByColData(x, y)  
  
## S4 method for signature 'MultiAssayExperiment,ANY'  
subsetByRow(x, y, ...)  
  
## S4 method for signature 'MultiAssayExperiment,ANY'  
subsetByColumn(x, y)  
  
## S4 method for signature 'MultiAssayExperiment'  
subsetByAssay(x, y)  
  
## S4 method for signature 'MultiAssayExperiment,ANY,ANY,ANY'  
x[i, j, k, ..., drop = FALSE]  
  
## S4 method for signature 'MultiAssayExperiment,ANY,ANY'  
x[[i, j, ...]]  
  
## S4 replacement method for signature 'MultiAssayExperiment,ANY,ANY'  
x[[i, j, ...]] <- value  
  
## S4 replacement method for signature 'MultiAssayExperiment,ANY,ANY,ANY'  
x[i, j, ...] <- value
```

**Arguments**

x	A MultiAssayExperiment or ExperimentList
y	Any argument used for subsetting, can be a character, logical, integer, list or List vector
...	Additional arguments passed on to lower level functions.
i	Either a character, integer, logical or GRanges object for subsetting by rows
j	Either a character, logical, or numeric vector for subsetting by colData rows. See details for more information.
k	Either a character, logical, or numeric vector for subsetting by assays
drop	logical (default FALSE) whether to drop all empty assay elements in the ExperimentList
value	An assay compatible with the MultiAssayExperiment API

**Details**

Subsetting a MultiAssayExperiment by the **j** index can yield a call to either subsetByColData or subsetByColumn. For vector inputs, the subset will be applied to the colData rows. For List-type inputs, the List will be applied to each of the elements in the ExperimentList. The order of the subsetting elements in the List must match that of the ExperimentList in the MultiAssayExperiment.

- subsetByColData: Select biological units by vector input types
- subsetByColumn: Select observations by assay or for each assay
- subsetByRow: Select rows by assay or for each assay
- subsetByAssay: Select experiments

**Value**

subsetBy\* operations are endomorphic and return either MultiAssayExperiment or ExperimentList depending on the input.

**Examples**

```
## Load the example MultiAssayExperiment
example("MultiAssayExperiment")

## Using experiment names
subsetByAssay(mae, "Affy")

## Using numeric indices
subsetByAssay(mae, 1:2)

## Using a logical vector
subsetByAssay(mae, c(TRUE, FALSE, TRUE))

## Subset by character vector (Jack)
subsetByColData(mae, "Jack")
```

```

## Subset by numeric index of colData rows (Jack and Bob)
subsetByColData(mae, c(1, 3))

## Subset by logical indicator of colData rows (Jack and Jill)
subsetByColData(mae, c(TRUE, TRUE, FALSE, FALSE))

subsetByColumn(mae, list(Affy = 1:2,
  Methyl450k = c(3,5,2), RNASeqGene = 2:4, GISTIC = 1))

subsetWith <- S4Vectors::mendoapply(`[`, colnames(mae),
  MoreArgs = list(1:2))
subsetByColumn(mae, subsetWith)

## Use a GRanges object to subset rows where ranged data present
egr <- GenomicRanges::GRanges(seqnames = "chr2",
  IRanges::IRanges(start = 11, end = 13), strand = "-")
subsetByRow(mae, egr)

## Use a logical vector (recycling used)
subsetByRow(mae, c(TRUE, FALSE))

## Use a character vector
subsetByRow(mae, "ENST00000355076")

```

---

upsetSamples	<i>Create a generalized Venn Diagram analog for sample membership in multiple assays, using the upset algorithm in UpSetR</i>
--------------	---

---

## Description

Create a generalized Venn Diagram analog for sample membership in multiple assays, using the upset algorithm in UpSetR

## Usage

```

upsetSamples(
  MultiAssayExperiment,
  nsets = length(MultiAssayExperiment),
  nintersects = 24,
  order.by = "freq",
  nameFilter = force,
  check.names = FALSE,
  ...
)

```

## Arguments

MultiAssayExperiment  
 A [MultiAssayExperiment](#) instance

nsets	integer number of sets to analyze
nintersects	Number of intersections to plot. If set to NA, all intersections will be plotted.
order.by	How the intersections in the matrix should be ordered by. Options include frequency (entered as "freq"), degree, or both in any order.
nameFilter	function, defaulting to force, to manipulate colnames of incidence matrix
check.names	logical(1) used when incidence matrix is coerced to data.frame for use in UpSetR::upset
...	parameters passed to <a href="#">upset</a>

**Value**

Produces a visualization of set intersections using the UpSet matrix design

**Note**

This function is intended to provide convenient visualization of assay availability configurations in MultiAssayExperiment instances. The [upset](#) function requires data.frame input and has many parameters to tune appearance of the result. Assay name handling is important for interpretability, and the nameFilter parameter may be useful to simplify resulting outputs.

**Author(s)**

Vincent J Carey

**Examples**

```
data(miniACC)
upsetSamples(miniACC)
upsetSamples(miniACC, nameFilter = function(x) substr(x, 1, 5))
```



# Index

- \* **data**
  - miniACC, [9](#)
- [,MultiAssayExperiment,ANY,ANY,ANY-method (subsetBy), [28](#)
- [,MultiAssayExperiment,ANY-method (subsetBy), [28](#)
- [<-,MultiAssayExperiment,ANY,ANY,ANY-method (subsetBy), [28](#)
- [[,MultiAssayExperiment,ANY,ANY-method (subsetBy), [28](#)
- [[<-,MultiAssayExperiment,ANY,ANY-method (subsetBy), [28](#)
- \$,MultiAssayExperiment-method (MultiAssayExperiment-methods), [21](#)
- \$<-,MultiAssayExperiment-method (MultiAssayExperiment-methods), [21](#)
- anyReplicated (MultiAssayExperiment-helpers), [16](#)
- anyReplicated,MultiAssayExperiment-method (MultiAssayExperiment-helpers), [16](#)
- as, [15](#)
- assay,ANY,missing-method (ExperimentList-class), [5](#)
- assay,ExperimentList,character-method (ExperimentList-class), [5](#)
- assay,ExperimentList,missing-method (ExperimentList-class), [5](#)
- assay,ExperimentList,numeric-method (ExperimentList-class), [5](#)
- assay,MultiAssayExperiment,character-method (MultiAssayExperiment-class), [12](#)
- assay,MultiAssayExperiment,missing-method (MultiAssayExperiment-class), [12](#)
- assay,MultiAssayExperiment,numeric-method (MultiAssayExperiment-class), [12](#)
- assays,ExperimentList-method (ExperimentList-class), [5](#)
- assays,MultiAssayExperiment-method (MultiAssayExperiment-class), [12](#)
- c,MultiAssayExperiment-method (MultiAssayExperiment-class), [12](#)
- CharacterList, [6](#)
- coerce,List,ExperimentList-method (ExperimentList-class), [5](#)
- coerce,list,ExperimentList-method (ExperimentList-class), [5](#)
- coerce,List,MultiAssayExperiment-method (MultiAssayExperiment-class), [12](#)
- coerce,list,MultiAssayExperiment-method (MultiAssayExperiment-class), [12](#)
- coerce,MultiAssayExperiment,MatchedAssayExperiment-method (MatchedAssayExperiment-class), [8](#)
- coerce-ExperimentList (ExperimentList-class), [5](#)
- coerce-MultiAssayExperiment (MultiAssayExperiment-class), [12](#)
- colData, [20](#)
- colData,MultiAssayExperiment-method (MultiAssayExperiment-methods), [21](#)
- colData<-,MultiAssayExperiment,ANY-method (MultiAssayExperiment-methods), [21](#)
- colData<-,MultiAssayExperiment,DataFrame-method (MultiAssayExperiment-methods),

- 21
- colnames<- ,MultiAssayExperiment,List-method  
(MultiAssayExperiment-methods),  
21
- colnames<- ,MultiAssayExperiment,list-method  
(MultiAssayExperiment-methods),  
21
- complete.cases,MultiAssayExperiment-method  
(MultiAssayExperiment-helpers),  
16
- DataFrame, 8, 10, 14, 16, 17, 19, 20, 23, 25, 26
- DataFrame (reexports), 26
- dimnames,ExperimentList-method  
(ExperimentList-class), 5
- dimnames,MultiAssayExperiment-method  
(MultiAssayExperiment-class),  
12
- ExperimentList, 3, 6, 10–12, 14, 15, 20, 22,  
23, 25
- ExperimentList-class, 5
- experiments  
(MultiAssayExperiment-methods),  
21
- experiments,MultiAssayExperiment-method  
(MultiAssayExperiment-methods),  
21
- experiments<-  
(MultiAssayExperiment-methods),  
21
- experiments<- ,MultiAssayExperiment,ExperimentList-method  
(MultiAssayExperiment-methods),  
21
- experiments<- ,MultiAssayExperiment,List-method  
(MultiAssayExperiment-methods),  
21
- exportClass  
(MultiAssayExperiment-class),  
12
- exportClass,MultiAssayExperiment-method  
(MultiAssayExperiment-class),  
12
- ExpressionSet, 12, 19
- findOverlaps, 14
- getWithColData  
(MultiAssayExperiment-helpers),  
16
- GRanges, 19, 20
- GRangesList, 12
- hasAssay, 7
- hasRowRanges  
(MultiAssayExperiment-helpers),  
16
- hasRowRanges,ExperimentList-method  
(MultiAssayExperiment-helpers),  
16
- hasRowRanges,MultiAssayExperiment-method  
(MultiAssayExperiment-helpers),  
16
- HDF5MultiAssayExperiment  
(saveHDF5MultiAssayExperiment),  
26
- intersectColumns  
(MultiAssayExperiment-helpers),  
16
- intersectRows  
(MultiAssayExperiment-helpers),  
16
- isEmpty,ExperimentList-method  
(ExperimentList-class), 5
- isEmpty,MultiAssayExperiment-method  
(MultiAssayExperiment-helpers),  
16
- length,MultiAssayExperiment-method  
(MultiAssayExperiment-class),  
12
- List, 6, 14, 15
- listToMap, 7
- loadHDF5MultiAssayExperiment  
(saveHDF5MultiAssayExperiment),  
26
- LogicalList, 6, 18, 19
- longFormat  
(MultiAssayExperiment-helpers),  
16
- makeHitList  
(MultiAssayExperiment-helpers),  
16
- makeMatchList  
(MultiAssayExperiment-helpers),  
16
- mapToList (listToMap), 7

- MatchedAssayExperiment
  - (MatchedAssayExperiment-class), 8
- MatchedAssayExperiment-class, 8
- mcols, 20
- mergeReplicates
  - (MultiAssayExperiment-helpers), 16
- mergeReplicates, ANY-method
  - (MultiAssayExperiment-helpers), 16
- mergeReplicates, ExperimentList-method
  - (ExperimentList-class), 5
- mergeReplicates, MultiAssayExperiment-method
  - (MultiAssayExperiment-helpers), 16
- metadata, MultiAssayExperiment-method
  - (MultiAssayExperiment-methods), 21
- metadata<- , MultiAssayExperiment-method
  - (MultiAssayExperiment-methods), 21
- miniACC, 9
- MultiAssayExperiment, 8, 9, 10, 15, 19, 20, 22, 25, 27, 31
- MultiAssayExperiment-class, 10, 11, 12
- MultiAssayExperiment-helpers, 16
- MultiAssayExperiment-methods, 15, 21
- MultiAssayExperiment-package, 2
- MultiAssayExperimentToMAF, 24
  
- names, MultiAssayExperiment-method
  - (MultiAssayExperiment-class), 12
- names<- , MultiAssayExperiment-method
  - (MultiAssayExperiment-methods), 21
  
- prepMultiAssay, 25
  
- RaggedExperiment, 12
- reexports, 26
- renameColname
  - (MultiAssayExperiment-helpers), 16
- renamePrimary
  - (MultiAssayExperiment-helpers), 16
  
- replicated
  - (MultiAssayExperiment-helpers), 16
- replicated, MultiAssayExperiment-method
  - (MultiAssayExperiment-helpers), 16
- rowRanges, 17, 19
  
- sampleMap, 11, 12, 15, 25
- sampleMap
  - (MultiAssayExperiment-methods), 21
- sampleMap, MultiAssayExperiment-method
  - (MultiAssayExperiment-methods), 21
- sampleMap<-
  - (MultiAssayExperiment-methods), 21
- sampleMap<- , MultiAssayExperiment, ANY-method
  - (MultiAssayExperiment-methods), 21
- sampleMap<- , MultiAssayExperiment, DataFrame-method
  - (MultiAssayExperiment-methods), 21
- saveHDF5MultiAssayExperiment, 26
- show, ExperimentList-method
  - (ExperimentList-class), 5
- show, MultiAssayExperiment-method
  - (MultiAssayExperiment-class), 12
- SimpleList, 11, 14, 15
- splitAssays
  - (MultiAssayExperiment-helpers), 16
- splitAssays, MultiAssayExperiment-method
  - (MultiAssayExperiment-helpers), 16
- subset (subsetBy), 28
- subsetBy, 28
- subsetByAssay (subsetBy), 28
- subsetByAssay, ExperimentList-method
  - (subsetBy), 28
- subsetByAssay, MultiAssayExperiment-method
  - (subsetBy), 28
- subsetByColData (subsetBy), 28
- subsetByColData, MultiAssayExperiment, ANY-method
  - (subsetBy), 28
- subsetByColData, MultiAssayExperiment, character-method
  - (subsetBy), 28

subsetByColumn (subsetBy), [28](#)  
subsetByColumn, ExperimentList, List-method  
    (subsetBy), [28](#)  
subsetByColumn, ExperimentList, list-method  
    (subsetBy), [28](#)  
subsetByColumn, ExperimentList, logical-method  
    (subsetBy), [28](#)  
subsetByColumn, MultiAssayExperiment, ANY-method  
    (subsetBy), [28](#)  
subsetByRow (subsetBy), [28](#)  
subsetByRow, ExperimentList, ANY-method  
    (subsetBy), [28](#)  
subsetByRow, ExperimentList, List-method  
    (subsetBy), [28](#)  
subsetByRow, ExperimentList, list-method  
    (subsetBy), [28](#)  
subsetByRow, ExperimentList, logical-method  
    (subsetBy), [28](#)  
subsetByRow, MultiAssayExperiment, ANY-method  
    (subsetBy), [28](#)  
SummarizedExperiment, [12](#), [18–20](#)  
  
updateObject, MultiAssayExperiment-method  
    (MultiAssayExperiment-class),  
    [12](#)  
upset, [32](#)  
upsetSamples, [31](#)  
  
wideFormat  
    (MultiAssayExperiment-helpers),  
    [16](#)  
writeHDF5Array, [27](#), [28](#)