

Package ‘MeasurementError.cor’

September 25, 2024

Title Measurement Error model estimate for correlation coefficient

Version 1.77.0

Author Beiyong Ding

Description Two-stage measurement error model for correlation estimation with smaller bias than the usual sample correlation

Maintainer Beiyong Ding <bding@amgen.com>

License LGPL

biocViews StatisticalMethod

git_url <https://git.bioconductor.org/packages/MeasurementError.cor>

git_branch devel

git_last_commit f731521

git_last_commit_date 2024-04-30

Repository Bioconductor 3.20

Date/Publication 2024-09-24

Contents

| | |
|-------------------------|----------|
| cor.me.matrix | 1 |
| cor.me.vector | 2 |
| Index | 4 |

| | |
|---------------|---|
| cor.me.matrix | <i>A function to calculate measurement error estimates for all pairs of genes given by the matrix</i> |
|---------------|---|

Description

Given a matrix ($p \times n$) for observed values of p variables and a corresponding matrix for their standard errors, the all pairwise measurement error estimates for true correlations are returned

Usage

```
cor.me.matrix(exp, se)
```

Arguments

| | |
|-----|-----------------------|
| exp | observed value matrix |
| se | standard error matrix |

Value

The final estimates for true correlation (i.e. cor.true) from the measurement error model

Note

The function involves using quasi-newton for linear optimization, "BFGS" is the only implemented method now. Refer to cor.me.vector for more details.

Author(s)

Beiyong Ding

References

Ding, B.Y. and Gentleman, R.(2003) Measurement error model for correlation coefficient estimation and its application in microarray analysis

See Also

cor.me.vector

Examples

```
exp <- matrix(abs(rnorm(200,1000,20)),ncol=10)
se <- matrix(abs(rnorm(200,50,5)),ncol=10)
cor.me.matrix(exp,se)
```

cor.me.vector

A function to calculate measurement error model estimates for correlation coefficient between two variables

Description

Given the observed value of two variables and their respective standard error, the measurement error estimate for their correlation coefficient is returned

Usage

```
cor.me.vector(exp1, se1, exp2, se2)
```

Arguments

| | |
|------|---------------------------------------|
| exp1 | observed value for vector 1 |
| se1 | estimated standard error for vector 1 |
| exp2 | observed value for vector 2 |
| se2 | estimated standard error for vector 2 |

Value

| | |
|-------------|--|
| estimate | Vecotr containing the estimates from the measurement error model, i.e. cor.me, cor.true, mu1, mu2, s1, s2 which are correlation for the measurement error distribution of the two variables, true correlation between the two variables, and true mean and standard deviation estimates for the two variables respectively |
| count | numer of function and gradient evaluation |
| convergence | 0 if converged. See optim() for details |

Note

Most applicable for microarray expression data where standard errors are readily estimated by most low level analysis softwares. Hence variables can be thought of as genes. One also need to differentiate between cor.me and cor.true: the first one being the correlation between the measurement error distributions of the two genes whereas the second one is the quantity of interest, i.e true correlation between the two gene expression profiles.\

The function involves using quasi-newton for linear optimization, "BFGS" is the only implemented method now.

Author(s)

Beiyong Ding

References

Ding, B.Y. and Gentleman, R. (2003) Measurement Error Model for correlation coefficient estimation and its application in microarray analysis

See Also

cor.me.matrix

Examples

```
exp <- matrix(abs(rnorm(200,1000,20)),ncol=10)
se <- matrix(abs(rnorm(200,50,5)),ncol=10)
cor.me.vector(exp[1,],se[1,],exp[2,],se[2,])
```

Index

*** multivariate**

cor.me.matrix, [1](#)
cor.me.vector, [2](#)

cor.me.matrix, [1](#)
cor.me.vector, [2](#)