

Package ‘biodbUniprot’

December 23, 2024

Title biodbUniprot, a library for connecting to the Uniprot Database

Version 1.12.0

Description The biodbUniprot library is an extension of the biodb framework package. It provides access to the UniProt database. It allows to retrieve entries by their accession number, and run web service queries for searching for entries.

URL <https://github.com/pkrog/biodbUniprot>

BugReports <https://github.com/pkrog/biodbUniprot/issues>

biocViews Software, Infrastructure, DataImport

Depends R (>= 4.1.0)

License AGPL-3

Encoding UTF-8

VignetteBuilder knitr

Suggests BiocStyle, roxygen2, devtools, testthat (>= 2.0.0), knitr, rmarkdown, lgr, covr

Imports R6, biodb (>= 1.4.2)

RoxygenNote 7.2.1

Collate 'UniprotConn.R' 'UniprotEntry.R' 'package.R'

git_url <https://git.bioconductor.org/packages/biodbUniprot>

git_branch RELEASE_3_20

git_last_commit 535c0a6

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-23

Author Pierrick Roger [aut, cre] (<<https://orcid.org/0000-0001-8177-4873>>)

Maintainer Pierrick Roger <pierrick.roger@cea.fr>

Contents

UniprotConn	2
UniprotEntry	4
Index	5

 UniprotConn

The connector class to Uniprot database.

Description

The connector class to Uniprot database.

The connector class to Uniprot database.

Details

This is a concrete connector class. It must never be instantiated directly, but instead be instantiated through the factory `BiodbFactory`. Only specific methods are described here. See super classes for the description of inherited methods.

Super classes

`biodb::BiodbConnBase` -> `biodb::BiodbConn` -> UniprotConn

Methods

Public methods:

- `UniprotConn$wsSearch()`
- `UniprotConn$wsQuery()`
- `UniprotConn$geneSymbolToUniprotIds()`
- `UniprotConn$clone()`

Method `wsSearch()`: Calls search service on the database for searching for compounds. See https://www.uniprot.org/help/programmatic_access for details.

Usage:

```
UniprotConn$wsSearch(
  query = "",
  fields = NULL,
  format = NULL,
  size = NULL,
  retfmt = c("plain", "parsed", "ids", "request")
)
```

Arguments:

`query` The query to send to the database.

`fields` The field columns to retrieve from the database (e.g.: 'id', 'entry name', 'pathway', 'organism', 'sequence', etc).

`format` The return format (e.g.: 'tsv').

`size` The maximum number of entries to return.

`retfmt` Use to set the format of the returned value. 'plain' will return the raw results from the server, as a character value. 'parsed' will return the parsed results, as a JSON object. 'request' will return a `BiodbRequest` object representing the request as it would have been sent. 'ids' will return a character vector containing the IDs of the matching entries.

Returns: Depending on 'retfmt' parameter.

Method `wsQuery()`: Calls query service on the database for searching for compounds. See http://www.uniprot.org/help/api_queries for details.

Usage:

```
UniprotConn$wsQuery(
  query = "",
  columns = NULL,
  format = NULL,
  limit = NULL,
  retfmt = c("plain", "parsed", "ids", "request")
)
```

Arguments:

`query` The query to send to the database.

`columns` The field columns to retrieve from the database (e.g.: 'id', 'entry name', 'pathway', 'organism', 'sequence', etc).

`format` The return format (e.g.: 'tsv').

`limit` The maximum number of entries to return.

`retfmt` Use to set the format of the returned value. 'plain' will return the raw results from the server, as a character value. 'parsed' will return the parsed results, as a JSON object. 'request' will return a `BiodbRequest` object representing the request as it would have been sent. 'ids' will return a character vector containing the IDs of the matching entries.

Returns: Depending on 'retfmt' parameter.

Method `geneSymbolToUniprotIds()`: Gets UniProt IDs associated with gene symbols.

Usage:

```
UniprotConn$geneSymbolToUniprotIds(
  genes,
  ignore.nonalphanum = FALSE,
  partial.match = FALSE,
  filtering = TRUE,
  max.results = 0
)
```

Arguments:

`genes` A vector of gene symbols to convert to UniProt IDs.

`ignore.nonalphanum` If set to TRUE, do not take into account non-alphanumeric characters when comparing gene symbols.

`partial.match` If set to TRUE, a match will be valid even if the provided gene symbol is only a substring of the found gene symbol.

`filtering` If set to FALSE, do not run any filtering and return all the UniProt IDs given by UniProt search web service. DEPRECATED: new UniProt REST API returns only exact match.

`max.results` Maximum of UniProt IDs returned for each gene symbol.

Returns: A named list of vectors of UniProt IDs. The names are gene symbols provided with the `genes` parameter. For each gene symbol, a vector of found UniProt IDs is set.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
UniprotConn$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
# Create an instance with default settings:
mybiodb <- biodb::newInst()

# Get Uniprot connector
uniprot <- mybiodb$getFactory()$createConn('uniprot')

# Access web service "search":
result <- uniprot$wsSearch(query='protein_name:"prion protein"',
                          fields=c('id', 'entry name'),
                          format='tsv', size=10)

# Terminate instance.
mybiodb$terminate()
```

UniprotEntry

Uniprot entry class.

Description

This is the entry class for Uniprot database.

Super classes

[biodb::BiodbEntry](#) -> [biodb::BiodbXmlEntry](#) -> UniprotEntry

Methods

Public methods:

- [UniprotEntry\\$clone\(\)](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
UniprotEntry$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
# Create an instance with default settings:
mybiodb <- biodb::newInst()

# Create a connector
conn <- mybiodb$getFactory()$createConn('uniprot')

# Get an entry
e <- conn$getEntry('P01011')

# Terminate instance.
mybiodb$terminate()
```

Index

biodb::BiodbConn, [2](#)
biodb::BiodbConnBase, [2](#)
biodb::BiodbEntry, [4](#)
biodb::BiodbXmlEntry, [4](#)

UniprotConn, [2](#)
UniprotEntry, [4](#)