

Package ‘enhancerHomologSearch’

December 23, 2024

Type Package

Title Identification of putative mammalian orthologs to given enhancer

Version 1.12.0

Description Get ENCODE data of enhancer region via H3K4me1 peaks and search homolog regions for given sequences. The candidates of enhancer homolog regions can be filtered by distance to target TSS. The top candidates from human and mouse will be aligned to each other and then exported as multiple alignments with given enhancer.

BugReports <https://github.com/jianhong/enhancerHomologSearch/issues>

URL <https://jianhong.github.io/enhancerHomologSearch>

Depends R (>= 4.1.0), methods

Imports BiocGenerics, Biostrings, BSgenome, BiocParallel, BiocFileCache, GenomeInfoDb, GenomicRanges, httr, IRanges, jsonlite, motifmatchr, Matrix, pwalign, rtracklayer, Rcpp, S4Vectors, stats, utils

Suggests knitr, rmarkdown, BSgenome.Drerio.UCSC.danRer10, BSgenome.Hsapiens.UCSC.hg38, BSgenome.Mmusculus.UCSC.mm10, TxDb.Hsapiens.UCSC.hg38.knownGene, org.Hs.eg.db, TxDb.Mmusculus.UCSC.mm10.knownGene, org.Mm.eg.db, MotifDb, testthat, TFBSTools

biocViews Sequencing, GeneRegulation, Alignment

License GPL (>= 2)

Encoding UTF-8

VignetteBuilder knitr

RoxygenNote 7.3.1

LinkingTo Rcpp

git_url <https://git.bioconductor.org/packages/enhancerHomologSearch>

git_branch RELEASE_3_20

git_last_commit 1f62e7e

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-23

Author Jianhong Ou [aut, cre] (<<https://orcid.org/0000-0002-8652-2488>>),
Valentina Cigliola [dct],
Kenneth Poss [fnd]

Maintainer Jianhong Ou <jianhong.ou@duke.edu>

Contents

alignment	2
alignmentOne	3
conservedMotifs	4
Enhancers-class	5
getENCODEdata	7
motifs	8
queryEncode	8
saveAlignments	9
searchTFBPS	10
shuffle	11
Index	12

alignment	<i>Output</i>
-----------	---------------

Description

Do pairwise alignment for query enhancer to target genome

Usage

```
alignment(
  query,
  subject,
  method = c("ClustalW", "Muscle"),
  cluster = c("nj", "upgma", "upgmamax", "upgmamin", "upgmb"),
  substitutionMatrix = c("iub", "clustalw"),
  gapOpening = ifelse(method[1] == "ClustalW", 15, 400),
  gapExtension = ifelse(method[1] == "ClustalW", 6.66, 0),
  maxiters = ifelse(method[1] == "ClustalW", 3, 16),
  order = c("aligned", "input"),
  ...
)
```

Arguments

query	An object of DNASTringSet to represent enhancer
subject	An list of objects of Enhancers .
method	specifies the multiple sequence alignment to be used; currently, "ClustalW", and "Muscle" are supported. Default is "Muscle"
cluster	The clustering method which should be used. Possible values are "nj" (default) and "upgma". In the original ClustalW implementation, this parameter is called clustering.

substitutionMatrix	substitution matrix for scoring matches and mismatches; The valid choices for this parameter are "iub" and "clustalw". In the original ClustalW implementation, this parameter is called matrix.
gapOpening	gap opening penalty; the default is 400 for DNA sequences and 420 for RNA sequences. The default for amino acid sequences depends on the profile score settings: for the setting le=TRUE, the default is 2.9, for sp=TRUE, the default is 1,439, and for sv=TRUE, the default is 300. Note that these defaults may not be suitable if custom substitution matrices are being used. In such a case, a sensible choice of gap penalties that fits well to the substitution matrix must be made.
gapExtension	gap extension penalty; the default is 0.
maxiters	maximum number of iterations; the default is 16.
order	how the sequences should be ordered in the output object; if "aligned" is chosen, the sequences are ordered in the way the multiple sequence alignment algorithm orders them. If "input" is chosen, the sequences in the output object are ordered in the same way as the input sequences.
...	Parameters can be used by Muscle, or ClustalW.

Value

An object of [Enhancers](#).

Examples

```
library(BSgenome.Hsapiens.UCSC.hg38)
library(BSgenome.Mmusculus.UCSC.mm10)
library(BSgenome.Drerio.UCSC.danRer10)
LEN <- GRanges("chr4", IRanges(19050041, 19051709))
seqEN <- getSeq(BSgenome.Drerio.UCSC.danRer10, LEN)
aln_hs <- readRDS(system.file("extdata", "aln_hs.rds",
                             package="enhancerHomologSearch"))
genome(aln_hs) <- Hsapiens
aln_mm <- readRDS(system.file("extdata", "aln_mm.rds",
                             package="enhancerHomologSearch"))
genome(aln_mm) <- Mmusculus
al <- alignment(seqEN, list(human=aln_hs, mouse=aln_mm),
               method="ClustalW", order="input")
```

alignmentOne

Get alignment scores

Description

Do pairwise alignment for query enhancer to target genome

Usage

```
alignmentOne(query, subject, block = 1000, bpparam = bpparam(), ...)
```

Arguments

query	An object of DNASTringSet to represent enhancer
subject	Output of getENCODEdata. An object of Enhancers
block	The size of sequences to do alignment. Increase the size will increase the memory cost. Default 1000.
bpparam	BiocParallel parameters.
...	not used.

Value

An object of [Enhancers](#).

Examples

```
library(BiocParallel)
bpparam <- MulticoreParam(workers = 1, tasks=200, progressbar=TRUE)
library(BSgenome.Hsapiens.UCSC.hg38)
peaks <- GRanges("chr1", IRanges(seq(5000, 50000, by=1000), width=1000))
peaks$id <- paste(seq_along(peaks), 1, sep="_")
subj <- Enhancers(genome=Hsapiens, peaks=peaks)
q <- getSeq(Hsapiens, GRanges("chr1", IRanges(90000, width=1000)))
ao <- alignmentOne(q, subj, bpparam=bpparam)
```

conservedMotifs

check the conserved motifs in the orthologs

Description

Print the conserved motifs in the alignments

Usage

```
conservedMotifs(
  aln,
  aln_list,
  PWMs,
  queryGenome,
  background = "genome",
  ...,
  output_folder,
  format = c("txt", "html")
)
```

Arguments

aln	alignment of multiple DNAs. Output of alignment function.
aln_list	The list of output of searchTFBPS such as for human and mouse.
PWMs	The Position Weight Matrix list represented as a numeric matrix. Object of PWMMatrixList or PFMatrixList .
queryGenome	An object of BSgenome for query enhancer.

background Background nucleotide frequencies. Default is "genome". Refer [matchMotifs](#) for details.

... Other parameters can be passed to [matchMotifs](#).

output_folder Output folder name.

format The format of output files with motif match positions. Available formats are 'txt' and 'html'. Default is 'txt'.

Value

A list of [XStringViews](#)

Examples

```
library(BSgenome.Hsapiens.UCSC.hg38)
library(BSgenome.Mmusculus.UCSC.mm10)
library(BSgenome.Drerio.UCSC.danRer10)
LEN <- GRanges("chr4", IRanges(19050041, 19051709))
seqEN <- getSeq(BSgenome.Drerio.UCSC.danRer10, LEN)
aln_hs <- readRDS(system.file("extdata", "aln_hs.rds",
                             package="enhancerHomologSearch"))
genome(aln_hs) <- Hsapiens
aln_mm <- readRDS(system.file("extdata", "aln_mm.rds",
                             package="enhancerHomologSearch"))
genome(aln_mm) <- Mmusculus
al <- alignment(seqEN, list(human=aln_hs, mouse=aln_mm),
                method="ClustalW", order="input")
data(motifs)
conservedMotifs(al[[1]], list(human=aln_hs, mouse=aln_mm),
                motifs[["dist60"]], Drerio)
```

Enhancers-class	<i>Class "Enhancers"</i>
-----------------	--------------------------

Description

An object of class "Enhancers" represents the output of function [getENCODEdata](#), which includes the sequences of enhancers and their genomic coordinates.

Usage

```
Enhancers(genome, peaks, TFBP, TFBP0)

## S4 method for signature 'Enhancers'
x$name

## S4 replacement method for signature 'Enhancers'
x$name <- value

## S4 method for signature 'Enhancers,ANY'
distance(x)

## S4 replacement method for signature 'Enhancers'
```

```

distance(x) <- value

## S4 method for signature 'Enhancers'
tfbp(x)

## S4 method for signature 'Enhancers'
query_tfbp(x)

## S4 method for signature 'Enhancers'
getSeq(x, ...)

## S4 method for signature 'Enhancers,ANY'
subsetByOverlaps(
  x,
  ranges,
  maxgap = -1L,
  minoverlap = 0L,
  type = c("any", "start", "end", "within", "equal"),
  invert = FALSE,
  ...
)

## S4 method for signature 'Enhancers'
subset(x, ...)

## S4 method for signature 'Enhancers'
seqinfo(x)

## S4 method for signature 'Enhancers'
genome(x)

## S4 replacement method for signature 'Enhancers'
genome(x) <- value

## S4 method for signature 'Enhancers'
peaks(x)

## S4 replacement method for signature 'Enhancers'
peaks(x) <- value

## S4 method for signature 'Enhancers'
show(object)

```

Arguments

genome	An object of BSgenome .
peaks	An object of GRanges .
TFBP	An object of lgCMatrix .
TFBP0	An vector of logical. "Enhancers"
x	An object of "Enhancers"
name	Slot name.

value The values.
 ... parameters can be passed to upstream functions.
 ranges, maxgap, minoverlap, type, invert
 parameters used by [subsetByOverlaps](#)
 object An object of "Enhancers"

Value

An object of Enhancers.

Slots

genome An object of [BSgenome](#).
 peaks An object of [GRanges](#).
 TFBP An object of [lgcMatrix](#).
 TFBP0 An vector of logical.

Examples

```
Enhancers()
```

```
getENCODEdata
```

Download enhancer sequences from ENCODE

Description

Query enhancer peak and extract sequences from ENCODE

Usage

```
getENCODEdata(  
  genome,  
  markers = "H3K4me1",  
  window_size = 1000L,  
  step = 50L,  
  ...  
)
```

Arguments

genome An object of [BSgenome](#).
 markers Enhancer markers. Default 'H3K4me1'. For active enhancer, it can be set as c('H3K4me1', 'H3K27ac'). If markers is a 'GRanges' object, the function will skip the download step.
 window_size, step The size of windows and steps to split the peaks into small pieces. These parameter is used because the width of histone marker peaks are different sizes. Break the peaks into small pieces can increase the matching score and align the matching for different peaks into same size. The window_size is also be used for overlapping detection of multiple histone markers.
 ... Parameters can be passed to [queryEncode](#)

Value

An object of [Enhancers](#) with genome, and peaks. The peaks is an object of GRanges. The genome is an object of BSgenome.

Examples

```
library(BSgenome.Hsapiens.UCSC.hg38)
hs <- getENCODEdata(genome=Hsapiens,
                    partialMatch=c(biosample_summary="spinal cord"))
```

motifs

Pre-clustered motifs from human and mouse

Description

The data were extracted from MotifDb package (v 1.34.0) and grouped by motifStack package (v 1.37.2). The data were packaged as PFMATRIX object by TFBSTools (v 1.30.0)

Usage

```
data(motifs)
```

Format

a list of PFMATRIX. The names of the list is the group distance.

Source

MotifDb package. Source code for the data generation is in extdata folder

Examples

```
data(motifs)
names(motifs)
motifs[[1]]
```

queryEncode

query data from ENCODE by predefined criteria

Description

Search ENCODE data by querying the ENCODE Portal using its REST API.

Usage

```
queryEncode(
  exactMatch,
  partialMatch = character(0),
  API_url = "https://www.encodeproject.org/search/",
  ...
)
```


Arguments

exactMatch	character. Exact-match keywords refer to search results that perfectly match all the keywords in the search query, exactly as entered. It is a named character vector. The names will be the keys and characters will be the values for search.
partialMatch	character. Partial-match refer to search results that contain the search query. It is a named character vector. The names will be the keys and characters will be the values for search. The value starting from '!' indicates logical negation(NOT). The value starting from '>', '>=', '<', '==', '<=' indicates string comparison.
API_url	character. The ENCODE REST API url.
...	Not used.

Value

A list of search results

Examples

```
res <- queryEncode(
  exactMatch=c(
    target.label="H3K4me1",
    replicates.library.biosample.donor.organism.scientific_name="Homo sapiens",
    assembly="GRCh38",
    assay_term_name="ChIP-seq"),
  partialMatch=c(biosample_summary="heart"))
```

saveAlignments

output alignments

Description

Save enhancer homologs to file in phylip format.

Usage

```
saveAlignments(
  al,
  output_folder = tempdir(),
  motifConsensus = NULL,
  format = c("txt", "html")
)
```

Arguments

al	output of alignment .
output_folder	output folder.
motifConsensus	Transcription factor binding consensus.
format	The format of output files. Available formats are 'txt' and 'html'. Default is 'txt'.

Value

The I/O status.

Examples

```
al <- readRDS(system.file("extdata", "al.rds",
  package="enhancerHomologSearch"))
tmpfolder <- tempdir()
library(MotifDb)
motifs <- query(MotifDb, "JASPAR_CORE")
consensus <- sapply(motifs, consensusString)
consensus <- DNASTringSet(gsub("\\?", "N", consensus))
saveAlignments(al, output_folder=tmpfolder, motifConsensus=consensus)
```

 searchTFBPS

Transcription Factor Binding Pattern Similarity (TFBPS) search

Description

Search the TFBPs for query in subject.

Usage

```
searchTFBPS(
  query,
  subject,
  PWMs,
  queryGenome,
  background = "genome",
  ...,
  maximalShuffleEnhancers = 1000
)
```

Arguments

query	An object of DNASTringSet to represent enhancer
subject	Output of getENCODEdata. An object of Enhancers
PWMs	The Position Weight Matrix list represented as a numeric matrix. Object of PWMMatrixList or PFMatrixList .
queryGenome	An object of BSgenome for query data.
background	background nucleotide frequencies. Default is "genome". Refer matchMotifs for details.
...	Parameters will be passed to matchMotifs except 'out' and 'genome'.
maximalShuffleEnhancers	The maximal number of Shuffled enhancers. If the number of the input enhancer candidates is greater than maximalShuffleEnhancers, no shuffled enhancer sequences will be included. The shuffled enhancers will be created by shuffle .

Value

An object of [Enhancers](#).

Examples

```
library(BSgenome.Hsapiens.UCSC.hg38)
peaks <- GRanges("chr1", IRanges(seq(5000, 50000, by=1000), width=1000))
peaks$id <- paste(seq_along(peaks), 1, sep="_")
subj <- Enhancers(genome=Hsapiens, peaks=peaks)
q <- getSeq(Hsapiens, GRanges("chr1", IRanges(90000, width=1000)))
data(motifs)
ao <- searchTFBPS(q, subj, motifs[["dist60"]], queryGenome=Hsapiens,
                 maximalShuffleEnhancers = 50)
```

shuffle

shuffle reads

Description

Uses the uShuffle library to shuffle reads

Usage

```
shuffle(reads, k = 2, n = 2)
```

Arguments

reads	An object of BStringSet .
k	the k-let size.
n	the number of random sequences to generate.

Value

An object of [BStringSet](#).

References

Jiang, M., Anderson, J., Gillespie, J. et al. uShuffle: A useful tool for shuffling biological sequences while preserving the k-let counts. BMC Bioinformatics 9, 192 (2008). <https://doi.org/10.1186/1471-2105-9-192>

Examples

```
library(Biostrings)
f <- DNASTringSet(c("CTC-NACCAAGTAT", "TTGA", "TACCTAGAG"))
shuffle(f)
```

Index

- * **datasets**
 - motifs, 8
- \$, Enhancers-method (Enhancers-class), 5
- \$<-, Enhancers-method (Enhancers-class), 5
- alignment, 2, 4, 9
- alignmentOne, 3
- BSgenome, 4, 6, 7, 10
- BStringSet, 11
- coerce (Enhancers-class), 5
- coerce, Enhancers, GRanges-method (Enhancers-class), 5
- conservedMotifs, 4
- distance (Enhancers-class), 5
- distance, Enhancers, ANY-method (Enhancers-class), 5
- distance, Enhancers-method (Enhancers-class), 5
- distance<- (Enhancers-class), 5
- distance<-, Enhancers, ANY-method (Enhancers-class), 5
- distance<-, Enhancers-method (Enhancers-class), 5
- Enhancers, 2-4, 8, 10
- Enhancers (Enhancers-class), 5
- Enhancers-class, 5
- genome (Enhancers-class), 5
- genome, Enhancers-method (Enhancers-class), 5
- genome<- (Enhancers-class), 5
- genome<-, Enhancers, BSgenome-method (Enhancers-class), 5
- genome<-, Enhancers-method (Enhancers-class), 5
- getENCODEdata, 5, 7
- getSeq, Enhancers-method (Enhancers-class), 5
- GRanges, 6, 7
- lgMatrix, 6, 7
- matchMotifs, 5, 10
- motifs, 8
- peaks (Enhancers-class), 5
- peaks, Enhancers-method (Enhancers-class), 5
- peaks<- (Enhancers-class), 5
- peaks<-, Enhancers, GRanges-method (Enhancers-class), 5
- peaks<-, Enhancers-method (Enhancers-class), 5
- PFMatrixList, 4, 10
- PWMatrixList, 4, 10
- query_tfbp (Enhancers-class), 5
- query_tfbp, Enhancers, ANY-method (Enhancers-class), 5
- query_tfbp, Enhancers-method (Enhancers-class), 5
- queryEncode, 7, 8
- saveAlignments, 9
- searchTFBPS, 4, 10
- seqinfo, Enhancers-method (Enhancers-class), 5
- show, Enhancers-method (Enhancers-class), 5
- shuffle, 10, 11
- subset, Enhancers-method (Enhancers-class), 5
- subsetByOverlaps, 7
- subsetByOverlaps, Enhancers, ANY-method (Enhancers-class), 5
- subsetByOverlaps, Enhancers-method (Enhancers-class), 5
- tfbp (Enhancers-class), 5
- tfbp, Enhancers, ANY-method (Enhancers-class), 5
- tfbp, Enhancers-method (Enhancers-class), 5
- XStringViews, 5