

BSgenome.Gaculeatus.UCSC.gasAcu1

December 25, 2024

BSgenome.Gaculeatus.UCSC.gasAcu1

Full genome sequences for Gasterosteus aculeatus (UCSC version gasAcu1)

Description

Full genome sequences for *Gasterosteus aculeatus* (Stickleback) as provided by UCSC (gasAcu1, Feb. 2006) and stored in Biostrings objects.

Note

This BSgenome data package was made from the following source data files:

chromFa.tar.gz from <http://hgdownload.cse.ucsc.edu/goldenPath/gasAcu1/bigZips/>

See [?BSgenomeForge](#) and the BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Author(s)

The Bioconductor Dev Team

See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNAString](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (`vignette("BSgenomeForge")`) in the **BSgenome** software package for how to make a BSgenome data package.

Examples

```

BSgenome.Gaculeatus.UCSC.gasAcu1
genome <- BSgenome.Gaculeatus.UCSC.gasAcu1
seqlengths(genome)
genome$chrI # same as genome[["chrI"]]

## -----
## Upstream sequences
## -----
## Starting with BioC 3.0, the upstream1000, upstream2000, and
## upstream5000 sequences for gasAcu1 are not included in the BSgenome
## data package anymore. However they can easily be extracted from the
## full genome sequences with something like:

library(GenomicFeatures)
txdb <- makeTranscriptDbFromUCSC("gasAcu1", "refGene")
gn <- sort(genes(txdb))
up1000 <- flank(gn, width=1000)
up1000seqs <- getSeq(genome, up1000)

## IMPORTANT: Make sure you use a TxDb package (or TranscriptDb object),
## that contains a gene model based on the exact same reference genome
## as the BSgenome object you pass to getSeq(). Note that you can make
## your own custom TranscriptDb object from various annotation resources.
## See the makeTranscriptDbFromUCSC(), makeTranscriptDbFromBiomart(),
## and makeTranscriptDbFromGFF() functions in the GenomicFeatures
## package.

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")

```

Index

* **data**

BSgenome.Gaculeatus.UCSC.gasAcu1,
[1](#)

* **package**

BSgenome.Gaculeatus.UCSC.gasAcu1,
[1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Gaculeatus.UCSC.gasAcu1, [1](#)

BSgenome.Gaculeatus.UCSC.gasAcu1-package
(BSgenome.Gaculeatus.UCSC.gasAcu1),
[1](#)

BSgenomeForge, [1](#)

DNAStrng, [1](#)

Gaculeatus

(BSgenome.Gaculeatus.UCSC.gasAcu1),
[1](#)