

# RmiR.Hs.miRNA

March 12, 2025

---

RmiR.Hs.miRNA\_dbconn *Collect information from different miRNA targets databases*

---

## Description

A function to get a connection object to some miRNA targets databases.

## Usage

```
RmiR.Hs.miRNA_dbconn()  
RmiR.Hs.miRNA_dbfile()
```

## Details

RmiR.Hs.miRNA\_dbconn returns a connection object to some miRNA targets databases. **IMPORTANT:** Do not call [dbDisconnect](#) on the connection object returned by RmiR.Hs.miRNA\_dbconn or you will break all the [AnnDbObj](#) objects defined in this package!

RmiR.Hs.miRNA\_dbfile returns the path (character string) to the package annotation DB (this is an SQLite v3 file).

## Value

RmiR.Hs.miRNA\_dbconn  
A DBIConnection object representing an open connection to the miRNA targets database.

RmiR.Hs.miRNA\_dbfile  
A character string with the path to the miRNA targets database.

## See Also

[dbGetQuery](#), [dbConnect](#), [dbconn](#), [dbfile](#)

**Examples**

```
## List all the tables of the database:
dbListTables(RmiR.Hs.miRNA_dbconn())

## Count the number of rows in the "targetscan" table:
dbGetQuery(RmiR.Hs.miRNA_dbconn(), "SELECT COUNT(*) FROM targetscan")

## List the contents of the "mirbase" tables:
dbListFields(RmiR.Hs.miRNA_dbconn(), "mirbase")

## List all targets of "hsa-miR-21" in miranda database:
dbGetQuery(RmiR.Hs.miRNA_dbconn(),
  "SELECT * FROM tarbase where mature_miRNA='hsa-miR-21'")

## The connection object returned by RmiR.Hs.miRNA_dbconn() was created with:
dbConnect(SQLite(), dbname=RmiR.Hs.miRNA_dbfile(), cache_size=64000, synchronous=0)
```

# Index

## \* datasets

RmiR.Hs.miRNA\_dbconn, [1](#)

## \* utilities

RmiR.Hs.miRNA\_dbconn, [1](#)

AnnDbObj, [1](#)

dbconn, [1](#)

dbConnect, [1](#)

dbDisconnect, [1](#)

dbfile, [1](#)

dbGetQuery, [1](#)

RmiR.Hs.miRNA\_dbconn, [1](#)

RmiR.Hs.miRNA\_dbfile

(RmiR.Hs.miRNA\_dbconn), [1](#)