

Package ‘tuberculosis’

December 26, 2024

Title Tuberculosis Gene Expression Data for Machine Learning

Description The tuberculosis R/Bioconductor package features tuberculosis gene expression data for machine learning. All human samples from GEO that did not come from cell lines, were not taken postmortem, and did not feature recombination have been included. The package has more than 10,000 samples from both microarray and sequencing studies that have been processed from raw data through a hyper-standardized, reproducible pipeline.

biocViews ExperimentHub, ExpressionData, Homo_sapiens_Data, MicroarrayData, SequencingData, ReproducibleResearch

Version 1.12.0

License Artistic-2.0

Depends R (>= 4.1.0), SummarizedExperiment

Imports AnnotationHub, ExperimentHub, S4Vectors, dplyr, magrittr, purrr, rlang, stringr, tibble, tidyr

Suggests BiocStyle, ggplot2, hrbthemes, knitr, readr, rmarkdown, scater, usethis, utils

URL <https://github.com/schifferl/tuberculosis>

BugReports <https://github.com/schifferl/tuberculosis/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/tuberculosis>

git_branch RELEASE_3_20

git_last_commit 316c333

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-12-26

Author Lucas Schiffer [aut, cre] (<<https://orcid.org/0000-0003-3628-0326>>)

Maintainer Lucas Schiffer <schiffer.lucas@gmail.com>

Contents

tuberculosis	2
Index	3

tuberculosis	<i>find/get tuberculosis gene expression data</i>
--------------	---

Description

To find or get tuberculosis gene expression data, users will use the `tuberculosis` function. The `dryrun` argument allows users to test a query prior to returning resources. When `dryrun = TRUE`, the function will print the names of matching resources as a message and return them invisibly as a character vector. When `dryrun = FALSE`, the function will either download resources from ExperimentHub or load them from the user's local cache. If a resource has multiple creation dates, the most recent is selected by default; add a date to override this behavior.

Usage

```
tuberculosis(pattern, dryrun = TRUE)
```

Arguments

<code>pattern</code>	regular expression pattern to look for in the titles of resources available in <code>tuberculosis</code> ; "." will return all resources
<code>dryrun</code>	if <code>TRUE</code> (the default), a character vector of resource names is returned invisibly; if <code>FALSE</code> , a list of resources is returned

Value

if `dryrun = TRUE`, a character vector of resource names is returned invisibly; if `dryrun = FALSE`, a list of resources is returned

Examples

```
tuberculosis("GSE103147")
```

Index

tuberculosis, 2