

Package ‘OncoScore’

March 13, 2025

Version 1.35.0

Date 2024-09-20

Title A tool to identify potentially oncogenic genes

Depends R (>= 4.1.0),

Imports biomaRt, grDevices, graphics, utils, methods,

Suggests BiocGenerics, BiocStyle, knitr, testthat,

Description OncoScore is a tool to measure the association of genes to cancer based on citation frequencies in biomedical literature. The score is evaluated from PubMed literature by dynamically updatable web queries.

Encoding UTF-8

License file LICENSE

URL <https://github.com/danro9685/OncoScore>

BugReports <https://github.com/danro9685/OncoScore>

biocViews BiomedicalInformatics

RoxygenNote 7.3.2

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/OncoScore>

git_branch devel

git_last_commit 0ae7426

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2025-03-12

Author Luca De Sano [cre, aut] (ORCID:
<<https://orcid.org/0000-0002-9618-3774>>),
Carlo Gambacorti Passerini [ctb],
Rocco Piazza [ctb],
Daniele Ramazzotti [aut] (ORCID:
<<https://orcid.org/0000-0002-6087-2666>>),
Roberta Spinelli [ctb]

Maintainer Luca De Sano <luca.desano@gmail.com>

Contents

combine.query.results	2
combine.single.matrix	3
compute.frequencies.scores	3
compute.oncoscore	4
compute.oncoscore.from.region	5
compute.oncoscore.timeseries	6
estimate.oncogenes	7
genes	7
get.genes.from.biomart	8
get.list.from.xml	8
get.pubmed.driver.analysis	9
perform.query	9
perform.query.from.region	10
perform.query.timeseries	11
plot.oncoscore	12
plot.oncoscore.timeseries	13
query	14
query.timepoints	14
timepoints	15
try.scan	15
Index	16

combine.query.results *combine.query.results*

Description

Merge a set of genes in a unique one in order to account for possible aliases

Usage

```
combine.query.results(query, genes, new.name)
```

Arguments

query	The result of perform.query, perform.query.timeseries of perform.query.from.region
genes	A list of genes to be merged
new.name	A string containing the new name to be used for the new genes

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
data(query)
combine.query.results(query, c('IDH1', 'IDH2'), 'new_gene')
```

```
combine.single.matrix combine.single.matrix
```

Description

Perform merge procedure on a matrix

Usage

```
combine.single.matrix(query, genes, new.name)
```

Arguments

query	The result of perform.query, perform.query.timeseries or perform.query.from.region
genes	A list of genes to be merged
new.name	A string containing the new name to be used for the new genes

Value

a merged matrix

```
compute.frequencies.scores
compute.frequencies.scores
```

Description

compute the logarithmic scores based on the frequencies of the genes

Usage

```
compute.frequencies.scores(data, filter.threshold = 1, analysis.mode = "Log2")
```

Arguments

data	input data as result of the function perform.query
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logarithmic scores to be computed, i.e., log10, log2, natural log or log5

Value

the computed scores

compute.oncoscore *compute.oncoscore*

Description

compute the OncoScore for a list of genes

Usage

```
compute.oncoscore(  
  data,  
  filter.threshold = 0,  
  analysis.mode = "Log2",  
  cutoff.threshold = 21.09,  
  file = NULL,  
  filter.invalid = TRUE  
)
```

Arguments

`data` input data as result of the function `perform.query`

`filter.threshold` threshold to filter for a minimum number of citations for the genes

`analysis.mode` logarithmic scores to be computed, i.e., log10, log2, natural log or log5

`cutoff.threshold` threshold to be used to asses the oncogenes

`file` should I save the results to text files?

`filter.invalid` auto-remove genes with invalid count

Value

the computed OncoScores and the clusters for the genes

Examples

```
data(query)  
compute.oncoscore(query)
```

```
compute.oncoscore.from.region  
    compute.oncoscore.from.region
```

Description

Perform OncoScore analysis on a given chromosomal region

Usage

```
compute.oncoscore.from.region(  
  chromosome,  
  start = NA,  
  end = NA,  
  gene.num.limit = 100,  
  filter.threshold = NA,  
  analysis.mode = "Log2",  
  cutoff.threshold = 21.09,  
  file = NULL  
)
```

Arguments

chromosome	chromosome to be retrieved
start	initial position to be used
end	final position to be used
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logarithmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to assess the oncogenes
file	should I save the results to text files?

Value

the computed scores

Examples

```
chromosome = 15  
start = 200000  
end = 300000
```

```
compute.oncoscore.timeseries  
    compute.oncoscore.timeseries
```

Description

perform the OncoScore time series analysis for a list of genes and data times

Usage

```
compute.oncoscore.timeseries(  
  data,  
  filter.threshold = 0,  
  analysis.mode = "Log2",  
  cutoff.threshold = 21.09,  
  file = NULL  
)
```

Arguments

data	input data as result of the function perform.query.timeseries
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logarithmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to asses the oncogenes
file	should I save the results to text files?

Value

the performed OncoScores time series analysis

Examples

```
data(query.timepoints)  
compute.oncoscore.timeseries(query.timepoints)
```

estimate.oncogenes	<i>estimate.oncogenes</i>
--------------------	---------------------------

Description

estimate the oncoscore for the genes

Usage

```
estimate.oncogenes(data, cutoff.threshold = 21.09)
```

Arguments

data	input data as result of the function compute.frequencies.scores
cutoff.threshold	threshold to be used to asses the oncogenes

Value

the computed scores and oncogenes

genes	<i>A list of genes</i>
-------	------------------------

Description

This dataset contains a list of genes to be used in the analysis as an example

Usage

```
data(genes)
```

Format

rdata

Value

list of 5 elements

Source

example data

```
get.genes.from.biomart
```

```
get.genes.from.biomart
```

Description

Get a gene list from biomart

Usage

```
get.genes.from.biomart(chromosome, start = NA, end = NA)
```

Arguments

chromosome	chromosome to be retrieved
start	initial position to be used
end	final position to be used

Value

A list of genes

Examples

```
chromosome = 15  
start = 200000  
end = 300000
```

```
get.list.from.xml
```

```
get.list.from.xml
```

Description

process the result of the query

Usage

```
get.list.from.xml(webget)
```

Arguments

webget	The result from the query to PubMed
--------	-------------------------------------

Value

Processed result obtained from the query to PubMed

```
get.pubmed.driver.analysis
      get.pubmed.driver.analysis
```

Description

query PubMed for a list of genes

Usage

```
get.pubmed.driver.analysis(keywords, gene)
```

Arguments

keywords	The set of keywords to be used for the query to PubMed
gene	The name of a gene to be used for the query to PubMed

Value

The frequency for the current gene retrieved with the query on the provided set of keywords

```
perform.query      perform.query
```

Description

perform the query to PubMed

Usage

```
perform.query(list.of.genes, gene.num.limit = 100, custom.search = NA)
```

Arguments

list.of.genes	The list of genes to be used in the queries to PubMed
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
custom.search	A custom set of keywords to be used when querying PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
data(genes)
```

```
perform.query.from.region  
    perform.query.from.region
```

Description

Perform the query to PubMed on a given chromosomal region

Usage

```
perform.query.from.region(  
  chromosome,  
  start = NA,  
  end = NA,  
  gene.num.limit = 100  
)
```

Arguments

<code>chromosome</code>	chromosome to be retrieved
<code>start</code>	initial position to be used
<code>end</code>	final position to be used
<code>gene.num.limit</code>	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed

Examples

```
chromosome = 15  
start = 200000  
end = 300000
```

```
perform.query.timeseries  
    perform.query.timeseries
```

Description

perform the query to PubMed for the time series analysis

Usage

```
perform.query.timeseries(  
  list.of.genes,  
  list.of.datatimes,  
  gene.num.limit = 100,  
  timepoints.limit = 10,  
  custom.search = NA  
)
```

Arguments

`list.of.genes` The list of genes to be used in the queries to PubMed

`list.of.datatimes`
The list of time points to be used in the queries to PubMed

`gene.num.limit` A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed

`timepoints.limit`
A limit to the time points to be considered in the analysis; this is done to limit the number of queries to PubMed

`custom.search` A custom set of keywords to be used when querying PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retrieved on PubMed at the specified time points

Examples

```
data(genes)  
data(timepoints)
```

plot.oncoscore *plot.oncoscore*

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore'  
plot(  
  x,  
  gene.number = 5,  
  main = "OncoScore",  
  xlab = "score",  
  ylab = "genes",  
  file = NA,  
  ...  
)
```

Arguments

x	input data as result of the function compute.OncoScore
gene.number	number of genes to print
main	the title
xlab	description of x asix (defaul score)
ylab	description of y asix (defaul genes)
file	where to save the plot
...	additional parameter to pass to the barplot function

Value

A plot

Examples

```
data(query)  
result = compute.oncoscore(query)  
plot.oncoscore(result)
```

```
plot.oncoscore.timeseries  
plot.oncoscore.timeseries
```

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore.timeseries'  
plot(  
  x,  
  gene.number = 5,  
  incremental = FALSE,  
  relative = FALSE,  
  main = "OncoScore",  
  xlab = "timepoints",  
  ylab = "score",  
  legend.pos = "top",  
  file = NA,  
  ...  
)
```

Arguments

x	input data as result of the function compute.OncoScore
gene.number	number of genes to print
incremental	display the OncoScore increment
relative	display the incrementa as relative value
main	the title
xlab	description of x asix (defaul score)
ylab	description of y asix (defaul genes)
legend.pos	Position of the legend
file	where to save the plot
...	additional parameter to pass to the lines function

Value

A plot

Examples

```
data(query.timepoints)
result = compute.oncoscore.timeseries(query.timepoints)
plot.oncoscore.timeseries(result)
```

query	<i>The result of perform.web.query on genes</i>
-------	---

Description

This dataset contains the result of perform.web.query on genes

Usage

```
data(query)
```

Format

rdata

Value

matrix 5 x 2

Source

example data

query.timepoints	<i>The result of perform.time.series.query on genes and timepoints</i>
------------------	--

Description

This dataset contains the result of perform.time.series.query on genes and timepoints

Usage

```
data(query.timepoints)
```

Format

rdata

Value

list of 5 matrix 5 x 2

Source

example data

timepoints	<i>A list of timepoints</i>
------------	-----------------------------

Description

This dataset contains a list of time points to be used in the analysis as an example

Usage

```
data(timepoints)
```

Format

rdata

Value

list of 5 elements

Source

example data

try.scan	<i>try.scan</i>
----------	-----------------

Description

try to query the given URL

Usage

```
try.scan(getURL)
```

Arguments

getURL The given URL

Value

Result obtained from PubMed

Index

`combine.query.results`, 2
`combine.single.matrix`, 3
`compute.frequencies.scores`, 3
`compute.oncoscore`, 4
`compute.oncoscore.from.region`, 5
`compute.oncoscore.timeseries`, 6

`estimate.oncogenes`, 7

`genes`, 7
`get.genes.from.biomart`, 8
`get.list.from.xml`, 8
`get.pubmed.driver.analysis`, 9

`perform.query`, 9
`perform.query.from.region`, 10
`perform.query.timeseries`, 11
`plot.oncoscore`, 12
`plot.oncoscore.timeseries`, 13

`query`, 14
`query.timepoints`, 14

`timepoints`, 15
`try.scan`, 15