Package 'enrichplot'

May 7, 2025

Title Visualization of Functional Enrichment Result

Version 1.28.2

Description The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis.
It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Depends R (>= 3.5.0)

Imports aplot (>= 0.2.1), DOSE (>= 3.31.2), ggfun (>= 0.1.7), ggnewscale, ggplot2, ggrepel (>= 0.9.0), ggtangle (>= 0.0.5), graphics, grid, igraph, methods, plyr, purrr, RColorBrewer, reshape2, rlang, stats, utils, scatterpie, GOSemSim (>= 2.31.2), magrittr, ggtree, yulab.utils (>= 0.1.6)

Suggests clusterProfiler, dplyr, europepmc, ggarchery, ggupset, glue, knitr, rmarkdown, org.Hs.eg.db, prettydoc, tibble, tidyr, ggforce, ggHoriPlot, AnnotationDbi, ggplotify, ggridges, grDevices, gridExtra, ggstar, scales, ggtreeExtra, tidydr

Remotes YuLab-SMU/tidydr

VignetteBuilder knitr

License Artistic-2.0

URL https://yulab-smu.top/contribution-knowledge-mining/

BugReports https://github.com/GuangchuangYu/enrichplot/issues

biocViews Annotation, GeneSetEnrichment, GO, KEGG, Pathways, Software, Visualization

Encoding UTF-8

RoxygenNote 7.3.2

git_url https://git.bioconductor.org/packages/enrichplot

git_branch RELEASE_3_21

git_last_commit 8109fe0

git_last_commit_date 2025-04-28

Repository Bioconductor 3.21

Date/Publication 2025-05-07

Author Guangchuang Yu [aut, cre] (ORCID:
<https://orcid.org/0000-0002-6485-8781>),
Chun-Hui Gao [ctb] (ORCID: <https://orcid.org/0000-0002-1445-7939>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Contents

enrichplot-package . . . 3
autofacet . . . 3
barplot.enrichResult . . . 4
cnetplot.enrichResult . . . 5
color_palette . . . 7
dotplot . . . 7
dotplot2 . . . 11
emapplot . . . 12
fortify.compareClusterResult . . . 14
geom_gsea_gene . . . 15
ggtable . . . 16
goplot . . . 17
gseadist . . . 18
gseaplot . . . 19
gseaplot2 . . . 20
gsearank . . . 21
gsInfo . . . 22
heatplot . . . 22
hplot . . . 23
pairwise_termsim . . . 24
plotting.clusterProfile . . . 25
pmcplot . . . 26
reexports . . . 27
ridgeplot . . . 27
set_enrichplot_color . . . 29
ssplot . . . 29
treeplot . . . 32
upsetplot . . . 36
volplot . . . 37

Index **40**

enrichplot-package *enrichplot: Visualization of Functional Enrichment Result*

Description

The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> (ORCID)

Other contributors:

- Chun-Hui Gao <gaospecial@gmail.com> (ORCID) [contributor]

See Also

Useful links:

- https://yulab-smu.top/contribution-knowledge-mining/
- Report bugs at https://github.com/GuangchuangYu/enrichplot/issues

autofacet *automatically split barplot or dotplot into several facets*

Description

automatically split barplot or dotplot into several facets

Usage

```
autofacet(by = "row", scales = "free", levels = NULL)
```

Arguments

by	one of 'row' or 'column'
scales	wether 'fixed' or 'free'
levels	set facet levels

Value

a ggplot object

barplot.enrichResult *barplot*

Description

barplot of enrichResult

Usage

```
## S3 method for class 'enrichResult'
barplot(
  height,
  x = "Count",
  color = "p.adjust",
  showCategory = 8,
  font.size = 12,
  title = "",
  label_format = 30,
  ...
)
```

Arguments

height	enrichResult object
x	one of 'Count' and 'GeneRatio'
color	one of 'pvalue', 'p.adjust' and 'qvalue'
showCategory	number of categories to show
font.size	font size
title	plot title
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer that 30 characters
...	other parameter, ignored

Value

ggplot object

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
barplot(x)
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
barplot(x, showCategory = 10)
```

```
categorys <- c("urinary bladder cancer", "bronchiolitis obliterans",
               "aortic aneurysm", "esophageal cancer")
barplot(x, showCategory = categorys)
```

`cnetplot.enrichResult` *cnetplot*

Description

category-gene-network plot

Usage

```
## S3 method for class 'enrichResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
  color_item = "#B3B3B3",
  size_item = 1,
  color_edge = "grey",
  size_edge = 0.5,
  node_label = "all",
  foldChange = NULL,
  hilight = "none",
  hilight_alpha = 0.3,
  ...
)

## S3 method for class 'gseaResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
  color_item = "#B3B3B3",
  size_item = 1,
  color_edge = "grey",
  size_edge = 0.5,
  node_label = "all",
  foldChange = NULL,
  hilight = "none",
  hilight_alpha = 0.3,
  ...
```

```
)

## S3 method for class 'compareClusterResult'
cnetplot(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 5,
  color_category = "#E5C494",
  size_category = 1,
  color_item = "#B3B3B3",
  size_item = 1,
  color_edge = "grey",
  size_edge = 0.5,
  node_label = "all",
  foldChange = NULL,
  hilight = "none",
  hilight_alpha = 0.3,
  pie = "equal",
  ...
)
```

Arguments

x	input object
layout	network layout
showCategory	selected category to be displayed
color_category	color of category node
size_category	relative size of the category
color_item	color of item node
size_item	relative size of the item (e.g., genes)
color_edge	color of edge
size_edge	relative size of edge
node_label	one of 'all', 'none', 'category', 'item', 'exclusive' or 'share'
foldChange	numeric values to color the item (e.g, foldChange of gene expression values)
hilight	selected category to be highlighted
hilight_alpha	transparent value for not selected to be highlight
...	additional parameters
pie	one of 'equal' or 'Count' to set the slice ratio of the pies

See Also

[cnetplot][ggtangle::cnetplot]

color_palette *color_palette*

Description

create color palette for continuous data

Usage

```
color_palette(colors)
```

Arguments

colors	colors of length >=2

Value

color vector

Author(s)

guangchuang yu

Examples

```
color_palette(c("red", "yellow", "green"))
```

dotplot *dotplot*

Description

dotplot for enrichment result

Usage

```
dotplot(object, ...)

## S4 method for signature 'enrichResult'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
```

```
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'compareClusterResult'
dotplot(
  object,
  x = "Cluster",
  color = "p.adjust",
  showCategory = 5,
  split = NULL,
  font.size = 12,
  title = "",
  by = "geneRatio",
  size = NULL,
  includeAll = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'enrichResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
```

```
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

dotplot.enrichResult(
  object,
  x = "geneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  decreasing = TRUE
)

dotplot.compareClusterResult(
  object,
  x = "Cluster",
  colorBy = "p.adjust",
  showCategory = 5,
  by = "geneRatio",
  size = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  font.size = 12,
  title = "",
  label_format = 30,
  group = FALSE,
  shape = FALSE,
```

```
  facet = NULL,
  strip_width = 15
)
```

Arguments

object	compareClusterResult object
...	additional parameters
x	variable for x-axis, one of 'GeneRatio' and 'Count'
color	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
showCategory	A number or a list of terms. If it is a number, the first n terms will be displayed. If it is a list of terms, the selected terms will be displayed.
size	variable that used to scale the sizes of categories, one of "geneRatio", "Percentage" and "count"
split	apply 'showCategory' to each category specified by the 'split', e.g., "ONTOLOGY", "category" and "intersect". Default is NULL and do nothing
font.size	font size
title	figure title
orderBy	The order of the Y-axis
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer that 30 characters
by	one of "geneRatio", "Percentage" and "count"
includeAll	logical
decreasing	logical. Should the orderBy order be increasing or decreasing?
colorBy	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
group	a logical value, whether to connect the nodes of the same group with wires.
shape	a logical value, whether to use nodes of different shapes to distinguish the group it belongs to
facet	apply 'facet_grid' to the plot by specified variable, e.g., "ONTOLOGY", "category" and "intersect".
strip_width	width of strip text, a.k.a facet label.

Value

plot

Author(s)

Guangchuang Yu

Examples

```
## Not run:
    library(DOSE)
    data(geneList)
    de <- names(geneList)[1:100]
    x <- enrichDO(de)
    dotplot(x)
   # use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
    dotplot(x, showCategory = 10)
    categorys <- c("pre-malignant neoplasm", "intestinal disease",
                   "breast ductal carcinoma", "non-small cell lung carcinoma")
    dotplot(x, showCategory = categorys)
    # It can also graph compareClusterResult
    data(gcSample)
    library(clusterProfiler)
    library(DOSE)
    library(org.Hs.eg.db)
    data(gcSample)
    xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
    xx2 <- pairwise_termsim(xx)
    library(ggstar)
    dotplot(xx2)
    dotplot(xx2, shape = TRUE)
    dotplot(xx2, group = TRUE)
    dotplot(xx2, x = "GeneRatio", group = TRUE, size = "count")

## End(Not run)
```

`dotplot2` *dotplot2*

Description

compare two clusters in the compareClusterResult object

Usage

```
dotplot2(object, x = "FoldEnrichment", vars = NULL, label = "auto", ...)
```

Arguments

`object`	a compareClusterResult object
`x`	selected variable to visualize in x-axis
`vars`	selected Clusters to be compared, only length of two is supported
`label`	to label the Clusters in the plot, should be a named vector
`...`	additional parameters passed to dotplot

Value

a ggplot object

Author(s)

Guangchuang Yu

`emapplot` *emapplot*

Description

Enrichment Map for enrichment result of over-representation test or gene set enrichment analysis

Usage

```
emapplot(x, ...)

## S4 method for signature 'enrichResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
emapplot(x, showCategory = 30, ...)

emapplot_internal(
  x,
  layout = igraph::layout_with_kk,
  showCategory = 30,
  color = "p.adjust",
  size_category = 1,
  min_edge = 0.2,
  color_edge = "grey",
  size_edge = 0.5,
  node_label = "category",
  pie = "equal",
  group = FALSE,
  group_style = "ggforce",
  label_group_style = "shawdowtext",
  label_format = 30,
  clusterFunction = stats::kmeans,
  nWords = 4,
  nCluster = NULL
)
```

Arguments

x	Enrichment result.
...	Additional parameters
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
layout	igraph layout
color	Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'.
size_category	relative size of the categories
min_edge	The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2.
color_edge	color of the network edge
size_edge	relative size of edge width
node_label	Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'.
pie	one of 'equal' or 'Count' to set the slice ratio of the pies
group	logical, if TRUE, group the category.
group_style	style of ellipse, one of "ggforce" an "polygon".
label_group_style	style of group label, one of "shadowtext" and "ggforce".
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
clusterFunction	function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam.
nWords	Numeric, the number of words in the cluster tags, the default value is 4.
nCluster	Numeric, the number of clusters, the default value is square root of the number of nodes.

Details

This function visualizes gene sets as a network (i.e. enrichment map). Mutually overlapping gene sets tend to cluster together, making it easier for interpretation. When the similarity between terms meets a certain threshold (default is 0.2, adjusted by parameter 'min_edge'), there will be edges between terms. The stronger the similarity, the shorter and thicker the edges. The similarity between terms is obtained by function 'pairwise_termsim', the details of similarity calculation can be found in its documentation: pairwise_termsim.

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
    library(DOSE)
    data(geneList)
    de <- names(geneList)[1:100]
    x <- enrichDO(de)
    x2 <- pairwise_termsim(x)
    emapplot(x2)
    # use `layout` to change the layout of map
    emapplot(x2, layout = "star")
   # use `showCategory` to  select the displayed terms. It can be a number of a vector of terms.
    emapplot(x2, showCategory = 10)
    categorys <- c("pre-malignant neoplasm", "intestinal disease",
                   "breast ductal carcinoma")
    emapplot(x2, showCategory = categorys)

    # It can also graph compareClusterResult
    library(clusterProfiler)
    library(DOSE)
    library(org.Hs.eg.db)
    data(gcSample)
    xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
    xx2 <- pairwise_termsim(xx)
    emapplot(xx2)

## End(Not run)
```

---

fortify.compareClusterResult

fortify

Description

convert compareClusterResult to a data.frame that ready for plot

convert enrichResult object for ggplot2

Usage

```
## S3 method for class 'compareClusterResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  ...
)
```

```
## S3 method for class 'enrichResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "Count",
  order = FALSE,
  drop = FALSE,
  split = NULL,
  ...
)
```

Arguments

model	'enrichResult' or 'compareClusterResult' object
data	not use here
showCategory	Category numbers to show
by	one of Count and GeneRatio
split	separate result by 'split' variable
includeAll	logical
...	additional parameter
order	logical
drop	logical

Value

data.frame

data.frame

Author(s)

Guangchuang Yu

---

geom_gsea_gene *geom_gsea_gene*

Description

label genes in running score plot

Usage

```
geom_gsea_gene(
  genes,
  mapping = NULL,
  geom = ggplot2::geom_text,
  ...,
  geneSet = NULL
)
```

Arguments

genes	selected genes to be labeled
mapping	aesthetic mapping, default is NULL
geom	geometric layer to plot the gene labels, default is geom_text
...	additional parameters passed to the 'geom'
geneSet	choose which gene set(s) to be label if the plot contains multiple gene sets

Value

ggplot object

Author(s)

Guangchuang Yu

---

ggtable *ggtable*

Description

plot table

Usage

```
ggtable(d, p = NULL)
```

Arguments

d	data frame
p	ggplot object to extract color to color rownames(d), optional

Value

ggplot object

Author(s)

guangchuang yu

goplot *goplot*

Description

plot induced GO DAG of significant terms

Usage

```
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

## S4 method for signature 'enrichResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = igraph::layout_with_sugiyama,
  geom = "text",
  ...
)

## S4 method for signature 'gseaResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = igraph::layout_with_sugiyama,
  geom = "text",
  ...
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
color	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
layout	layout of the map
geom	label geom, one of 'label' or 'text'
...	additional parameter

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
 library(clusterProfiler)
  data(geneList, package = "DOSE")
 de <- names(geneList)[1:100]
 yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
    goplot(yy)
    goplot(yy, showCategory = 5)

## End(Not run)
```

`gseadist` *gseadist*

Description

plot logFC distribution of selected gene sets

Usage

```
gseadist(x, IDs, type = "density")
```

Arguments

`x`	GSEA result
`IDs`	gene set IDs
`type`	one of 'density' or 'boxplot'

Value

distribution plot

Author(s)

Guangchuang Yu

gseaplot *gseaplot*

Description

visualize analyzing result of GSEA

Usage

```
gseaplot(x, geneSetID, by = "all", title = "", ...)

## S4 method for signature 'gseaResult'
gseaplot(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
  color.vline = "#FA5860",
  ...
)

gseaplot.gseaResult(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
  color.vline = "#FA5860",
  ...
)
```

Arguments

x	object of gsea result
geneSetID	geneSet ID
by	one of "runningScore" or "position"
title	plot title
...	additional parameters
color	color of line segments
color.line	color of running enrichment score line
color.vline	color of vertical line which indicating the maximum/minimal running enrichment score

Details

plotting function for gseaResult

Value

ggplot2 object

ggplot2 object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseDO(geneList)
gseaplot(x, geneSetID=1)
```

`gseaplot2` *gseaplot2*

Description

GSEA plot that mimic the plot generated by broad institute's GSEA software

Usage

```
gseaplot2(
  x,
  geneSetID,
  title = "",
  color = "green",
  base_size = 11,
  rel_heights = c(1.5, 0.5, 1),
  subplots = 1:3,
  pvalue_table = FALSE,
  ES_geom = "line"
)
```

Arguments

`x`	gseaResult object
`geneSetID`	gene set ID
`title`	plot title
`color`	color of running enrichment score line

base_size	base font size
rel_heights	relative heights of subplots
subplots	which subplots to be displayed
pvalue_table	whether add pvalue table
ES_geom	geom for plotting running enrichment score, one of 'line' or 'dot'

Value

plot

Author(s)

Guangchuang Yu

---

gsearank *gsearank*

Description

plot ranked list of genes with running enrichment score as bar height

Usage

```
gsearank(x, geneSetID, title = "", output = "plot")
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title
output	one of 'plot' or 'table' (for exporting data)

Value

ggplot object

Author(s)

Guangchuang Yu

gsInfo *gsInfo*

Description

extract gsea result of selected geneSet

Usage

```
gsInfo(object, geneSetID)
```

Arguments

object	gseaResult object
geneSetID	gene set ID

Value

data.frame

Author(s)

Guangchuang Yu

heatplot *heatplot*

Description

heatmap like plot for functional classification

Usage

```
heatplot(x, showCategory = 30, ...)

## S4 method for signature 'enrichResult'
heatplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
heatplot(x, showCategory = 30, ...)

heatplot.enrichResult(
  x,
  showCategory = 30,
  symbol = "rect",
```

```
  foldChange = NULL,
  pvalue = NULL,
  label_format = 30
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
...	Additional parameters
symbol	symbol of the nodes, one of "rect"(the default) and "dot" by default wraps names longer that 30 characters
foldChange	fold Change.
pvalue	pvalue of genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
heatplot(x)
```

---

hplot *hplot*

Description

Horizontal plot for GSEA result

Usage

```
hplot(x, geneSetID)
```

Arguments

x	gseaResult object
geneSetID	gene set ID

Value

horizontal plot

Author(s)

Guangchuang Yu

`pairwise_termsim` *pairwise_termsim*

Description

Get the similarity matrix

Usage

```
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'enrichResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'gseaResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'compareClusterResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

pairwise_termsim.enrichResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)

pairwise_termsim.compareClusterResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)
```

Arguments

x	enrichment result.
method	method of calculating the similarity between nodes, one of "Resnik", "Lin", "Rel", "Jiang" , "Wang" and "JC"(Jaccard similarity coefficient) methods.
semData	GOSemSimDATA object, can be obtained through godata function in GOSemSim package.
showCategory	number of enriched terms to display, default value is 200.

Details

This function add similarity matrix to the termsim slot of enrichment result. Users can use the ‘method‘ parameter to select the method of calculating similarity. The Jaccard correlation coefficient(JC) is used by default, and it applies to all situations. When users want to calculate the correlation between GO terms or DO terms, they can also choose "Resnik", "Lin", "Rel" or "Jiang" (they are semantic similarity calculation methods from GOSemSim packages), and at this time, the user needs to provide ‘semData‘ parameter, which can be obtained through godata function in GOSemSim package.

Examples

```
## Not run:
    library(clusterProfiler)
    library(org.Hs.eg.db)
    library(enrichplot)
    library(GOSemSim)
    library(DOSE)
    data(geneList)
    gene <- names(geneList)[abs(geneList) > 2]
    ego <- enrichGO(gene  = gene,
        universe      = names(geneList),
        OrgDb         = org.Hs.eg.db,
        ont           = "BP",
        pAdjustMethod = "BH",
        pvalueCutoff  = 0.01,
        qvalueCutoff  = 0.05,
        readable      = TRUE)
    d <- godata('org.Hs.eg.db', ont="BP")
    ego2 <- pairwise_termsim(ego, method="Wang", semData = d)
    emapplot(ego2)
    emapplot_cluster(ego2)

## End(Not run)
```

---

plotting.clusterProfile *plotting-clusterProfile*

Description

Internal plot function for plotting compareClusterResult

Usage

```
plotting.clusterProfile(
  clProf.reshape.df,
  x = ~Cluster,
  type = "dot",
  colorBy = "p.adjust",
  by = "geneRatio",
  title = "",
  font.size = 12
)
```

Arguments

clProf.reshape.df	data frame of compareCluster result
x	x variable
type	one of dot and bar
colorBy	one of pvalue or p.adjust
by	one of percentage and count
title	graph title
font.size	graph font size

Value

ggplot object

Author(s)

Guangchuang Yu https://yulab-smu.top

---

pmcplot *pmcplot*

Description

PubMed Central Trend plot

Usage

```
pmcplot(query, period, proportion = TRUE)
```

Arguments

query	query terms
period	period of query in the unit of year
proportion	If TRUE, use query_hits/all_hits, otherwise use query_hits

Value

ggplot object

Author(s)

guangchuang yu

---

reexports *Objects exported from other packages*

Description

These objects are imported from other packages. Follow the links below to see their documentation.

aplot plot_list

ggplot2 facet_grid, ggtitle

ggtangle cnetplot, geom_cnet_label

---

ridgeplot *ridgeplot*

Description

ridgeline plot for GSEA result

Usage

```
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
ridgeplot(
```

```
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

ridgeplot.gseaResult(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  orderBy = "NES",
  decreasing = FALSE
)
```

Arguments

x	gseaResult object
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
fill	one of "pvalue", "p.adjust", "qvalue"
core_enrichment	whether only using core_enriched genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
...	additional parameters by default wraps names longer that 30 characters
orderBy	The order of the Y-axis
decreasing	logical. Should the orderBy order be increasing or decreasing?

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseDO(geneList)
ridgeplot(x)
```

set_enrichplot_color *set_enrichplot_color*

Description

helper function to set color for enrichplot

Usage

```
set_enrichplot_color(
  colors = get_enrichplot_color(2),
  type = "color",
  name = NULL,
  .fun = NULL,
  reverse = TRUE,
  ...
)
```

Arguments

colors	user provided color vector
type	one of 'color', 'colour' or 'fill'
name	name of the color legend
.fun	force to use user provided color scale function
reverse	whether reverse the color scheme, default is TRUE as it is more significant for lower pvalue
...	additional parameter that passed to the color scale function

Value

a color scale

ssplot *ssplot*

Description

Similarity space plot of enrichment analysis results.

Usage

```
ssplot(x, ...)

## S4 method for signature 'enrichResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
ssplot(x, showCategory = 30, ...)

ssplot.enrichResult(
  x,
  showCategory = 30,
  drfun = NULL,
  dr.params = list(),
  group = TRUE,
  node_label = "group",
  ...
)

ssplot.compareClusterResult(
  x,
  showCategory = 30,
  pie = "equal",
  drfun = NULL,
  dr.params = list(),
  group = TRUE,
  node_label = "group",
  ...
)
```

Arguments

x	Enrichment result.
...	additional parameters additional parameters can refer the following parameters. • `color` Variable that used to color enriched terms, e.g. 'pvalue','p.adjust' or 'qvalue'. the starting position of each text label. • `size_edge` Scale of line width. • `min_edge` The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2. • `size_category` Number indicating the amount by which plotting category nodes should be scaled relative to the default. • `label_style` style of group label, one of "shadowtext" and "ggforce".

- group Logical, if TRUE, the grouping legend will be displayed. The default is FALSE.
- nWords Numeric, the number of words in the cluster tags, the default value is 4.
- label_format a numeric value sets wrap length, alternatively a custom function to format axis labels.
- clusterFunction function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam.
- nCluster Numeric, the number of clusters, the default value is square root of the number of nodes.

additional parameters can refer the emapplot function: emapplot.

showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
drfun	The function used for dimension reduction, e.g. stats::cmdscale (the default), vegan::metaMDS, or ape::pcoa.
dr.params	list, the parameters of tidydr::dr. one of 'category', 'group', 'all' and 'none'.
group	logical, if TRUE, group the category.
node_label	Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'.
pie	one of 'equal' or 'Count' to set the slice ratio of the pies

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
    library(clusterProfiler)
    library(org.Hs.eg.db)
    library(enrichplot)
    library(GOSemSim)
    library(DOSE)
    data(geneList)
    gene <- names(geneList)[abs(geneList) > 2]
    ego <- enrichGO(gene  = gene,
        universe      = names(geneList),
        OrgDb         = org.Hs.eg.db,
        ont           = "BP",
        pAdjustMethod = "BH",
        pvalueCutoff  = 0.01,
        qvalueCutoff  = 0.05,
        readable      = TRUE)
    d <- godata('org.Hs.eg.db', ont="BP")
    ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
```

```
    ssplot(ego2)

## End(Not run)
```

---

treeplot *treeplot*

Description

Functional grouping tree diagram for enrichment result of over-representation test or gene set enrichment analysis.

Usage

```
treeplot(x, ...)

## S4 method for signature 'enrichResult'
treeplot(x, ...)

## S4 method for signature 'gseaResult'
treeplot(x, ...)

## S4 method for signature 'compareClusterResult'
treeplot(x, ...)

treeplot.enrichResult(
  x,
  showCategory = 30,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  label_format = NULL,
  label_format_cladelab = 30,
  label_format_tiplab = NULL,
  fontsize = 4,
  offset = rel(1),
  offset_tiplab = rel(1),
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  hexpand = 0.1,
  align = "both",
  hilight.params = list(hilight = TRUE, align = "both"),
 offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
 cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
```

```
    label_format = 30),
  ...
)

treeplot.compareClusterResult(
  x,
  showCategory = 5,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  split = NULL,
  label_format = NULL,
  label_format_cladelab = 30,
  label_format_tiplab = NULL,
  fontsize = 4,
  offset = rel(1),
  pie = "equal",
  legend_n = 3,
  offset_tiplab = rel(1),
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  geneClusterPanel = "heatMap",
  hexpand = 0.1,
  align = "both",
 cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
    label_format = 30),
  hilight.params = list(hilight = TRUE, align = "both"),
 clusterPanel.params = list(clusterPanel = "heatMap", pie = "equal", legend_n = 3,
    colnames_angle = 0),
 offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
  ...
)
```

Arguments

x	enrichment result.
...	additional parameters
showCategory	number of enriched terms to display
color	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
nWords	The number of words in the cluster tags. Will be removed in the next version.
nCluster	The number of clusters, the default value is 5. Will be removed in the next version.
cex_category	Number indicating the amount by which plotting category. nodes should be scaled relative to the default. Will be removed in the next version.

label_format a numeric value sets wrap length, alternatively a custom function to format axis labels.

label_format_cladelab label_format for group labels, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version.

label_format_tiplab label_format for tiplabs, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version.

fontsize The size of text, default is 4.

offset rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is rel(1), meaning 1 * 1.2 * x_range_of_tree plus distance_between_tree_and_tiplab (1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)). Will be removed in the next version.

offset_tiplab tiplab offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is rel(1), when geneClusterPanel = "pie", meaning 1 * max_radius_of_the_pies; when geneClusterPanel = "heatMap", meaning 1 * 0.16 * column_number_of_heatMap * x_range_of_tree; when geneClusterPanel = "dotplot", meaning 1 * 0.09 * column_number_of_dotplot * x_range_of_tree. Will be removed in the next version.

hclust_method Method of hclust. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC). Will be removed in the next version.

group_color A vector of group colors, the length of the vector should be the same as nCluster. Will be removed in the next version.

extend Numeric, extend the length of bar, default is 0.3. Will be removed in the next version.

hilight Logical value, if TRUE(default), add ggtree::geom_hilight() layer. Will be removed in the next version.

hexpand expand x limits by amount of xrange * hexpand. Will be removed in the next version.

align control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'. Will be removed in the next version.

hilight.params list, the parameters to control the attributes of highlight layer. see the hilight.params in the following. hilight.params control the attributes of highlight layer, it can be referred to the following parameters:

- hilight Logical value, if TRUE(default), add ggtree::geom_hilight() layer.
- align control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'.

offset.params list, the parameters to control the offset. see the offset.params in the following. offset.params control the attributes of offset, it can be referred to the following parameters:

- bar_tree rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is rel(1), meaning 1 * 1.2 * x_range_of_tree plus distance_between_tree_and_tiplab (1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)).

- `tiplab` tiplab offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is rel(1), when clusterPanel = "pie", meaning 1 * max_radius_of_the_pies; when clusterPanel = "heatMap", meaning 1 * 0.16 * column_number_of_heatMap * x_range_of_tree; when clusterPanel = "dotplot", meaning 1 * 0.09 * column_number_of_dotplot * x_range_of_tree.
- `extend` Numeric, extend the length of bar, default is 0.3.
- `hexpand` expand x limits by amount of xrange * hexpand.

`cluster.params` list, the parameters to control the attributes of highlighted nodes and edges. see the cluster.params in the following. cluster.params control the attributes of highlight, it can be referred to the following parameters:

- `method` function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam.
- `n` Numeric, the number of clusters, the default value is square root of the number of nodes.
- `color` A vector of group colors, the length of the vector should be the same as nCluster.
- `label_words_n` Numeric, the number of words in the cluster tags, the default value is 4.
- `label_format` A numeric value sets wrap length, alternatively a custom function to format axis labels.

`split` Separate result by 'category' variable.

`pie` Used only when geneClusterPanel = "pie", proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'. Will be removed in the next version.

`legend_n` Number of circle in legend, the default value is 3. Will be removed in the next version.

`geneClusterPanel` one of "heatMap"(default), "dotplot", "pie". Will be removed in the next version.

`clusterPanel.params` list, the parameters to control the attributes of cluster panel. see the clusterPanel.params in the following. clusterPanel.params control the attributes of cluster panel, it can be referred to the following parameters:

- `clusterPanel` one of "heatMap"(default), "dotplot", "pie".
- `pie` pUsed only when ClusterPanel = "pie", proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'.
- `legend_n` number of circle in legend.
- `colnames_angle` set the angle of colnames.

Details

This function visualizes gene sets as a tree. Gene sets with high similarity tend to cluster together, making it easier for interpretation.

Value

ggplot object

Examples

```
## Not run:
    library(clusterProfiler)
    library(org.Hs.eg.db)
    library(enrichplot)
    library(GOSemSim)
    library(ggplot2)
    library(DOSE)
    data(geneList)
    gene <- names(geneList)[abs(geneList) > 2]
    ego <- enrichGO(gene  = gene,
        universe      = names(geneList),
        OrgDb         = org.Hs.eg.db,
        ont           = "BP",
        pAdjustMethod = "BH",
        pvalueCutoff  = 0.01,
        qvalueCutoff  = 0.05,
        readable      = TRUE)
    d <- godata('org.Hs.eg.db', ont="BP")
    ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
    treeplot(ego2, showCategory = 30)
    # use `hilight = FALSE` to remove ggtree::geom_hilight() layer.
    treeplot(ego2, showCategory = 30, hilight = FALSE)
    # use `offset` parameter to adjust the distance of bar and tree.
    treeplot(ego2, showCategory = 30, hilight = FALSE, offset = rel(1.5))
    # use `offset_tiplab` parameter to adjust the distance of nodes and branches.
    treeplot(ego2, showCategory = 30, hilight = FALSE, offset_tiplab = rel(1.5))
    keep <- rownames(ego2@termsim)[c(1:10, 16:20)]
    keep
    treeplot(ego2, showCategory = keep)
    treeplot(ego2, showCategory = 20,
        group_color = c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442"))
    # It can also graph compareClusterResult
    data(gcSample)
    xx <- compareCluster(gcSample, fun="enrichKEGG",
                         organism="hsa", pvalueCutoff=0.05)
    xx <- pairwise_termsim(xx)
    treeplot(xx)

    # use `geneClusterPanel` to change the gene cluster panel.
    treeplot(xx, geneClusterPanel = "dotplot")

    treeplot(xx, geneClusterPanel = "pie")

## End(Not run)
```

---

upsetplot *upsetplot method*

Description

upsetplot method generics

Usage

```
upsetplot(x, ...)

## S4 method for signature 'enrichResult'
upsetplot(x, n = 10, ...)

## S4 method for signature 'gseaResult'
upsetplot(x, n = 10, ...)
```

Arguments

x	object
...	additional parameters
n	number of categories to be plotted

Value

plot

Author(s)

Guangchuang Yu

Examples

```
require(DOSE)
data(geneList)
de=names(geneList)[1:100]
x <- enrichDO(de)
upsetplot(x, 8)
```

---

volplot *volplot*

Description

volcano plot for enrichment result

Usage

```
volplot(
  x,
  color = "zScore",
  xintercept = 1,
  yintercept = 2,
  showCategory = 5,
  label_format = 30,
  ...
)

## S4 method for signature 'enrichResult'
volplot(
  x,
  color = "zScore",
  xintercept = 1,
  yintercept = 2,
  showCategory = 5,
  label_format = 30,
  ...
)

volplot.enrichResult(
  x,
  color = "zScore",
  xintercept = 1,
  yintercept = 2,
  showCategory = 5,
  label_format = 30,
  font.size = 12,
  size = 5
)
```

Arguments

x	enrichment result.
color	selected variable to color the dots
xintercept	value to set x intercept
yintercept	value to set y intercept
showCategory	number of most significant enriched terms or selected terms to display determined by the variable selected to color the dots
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
...	Additional parameters
font.size	font size for ‘theme_dose()‘
size	font size to label selected categories specified by showCategory

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
volplot(x)
```

Index

∗ **internal**
    enrichplot-package, 3
    reexports, 27

autofacet, 3

barplot.enrichResult, 4

cnetplot, *27*
cnetplot *(*reexports*)*, 27
cnetplot.compareClusterResult *(*cnetplot.enrichResult*)*, 5
cnetplot.enrichResult, 5
cnetplot.gseaResult *(*cnetplot.enrichResult*)*, 5
color_palette, 7

dotplot, 7
dotplot,compareClusterResult,ANY-method *(*dotplot*)*, 7
dotplot,compareClusterResult-method *(*dotplot*)*, 7
dotplot,enrichResult-method *(*dotplot*)*, 7
dotplot,enrichResultList,ANY-method *(*dotplot*)*, 7
dotplot,enrichResultList-method *(*dotplot*)*, 7
dotplot,gseaResult-method *(*dotplot*)*, 7
dotplot,gseaResultList,ANY-method *(*dotplot*)*, 7
dotplot,gseaResultList-method *(*dotplot*)*, 7
dotplot.compareClusterResult *(*dotplot*)*, 7
dotplot.enrichResult *(*dotplot*)*, 7
dotplot2, 11

emapplot, 12, *31*
emapplot,compareClusterResult-method *(*emapplot*)*, 12
emapplot,enrichResult-method *(*emapplot*)*, 12
emapplot,gseaResult-method *(*emapplot*)*, 12
emapplot_internal *(*emapplot*)*, 12
enrichplot *(*enrichplot-package*)*, 3
enrichplot-package, 3

facet_grid, *27*
facet_grid *(*reexports*)*, 27
fortify.compareClusterResult, 14
fortify.enrichResult *(*fortify.compareClusterResult*)*, 14

geom_cnet_label, *27*
geom_cnet_label *(*reexports*)*, 27
geom_gsea_gene, 15
ggtable, 16
ggtitle, *27*
ggtitle *(*reexports*)*, 27
godata, *25*
goplot, 17
goplot,enrichResult-method *(*goplot*)*, 17
goplot,gseaResult-method *(*goplot*)*, 17
gseadist, 18
gseaplot, 19
gseaplot,gseaResult-method *(*gseaplot*)*, 19
gseaplot.gseaResult *(*gseaplot*)*, 19
gseaplot2, 20
gsearank, 21
gsInfo, 22

heatplot, 22
heatplot,enrichResult-method *(*heatplot*)*, 22
heatplot,gseaResult-method *(*heatplot*)*, 22
heatplot.enrichResult *(*heatplot*)*, 22

hplot, 23

pairwise_termsim, *13*, 24
pairwise_termsim,compareClusterResult-method
(pairwise_termsim), 24
pairwise_termsim,enrichResult-method
(pairwise_termsim), 24
pairwise_termsim,gseaResult-method
(pairwise_termsim), 24
pairwise_termsim.compareClusterResult
(pairwise_termsim), 24
pairwise_termsim.enrichResult
(pairwise_termsim), 24
plot_list, *27*
plot_list (reexports), 27
plotting.clusterProfile, 25
pmcplot, 26

reexports, 27
ridgeplot, 27
ridgeplot,gseaResult-method
(ridgeplot), 27
ridgeplot.gseaResult (ridgeplot), 27

set_enrichplot_color, 29
ssplot, 29
ssplot,compareClusterResult-method
(ssplot), 29
ssplot,enrichResult-method (ssplot), 29
ssplot,gseaResult-method (ssplot), 29
ssplot.compareClusterResult (ssplot), 29
ssplot.enrichResult (ssplot), 29

treeplot, 32
treeplot,compareClusterResult-method
(treeplot), 32
treeplot,enrichResult-method
(treeplot), 32
treeplot,gseaResult-method (treeplot),
32
treeplot.compareClusterResult
(treeplot), 32
treeplot.enrichResult (treeplot), 32

upsetplot, 36
upsetplot,enrichResult,ANY-method
(upsetplot), 36
upsetplot,enrichResult-method
(upsetplot), 36
upsetplot,gseaResult (upsetplot), 36
upsetplot,gseaResult-method
(upsetplot), 36

volplot, 37
volplot,enrichResult-method (volplot),
37
volplot.enrichResult (volplot), 37