

# Package ‘BindingSiteFinder’

January 22, 2026

**Type** Package

**Title** Binding site defintion based on iCLIP data

**Version** 2.8.0

**Description** Precise knowledge on the binding sites of an RNA-binding protein (RBP) is key to understand (post-) transcriptional regulatory processes. Here we present a workflow that describes how exact binding sites can be defined from iCLIP data. The package provides functions for binding site definition and result visualization. For details please see the vignette.

**License** Artistic-2.0

**Encoding** UTF-8

**VignetteBuilder** knitr

**Imports** tidyr, tibble, plyr, matrixStats, stats, ggplot2, methods, tracklayer, S4Vectors, ggforce, GenomeInfoDb, ComplexHeatmap, RColorBrewer, lifecycle, rlang,forcats, dplyr, GenomicFeatures, IRanges, kableExtra, ggdist

**Depends** GenomicRanges, R (>= 4.2)

**Suggests** testthat, BiocStyle, knitr, rmarkdown, GenomicAlignments, scales, Gviz, xlsx, GGally, patchwork, viridis, ggplotify, SummarizedExperiment, DESeq2, ggpointdensity, ggrastr, ashR, txdbmaker, ggrepel, stringr

**RoxygenNote** 7.3.2

**Collate** 'AllClasses.R' 'AllGenerics.R' 'Functions.R' 'methods.R'  
'bindingsites.R' 'helper.R' 'PlotFunction.R'  
'CoverageFunctions.R' 'workflow.R' 'helperSpecific.R'  
'exports.R' 'coveragePlots.R' 'bsfind.R' 'helperPlots.R'  
'differentialFunctions.R' 'differentialPlots.R'

**biocViews** Sequencing, GeneExpression, GeneRegulation,  
FunctionalGenomics, Coverage, DataImport

**BugReports** <https://github.com/ZarnackGroup/BindingSiteFinder/issues>

**git\_url** <https://git.bioconductor.org/packages/BindingSiteFinder>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 74a4d9c

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-22

**Author** Mirko Brüggemann [aut, cre] (ORCID: <https://orcid.org/0000-0002-1778-0248>),

Melina Klostermann [aut] (ORCID: <https://orcid.org/0000-0003-3122-1095>),

Kathi Zarnack [aut] (ORCID: <https://orcid.org/0000-0003-3527-3378>)

**Maintainer** Mirko Brüggemann <[mirko.brueggemann@mail.de](mailto:mirko.brueggemann@mail.de)>

## Contents

add-BSFDataSet	3
annotateWithScore	4
assignToGenes	6
assignToTranscriptRegions	7
bindingSiteCoveragePlot	9
bindingSiteDefinednessPlot	10
BSFDataSet	11
BSFind	12
calculateBsBackground	16
calculateBsFoldChange	19
calculateSignalToFlankScore	21
clipCoverage	22
collapseReplicates	24
combineBSF	25
coverageOverRanges	27
duplicatedSitesPlot	28
estimateBsWidth	29
estimateBsWidthPlot	31
exportTargetGenes	32
exportToBED	33
filterBsBackground	34
geneOverlapsPlot	36
geneRegulationPlot	37
getMeta	39
getName	39
getRanges	40
getSignal	41
getSummary	42
globalScorePlot	42
imputeBsDifferencesForTestdata	43
makeBindingSites	44
makeBsSummaryPlot	46
mergeCrosslinkDiagnosticsPlot	47
mergeSummaryPlot	47
plotBsBackgroundFilter	48
plotBsMA	50
plotBsVolcano	51
processingStepsFlowChart	52
processingStepsTable	52
pureClipGeneWiseFilter	53

pureClipGlobalFilter	55
pureClipGlobalFilterPlot	56
quickFigure	56
rangeCoveragePlot	58
reproducibilityCutoffPlot	59
reproducibilityFilter	60
reproducibilityFilterPlot	61
reproducibilitySamplesPlot	62
reproducibilityScatterPlot	63
setMeta	64
setName	65
setRanges	65
setSignal	66
setSummary	67
show	68
subset-BSFDataSet	69
summary	69
supportRatio	70
supportRatioPlot	71
targetGeneSpectrumPlot	72
transcriptRegionOverlapsPlot	72
transcriptRegionSpectrumPlot	73

**Index****75**


---

add-BSFDataSet	<i>Add two <a href="#">BSFDataSet</a> objects</i>
----------------	---

---

**Description**

Use '+' to add two objects of type [BSFDataSet](#) to each other.

**Usage**

```
## S4 method for signature 'BSFDataSet,BSFDataSet'
e1 + e2
```

**Arguments**

e1	<a href="#">BSFDataSet</a> ; the first dataset
e2	<a href="#">BSFDataSet</a> ; the second dataset

**Details**

Meta data is extended by binding both input tables together. Ranges are added by re-centering partially overlapping ranges according to their combined coverage maximum.

Input ranges must be of the same size. Differently size objects cannot be added. For this and other usecases please see [combineBSF](#).

**Value**

A [BSFDataSet](#) object with ranges, signal and meta data from both inputs.

## Examples

```

# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)

# split ranges in two groups
allRanges = getRanges(bds)
set.seed(1234)
idx = sample(1:length(allRanges), size = length(allRanges)/2, replace = FALSE)
r1 = allRanges[idx]
r2 = allRanges[-idx]

# split meta data
allMeta = getMeta(bds)
m1 = allMeta[1:2,]
m2 = allMeta[3:4,]

# create new objects
bds1 = setRanges(bds, r1)
bds2 = setRanges(bds, r2)
bds1 = setMeta(bds1, m1)
bds2 = setMeta(bds2, m2)
bds1 = setName(bds1, "test1")
bds2 = setName(bds2, "test2")

# merge two objects with '+' operator
c1 = bds1 + bds2

```

---

annotateWithScore	<i>Annotation function for BSFDataSet object</i>
-------------------	--

---

## Description

This function can be used to annotate a BSFDataSet object with merged binding sites with scores from the initial ranges (eg. PureCLIP scores).

## Usage

```

annotateWithScore(
  object,
  match.ranges = NULL,
  match.score = "score",
  match.option = c("max", "sum", "mean"),
  scoreRanges = lifecycle::deprecated(),
  MatchColScore = lifecycle::deprecated(),
  quiet = FALSE
)

```

## Arguments

object	a BSFDataSet object
match.ranges	a GRanges object, with numeric column for the score to match
match.score	character; meta column name of the crosslink site <a href="#">GenomicRanges</a> object that holds the score to match
match.option	character; option how score should be matched
scoreRanges	deprecated -> use match.ranges instead
MatchColScore	deprecated -> use match.score instead
quiet	logical; whether to print messages

## Details

The function is part of the standard workflow performed by [BSFind](#).

## Value

an object of class BSFDataSet with updated meta columns of the ranges

## See Also

[BSFind](#), [globalScorePlot](#)

## Examples

```
if (.Platform$OS.type != "windows") {
  # load data
  csFile <- system.file("extdata", "PureCLIP_crosslink_sites_examples.bed",
                        package="BindingSiteFinder")
  cs = rtracklayer:::import(con = csFile, format = "BED",
                           extraCols=c("additionalScores" = "character"))
  cs$additionalScores = NULL
  clipFiles <- system.file("extdata", package="BindingSiteFinder")
  # two experimental conditions
  meta = data.frame(
    id = c(1,2,3,4),
    condition = factor(c("WT", "WT", "KD", "KD"),
                       levels = c("KD", "WT")),
    clPlus = list.files(clipFiles, pattern = "plus.bw$", full.names = TRUE),
    clMinus = list.files(clipFiles, pattern = "minus.bw$",
                        full.names = TRUE))
  bds = BSFDataSetFromBigWig(ranges = cs, meta = meta, silent = TRUE)

  # merge binding sites
  bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
                           minCrosslinks = 2, minClSites = 1)

  # annotate with original pureCLIP score
  bdsRe = annotateWithScore(bds, cs)
}
```

---

assignToGenes	<i>Assign binding sites to their hosting genes</i>
---------------	--

---

## Description

Function that assigns each binding site in the [BSFDataSet](#) to its hosting gene given a gene annotation (anno.annoDB, anno.genes).

## Usage

```
assignToGenes(
  object,
  overlaps = c("frequency", "hierarchy", "remove", "keep"),
  overlaps.rule = NULL,
  anno.annoDB = NULL,
  anno.genes = NULL,
  match.geneID = "gene_id",
  match.geneName = "gene_name",
  match.geneType = "gene_type",
  quiet = FALSE
)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored binding sites. This means that ranges should be $> 1$
overlaps	character; how overlapping gene loci should be handled.
overlaps.rule	character vector; a vector of gene type that should be used to handle overlapping cases in a hierarchical manor. The order of the vector is the order of the hierarchy.
anno.annoDB	an object of class <code>OrganismDbi</code> that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class <a href="#">GenomicRanges</a> that represents the gene ranges directly
match.geneID	character; meta column name of the gene ID
match.geneName	character; meta column name of the gene name
match.geneType	character; meta column name of the gene type
quiet	logical; whether to print messages

## Details

Regardless of the annotation source that is being used, the respective meta information about the genes have to be present. They can be set by the `match.geneID`, `match.geneName` and `match.geneType` arguments.

In the case of overlapping gene annotation, a single binding site will be associated with multiple genes. The `overlaps` parameter allows to decide in these cases. Option ‘frequency’ will take the most frequently observed gene type, option ‘hierarchy’ works in conjunction with a user defined rule (`overlaps.rule`). Options ‘remove’ and ‘keep’ will remove or keep all overlapping cases, respectively.

Note that if an overlaps exists, but gene types are identical options ‘frequency’ and ‘hierarchy’ will cause the gene that was seen first to be selected as representative.

The function is part of the standard workflow performed by [BSFind](#).

## Value

an object of class [BSFDataSet](#) with binding sites having hosting gene information added to their meta columns.

## See Also

[BSFind](#), [geneOverlapsPlot](#), [targetGeneSpectrumPlot](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
```

## assignToTranscriptRegions

*Assign binding sites to their hosting transcript regions*

## Description

Function that assigns each binding site in the [BSFDataSet](#) to its hosting transcript region given an annotation database (anno.annoDB), or a GRanges list / [CompressedGRangesList](#) (anno.transcriptRegionList) that holds the ranges for the transcript regions of interest.

## Usage

```
assignToTranscriptRegions(
  object,
  overlaps = c("frequency", "hierarchy", "flag", "remove"),
  overlaps.rule = NULL,
  anno.annoDB = NULL,
  anno.transcriptRegionList = NULL,
  normalize.exclude.upper = 0.02,
  normalize.exclude.lower = 0.02,
  quiet = FALSE
)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored binding sites. This means that ranges should be $> 1$
overlaps	character; how overlapping transcript regions should be handled.
overlaps.rule	character vector; a vector of transcript region names that should be used to handle overlapping cases in a hierarchical manor. The order of the vector is the order of the hierarchy.
anno.annoDB	an object of class <a href="#">OrganismDbi</a> that contains the transcript region annotation (!!! Experimental !!!).
anno.transcriptRegionList	an object of class <a href="#">CompressedGRangesList</a> that holds an ranges for each transcript region
normalize.exclude.upper	numeric; percentage value that indicates the upper boundary for transcript region length to be considered when calculating normalization factors for regions.
normalize.exclude.lower	numeric; percentage value that indicates the lower boundary for transcript region length to be considered when calculating normalization factors for regions.
quiet	logical; whether to print messages

## Details

Since the assignment is based on the overlaps of annotated transcript ranges and binding sites, no matching meta data is needed.

In the case of transcript regions overlaps are very frequent. To resolve these cases the `overlaps` argument can be used. Option ‘frequency’ will take the most frequently observed transcript region, option ‘hierarchy’ works in conjunction with a user defined rule (`overlaps.rule`). Options ‘flag’ and ‘remove’ will label binding sites with an ambiguous tag or remove all overlapping cases, respectively.

The function is part of the standard workflow performed by [BSFind](#).

## Value

an object of class [BSFDataSet](#) with binding sites having hosting transcript region information added to their meta columns.

## See Also

[BSFind](#), [transcriptRegionOverlapsPlot](#), [transcriptRegionSpectrumPlot](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])

bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
```

---

```
bindingSiteCoveragePlot
```

*Plot signal coverage of selected ranges*

---

## Description

Function plots the coverage of the CLIP data in the signal slot and plots it as coverage. The plot is centered around a given binding site, which can be selected by an index.

## Usage

```
bindingSiteCoveragePlot(  
  object,  
  plotIdx,  
  flankPos,  
  shiftPos = NULL,  
  mergeReplicates = FALSE,  
  autoscale = FALSE,  
  highlight = TRUE,  
  showCentralRange = TRUE,  
  customRange = NULL,  
  customRange.name = "custom",  
  customAnnotation = NULL,  
  customAnnotation.name = "anno",  
  title = NULL,  
  colorPalette = NULL  
)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object
plotIdx	integer, index of the range to plot
flankPos	numeric, number of nucleotides by which the plotting frame is symmetrically extended
shiftPos	numeric, nucleotide positions by which the current plotting range should be shifted
mergeReplicates	logical, if replicates should be merge per condition (TRUE) or if every replicates should be shown separately (FALSE)
autoscale	logical, if y-axis should be scaled to the maximum for all replicates (TRUE), or not (FALSE)
highlight	logical, if the central range should be highlighted (TRUE), or not (FALSE)
showCentralRange	logical, if the central range should be shown (TRUE), or not (FALSE)
customRange	GenomicRanges, a custom range object to be shown underneath the coverage tracks
customRange.name	character, the name of the customRange track

```

customAnnotation
  GenomicRanges or TxDb, a custom annotation for eg. gene, exons, etc. to be
  shown underneath the coverage tracks
customAnnotation.name
  character, the name of the customAnnotation track
title
  character, set plotting title
colorPalette
  vector, hex colors used for the conditions

```

### Value

an object of class GVIZ

### See Also

[BSFDataSet](#), [BSFind](#)

### Examples

```

# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bindingSiteCoveragePlot(bds, plotIdx = 3, flankPos = 10)

```

**bindingSiteDefinednessPlot**  
*Binding site definedness plot*

### Description

Binding site definedness is given by the percent of crosslinks that fall directly inside the binding site compare to those around the binding site. This plotting function shows the distribution of those percentage values grouped by what is indicated in the by argument.

### Usage

```

bindingSiteDefinednessPlot(
  object,
  by = c("all", "transcript_region", "gene_type"),
  showN.genes = 5,
  show.others = FALSE
)

```

### Arguments

object	a <a href="#">BSFDataSet</a> object
by	character; the option by which the plot should be grouped by. Options are: "all", "transcript_region", "gene_type"
showN.genes	numeric; if by is 'gene_type', then this argument set the maximum number of groups to be shown in the plot
show.others	logical; whether to show 'others' category.

## Details

If by = 'all', then all binding site are grouped into one distribution. For options 'transcript\_region' and 'gene\_type' binding sites are split into groups according to the respective assignment. This requires that the respective assignment function was executed on the dataset prior to calling this plot function.

## Value

a plot of type [ggplot](#)

## See Also

[BSFind](#), [calculateSignalToFlankScore](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,
  est.subsetChromosome = "chr22")
bds = calculateSignalToFlankScore(bds)
bindingSiteDefinednessPlot(bds)
```

## BSFDataSet

## BSFDataSet object and constructors

## Description

BSFDataSet contains the class GenomicRanges, which is used to store input ranges. Alongside with the iCLIP signal in list structure and additional meta data as `data.frame`.

## Usage

```
BSFDataSet(ranges, meta, signal, dropSeqlevels = TRUE, silent = FALSE)

BSFDataSet(ranges, meta, signal, dropSeqlevels = TRUE, silent = FALSE)

BSFDataSetFromBigWig(ranges, meta, silent = FALSE, dropSeqlevels = TRUE)
```

## Arguments

ranges	a GenomicRanges with the desired ranges to process. The strand slot must be either + or -.
meta	a <code>data.frame</code> with at least two columns. The first column should be a unique numeric id. The second column holds sample type information, such as the condition.

signal	a list with the two entries 'signalPlus' and 'signalMinus', following a special representation of SimpleRleList for counts per replicates (see details for more information).
dropSeqlevels	enforce seqnames to be the same in ranges and signal, by dropping unused seqlevels which is required for most downstream functions such as coverageOverRanges
silent	suppress messages but not warnings (TRUE/ FALSE)

### Details

The ranges are enforced to have to have a "+" or "-" strand annotation, "\*" is not allowed. They are expected to be of the same width and a warning is thrown otherwise.

The meta information is stored as `data.frame` with at least two required columns, 'id' and 'condition'. They are used to build the unique identifier for each replicate split by '\_' (eg. id = 1 and condition = WT will result in 1\_WT).

The meta data needs to have the additional columns 'clPlus' and 'clMinus' to be present if `BSFDataSetFromBigWig` is called. It is used to provide the location to the iCLIP coverage files to the import function. On object initialization these files are loaded and internally represented in the signal slot of the object (see `BSFDataSet`).

The iCLIP signal is stored in a special list structure. At the lowest level crosslink counts per nucleotide are stored as Rle per chromosome summarized as a `SimpleRleList`. Such a list exists for each replicate and must be named by the replicate identifier (eg. 1\_WT). Therefore this list contains always exactly the same number of entries as the number of replicates in the dataset. Since we handle strands initially separated from each other this list must be given twice, once for each strand. The strand specific entries must be named 'signalPlus' and 'signalMinus'.

The option `dropSeqlevels` forces the seqnames of the ranges and the signal to be the same. If for a specific chromosome in the ranges no respective entry in the signal list can be found, then entries with that chromosome are dropped. This behavior is needed to keep the `BSFDataSet` object in sync, which is required for downstream functions such as `coverageOverRanges`

### Value

A `BSFDataSet` object.

### Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
rng = getRanges(bds)
sgn = getSignal(bds)
mta = getMeta(bds)
bdsNew = BSFDataSet(ranges = rng, signal = sgn, meta = mta)
```

## Description

This is the main function that performs the binding site definition analysis through the following steps:

1. Filter PureCLIP sites by their score distribution: [pureClipGlobalFilter](#)
2. Estimate the appropriate binding site width together with the optimal gene-wise filter level: [estimateBsWidth](#)
3. Filter PureCLIP sites by their score distribution per gene: [pureClipGeneWiseFilter](#)
4. Define equally sized binding sites: [makeBindingSites](#)
5. Perform replicate reproducibility filter: [reproducibilityFilter](#)
6. Assign binding sites to their hosting genes: [assignToGenes](#)
7. Assign binding sites to their hosting transcript regions: [assignToTranscriptRegions](#)
8. Re-assign PureCLIP scores to binding sites: [annotateWithScore](#)
9. Calculation of signal-to-flank ratio: [calculateSignalToFlankScore](#)

## Usage

```
BSFind(
  object,
  bsSize = NULL,
  cutoff.geneWiseFilter = NULL,
  cutoff.globalFilter = 0.01,
  est.bsResolution = "medium",
  est.geneResolution = "medium",
  est.maxBsWidth = 13,
  est.minimumStepGain = 0.02,
  est.maxSites = Inf,
  est.subsetChromosome = "chr1",
  est.minLength = 2,
  est.offset = 1,
  est.sensitive = FALSE,
  est.sensitive.size = 5,
  est.sensitive.minLength = 2,
  merge.minLength = 2,
  merge.minLengthCrosslinks = 2,
  merge.minLengthC1Sites = 1,
  merge.CenterIsC1Site = TRUE,
  merge.CenterIsSummit = TRUE,
  repro.cutoff = NULL,
  repro.nReps = NULL,
  repro.minLengthCrosslinks = 1,
  overlaps.geneWiseFilter = "keepSingle",
  overlaps.geneAssignment = "frequency",
  overlaps.rule.geneAssignment = NULL,
  overlaps.TranscriptRegions = "frequency",
  overlaps.rule.TranscriptRegions = NULL,
  stf.flank = "bs",
  stf.flank.size = NULL,
  match.score = "score",
  match.geneID = "gene_id",
```

```

  match.geneName = "gene_name",
  match.geneType = "gene_type",
  match.ranges.score = NULL,
  match.option.score = "max",
  anno.annoDB = NULL,
  anno.genes = NULL,
  anno.transcriptRegionList = NULL,
  quiet = FALSE,
  veryQuiet = FALSE,
  ...
)

```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored ranges
bsSize	an odd integer value specifying the size of the output binding sites
cutoff.geneWiseFilter	numeric; defines the cutoff for which sites to remove in in function <a href="#">pureClipGeneWiseFilter</a> . The smallest step is 1% (0.01). A cutoff of 5% will remove the lowest 5% sites, given their score, on each gene, thus keeping the strongest 95%.
cutoff.globalFilter	numeric; defines the cutoff for which sites to keep, the smallest step is 1% (0.01) in function <a href="#">pureClipGlobalFilter</a>
est.bsResolution	character; level of resolution of the binding site width in function <a href="#">estimateBsWidth</a>
est.geneResolution	character; level of resolution of the gene-wise filtering in function <a href="#">estimateBsWidth</a>
est.maxBsWidth	numeric; the largest binding site width which should be considered in the testing
est.minimumStepGain	numeric; the minimum additional gain in the score in percent the next binding site width has to have, to be selected as best option
est.maxSites	numeric; maximum number of PureCLIP sites that are used
est.subsetChromosome	character; define on which chromosome the estimation should be done in function <a href="#">estimateBsWidth</a>
est.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
est.offset	constant added to the flanking count in the signal-to-flank ratio calculation to avoid division by Zero
est.sensitive	logical; whether to enable sensitive pre-filtering before binding site merging or not
est.sensitive.size	numeric; the size (in nucleotides) of the merged sensitive region
est.sensitive.minLength	numeric; the minimum size (in nucleotides) of the merged sensitive region
merge.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
merge.minCrosslinks	the minimal number of positions to overlap with at least one crosslink event in the final binding sites

```

merge.minCISites
  the minimal number of crosslink sites that have to overlap a final binding site
merge.CenterIsCISite
  logical, whether the center of a final binding site must be covered by an initial
  crosslink site
merge.CenterIsSummit
  logical, whether the center of a final binding site must exhibit the highest number
  of crosslink events
repro.cutoff  numeric; percentage cutoff to be used for the reproducibility quantile filtering
repro.nReps   numeric; number of replicates that must meet the cutoff defined in repro.cutoff
  for a binding site to be called reproducible. Defaults to N-1.
repro.minCrosslinks
  numeric; minimal number of crosslinks a binding site needs to have to be called
  reproducible. Acts as a lower boundary for repro.cutoff. Defaults to 1.
overlaps.geneWiseFilter
  character; how overlaps should be handled in pureClipGeneWiseFilter
overlaps.geneAssignment
  character; how overlaps should be handled in assignToGenes
overlaps.rule.geneAssignment
  character vector; a vector of gene types that should be used to handle overlaps if
  option 'hierarchy' is selected for assignToGenes. The order of the vector is the
  order of the hierarchy.
overlaps.TranscriptRegions
  character; how overlaps should be handled in assignToTranscriptRegions
overlaps.rule.TranscriptRegions
  character vector; a vector of gene types that should be used to handle overlaps if
  option 'hierarchy' is selected for assignToTranscriptRegions. The order of
  the vector is the order of the hierarchy.
stf.flank    character; how the flanking region shoule be set. Options are 'bs', 'manual'
stf.flank.size numeric; if flank='manual' provide the desired flanking size
match.score   character; meta column name of the crosslink site
match.geneID   character; meta column name of the genes
match.geneName  character; meta column name of the gene name
match.geneType  character; meta column name of the gene type
match.ranges.score
  a GRanges object, with numeric column for the score to match in function
  annotateWithScore
match.option.score
  character; meta column name of the crosslink site in function annotateWithScore
anno.annoDB   an object of class OrganismDbi that contains the gene annotation !!! Experimental !!!
anno.genes    an object of class GenomicRanges that represents the gene ranges directly
anno.transcriptRegionList
  an object of class CompressedGRangesList that holds an ranges for each transcript region
quiet        logical; whether to print messages
veryQuiet    logical; whether to suppress all messages
...          additional arguments passed to estimateBsWidth, makeBindingSites and reproducibilityFilter

```

## Details

If only the annotation is provided (anno.genes and anno.transcriptRegionList), then binding sites size (bsSize) and gene-wise cutoff (cutoff.geneWiseFilter) are estimated using `estimateBsWidth`. To avoid this behavior one has to provide input values for the arguments bsSize and cutoff.geneWiseFilter.

If no binding site size is provided through bsSize, then `estimateBsWidth` is called to estimate the optimal size for the given data-set. The result of this estimation can be looked at with `estimateBsWidthPlot` and arguments can be adjusted if needed.

Use the `processingStepsFlowChart` function to get an overview of all steps carried out by the function.

For complete details on each step, see the manual pages of the respective functions. The `BSFind` function returns a `BSFDataSet` with ranges merged into binding sites. A full flowchart for the entire process can be visualized with `processingStepsFlowChart`. For each of the individual steps dedicated diagnostic plots exists. Further information can be found in our Bioconductor vignette: <https://www.bioconductor.org/packages/release/bioc/html/BindingSiteFinder.html>

## Value

an object of class `BSFDataSet` with ranges merged into binding sites given the inputs.

## See Also

`BSFDataSet`, `estimateBsWidth`, `pureClipGlobalFilter`, `pureClipGeneWiseFilter`, `assignToGenes`, `assignToTranscriptRegions`, `annotateWithScore`, `reproducibilityFilter`, `calculateSignalToFlankScore`, `processingStepsFlowChart`

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# load transcript regions
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
BSFind(object = bds, bsSize = 9, anno.genes = gns,
       anno.transcriptRegionList = regions, est.subsetChromosome = "chr22")
```

---

`calculateBsBackground` *Compute background coverage for binding sites per gene*

---

## Description

This function computes the background coverage used for the differential binding analysis to correct for transcript level changes. Essentially, the crosslink signal on each gene is split into crosslinks that can be attributed to the binding sites and all other signal that can be attributed to the background.

**Usage**

```
calculateBsBackground(
  object,
  anno.annoDB = NULL,
  anno.genes = NULL,
  blacklist = NULL,
  use.offset = TRUE,
  ranges.offset = NULL,
  match.geneID.gene = "gene_id",
  match.geneID.bs = "geneID",
  match.geneID.blacklist = "geneID",
  generate.geneID.bs = FALSE,
  generate.geneID.blacklist = FALSE,
  uniqueID.gene = "gene_id",
  uniqueID.bs = "bsID",
  uniqueID.blacklist = "bsID",
  force.unequalSites = FALSE,
  quiet = FALSE,
  veryQuiet = TRUE,
  ...
)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object with two conditions
anno.annoDB	an object of class <code>OrganismDbi</code> that contains the gene annotation.
anno.genes	an object of class <a href="#">GenomicRanges</a> that represents the gene ranges directly
blacklist	GRanges; genomic ranges where the signal should be excluded from the background
use.offset	logical; if an offset region around the binding sites should be used on which the signal is excluded from the background
ranges.offset	numeric; number of nucleotides the offset window around each binding site should be wide (defaults to 1/2 binding site width - NULL)
match.geneID.gene	character; the name of the column with the gene ID in the genes meta columns used for matching binding sites to genes
match.geneID.bs	character; the name of the column with the gene ID in the binding sites meta columns used for matching binding sites to genes
match.geneID.blacklist	character; the name of the column with the gene ID in the blacklist meta columns used for matching the blacklist regions with the genes
generate.geneID.bs	logical; if the binding site to gene matching should be performed if no matching gene ID is provided
generate.geneID.blacklist	logical; if the blacklist to gene matching should be performed if no matching gene ID is provided
uniqueID.gene	character; column name of a unique ID for all genes

```

uniqueID.bs      character; column name of a unique ID for all binding sites
uniqueID.blacklist
                  character; column name of a unique ID for all blacklist regions
force.unequalSites
                  logical; if binding sites of not identical width should be allowed or not
quiet
      logical; whether to print messages or not
veryQuiet
      logical; whether to print messages or not
...
      additional arguments; passed to assignToGenes

```

## Details

To avoid that crosslinks from binding sites contaminate the background counts a protective region around each binding sites can be spanned with `use.offset` the default width of the offset region is half of the binding site width, but can also be changed with the `ranges.offset` parameter.

Additional region that one wants to exclude from contributing to the background signal can be incorporated as GRanges objects through the `blacklist` option.

It is expected that binding sites are assigned to hosting genes prior to running this function (see [BSFind](#)). This means a unique gene ID is present in the meta columns of each binding site ranges. If this is not the case one can invoke the binding site to gene assignment with `generate.geneID.bs`. The same is true for the blacklist regions with option `generate.geneID.blacklist`.

It is expected that all binding sites are of the same size (See [BSFind](#) on how to achieve this). If this is however not the case and one wants to keep binding sites of different width then option `force.unequalSites` can be used.

This function is intended to be used for the generation of the count matrix used for the differential binding analysis. It is usually preceded by `combineBSF` and followed by `filterBsBackground`.

## Value

an object of class `BSFDataSet` with counts for binding sites, background and total gene added to the meta column of the ranges

## See Also

`combineBSF`, `filterBsBackground`

## Examples

```

# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$",
full.names = TRUE))
load(list.files(files, pattern = ".rds$",
full.names = TRUE)[1])

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)

# change meta data
m = getMeta(bds)
m$condition = factor(c("WT", "WT", "KO", "KO"), levels = c("WT", "KO"))
bds = setMeta(bds, m)

# change signal

```

```

s = getSignal(bds)
names(s$signalPlus) = paste0(m$id, "_", m$condition)
names(s$signalMinus) = paste0(m$id, "_", m$condition)
bds = setSignal(bds, s)

# make example blacklist region
myBlacklist = getRanges(bds)
set.seed(1234)
myBlacklist = sample(myBlacklist, size = 500) + 4

# make background
bds.b1 = calculateBsBackground(bds, anno.genes = gns)

# make background - no offset
bds.b2 = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# make background - use blacklist
bds.b3 = calculateBsBackground(bds, anno.genes = gns, blacklist = myBlacklist)

```

---

calculateBsFoldChange *Compute fold-changes per binding site*

---

## Description

Given count data for binding sites and background regions this function will compute fold-changes between two condition for each binding site. Computation is based on [DESeq](#) using the Likelihood ratio test to disentangle transcription level changes from binding site level changes.

## Usage

```

calculateBsFoldChange(
  object,
  fitType = "local",
  sfType = "ratio",
  minReplicatesForReplace = 10,
  independentFiltering = TRUE,
  alpha = 0.05,
  pAdjustMethod = "BH",
  minmu = 0.5,
  filterFun = NULL,
  use.lfc.shrinkage = FALSE,
  type = c("ashr", "apeglm", "normal"),
  svalue = FALSE,
  apeAdapt = TRUE,
  apeMethod = "nbinomCR",
  match.geneID = "geneID",
  quiet = TRUE,
  veryQuiet = FALSE,
  replaceNegative = FALSE,
  removeNA = FALSE
)

```

### Arguments

object	a <a href="#">BSFDataSet</a> object
fitType	either "parametric", "local", "mean", or "glmGamPoi" for the type of fitting of dispersions to the mean intensity. See <a href="#">DESeq</a> for more details.
sfType	either "ratio", "poscounts", or "iterate" for the type of size factor estimation. See <a href="#">DESeq</a> for more details.
minReplicatesForReplace	the minimum number of replicates required in order to use replaceOutliers on a sample. See <a href="#">DESeq</a> for more details.
independentFiltering	logical, whether independent filtering should be applied automatically. See <a href="#">results</a> for more details.
alpha	the significance cutoff used for optimizing the independent filtering. See <a href="#">results</a> for more details.
pAdjustMethod	the method to use for adjusting p-values. See <a href="#">results</a> for more details.
minmu	lower bound on the estimated count. See <a href="#">results</a> for more details.
filterFun	an optional custom function for performing independent filtering and p-value adjustment. See <a href="#">results</a> for more details.
use.lfc.shrinkage	logical; whether to compute shrunken log2 fold changes for the DESeq results. See <a href="#">lfcShrink</a> for more details.
type	if 'ashr', 'apeglm' or 'normal' should be used for fold change shrinkage. See <a href="#">lfcShrink</a> for more details.
svalue	logical, should p-values and adjusted p-values be replaced with s-values when using apeglm or ash. See <a href="#">lfcShrink</a> for more details.
apeAdapt	logical, should apeglm use the MLE estimates of LFC to adapt the prior. See <a href="#">lfcShrink</a> for more details.
apeMethod	what method to run apeglm, which can differ in terms of speed. See <a href="#">lfcShrink</a> for more details.
match.geneID	character; the name of the column with the gene ID in the binding sites meta columns used for matching binding sites to genes
quiet	logical; whether to print messages or not
veryQuiet	logical; whether to print messages or not
replaceNegative	logical; force negative counts to be replaced by 0. Be careful when using this, having negative counts can point towards problems with the gene annotation in use.
removeNA	logical; force binding sites with any NA value to be removed. Be careful when using this, having negative counts can point towards problems with the gene annotation in use.

### Details

Fold-changes per binding sites are corrected for transcript level changes. Essentially, background counts are used to model transcript level changes, which are then used to compute fold-changes per binding site, which are corrected for the observed transcript level changes. This is done by using a

Likelihood ratio test comparing the full model (~condition + type + condition:type) to the reduced model (~condition + type).

Fold-changes for the transcript level changes are modeled explicitly in a second round of the `DESeq` workflow, using the default Wald test to compare changes between the conditions (~condition). Counts attributed to binding sites are removed from the gene level counts.

Results from both calculation rounds can be filtered and further manipulated with parameters given in the `DESeq2` framework (see `results`, `lfcShrink`).

This function is intended to be used right after a call of `filterBsBackground`.

## Value

a `BSFDataSet` object, with results from the `DESeq` analysis added to the meta columns of the binding site ranges.

## See Also

`calculateBsBackground`, `filterBsBackground`, `plotBsBackgroundFilter`, `DESeq`

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$",
  full.names = TRUE))
load(list.files(files, pattern = ".rds$",
  full.names = TRUE)[1])

# make example dataset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns)

# calculate fold changes - no shrinkage
bds = calculateBsFoldChange(bds)

# calculate fold changes - with shrinkage
bds = calculateBsFoldChange(bds, use.lfc.shrinkage = TRUE)
```

## calculateSignalToFlankScore

*Calculate signal-to-flank score*

## Description

This function calculates the signal-to-flank ratio for all present binding sites.

## Usage

```
calculateSignalToFlankScore(
  object,
  flank = c("bs", "manual"),
  flank.size = NULL,
  quiet = FALSE
)
```

**Arguments**

object	a BSFDataSet object
flank	character; how the flanking region shoule be set. Options are 'bs', 'manual'
flank.size	numeric; if flank='manual' provide the desired flanking size
quiet	logical; whether to print messages

**Details**

Each input range is treated as a binding site. For a particular binding site all overlapping crosslinks are summed up and divided by the normalized sum of the crosslinks in the two adjecent regions of the same size. This is done for all bining sites and the ratio is reported as a score.

The function is part of the standard workflow performed by [BSFind](#).

**Value**

an object of class [BSFDataSet](#) with signal-to-flank ratios added to the meta column of the ranges.

**See Also**

[BSFind](#), [bindingSiteDefinednessPlot](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(bds, bsSize = 5)
bds = calculateSignalToFlankScore(bds)
```

[clipCoverage](#)

*Coverage function for BSFDataSet objects*

**Description**

Function that computes a crosslink coverage with all samples over all ranges given in the [BSFDataSet](#). The coverage can be summarized over all combinations of the three dimension (samples, ranges, positions).

**Usage**

```
clipCoverage(
  object,
  ranges.merge = FALSE,
  ranges.merge.method = c("sum", "mean"),
  positions.merge = FALSE,
  positions.merge.method = c("sum", "mean"),
  samples.merge = TRUE,
  samples.group = c("all", "condition"),
  samples.merge.method = c("sum", "mean"),
```

```

  out.format = c("granges", "data.frame"),
  out.format.overwrite = FALSE,
  match.rangeID = "bsID",
  quiet = FALSE
)

```

## Arguments

object	a BSFDataSet object
ranges.merge	logical; whether to merge ranges
ranges.merge.method	character; how to combine ranges ('sum' or 'mean')
positions.merge	logical; whether to merge positions
positions.merge.method	character; how to combine positions ('sum' or 'mean')
samples.merge	logical: whether to merge samples
samples.group	character; how samples should be grouped when combining ('all', 'condition')
samples.merge.method	character; how to combine positions ('sum' or 'mean')
out.format	character; how the coverage should be returned ('data.frame' or 'granges'). Note that option 'granges' only exists if the output coverage is of the same rows as the input ranges.
out.format.overwrite	logical; if out.format='granges', then decide whether the meta columns should be extended by the coverage information or be overwritten
match.rangeID	character; unique internal identifier. Name of the meta column of the input ranges that should be used as identifier to match the coverage back to the input ranges. Is 'bsID' as default, since that ID exists for all binding sites after makeBindingSites was called.
quiet	logical; whether to print messages

## Details

When summarizing the crosslink coverage over samples (samples.merge=TRUE) one can decide whether to summarize all samples or whether to keep conditions separate (samples.group). This either reduces the samples dimension to a single matrix, or a list. For a binding site set with 100 binding sites of width=7 and 4 replicates with 2 conditions, the following options are possible. With merging enabled and samples.group='all' the coverage of all samples is combined. With samples.group='condition' only samples of the same condition are grouped.

When summarizing the crosslink coverage over ranges, all ranges are combined which reduces the ranges dimension to a single vector. This turns eg. a binding site set of 100 binding sites with width=7 into a vector of length 100 with exactly one column. Depending on how the samples were summarized, the result can be a single such vector, or a list.

When summarizing the crosslink coverage over positions, all positions are combined which reduces the positions dimension to a single vector. This turns eg. a binding site set of 100 binding sites with width=7 into a vector of length 1 with 7 columns. Depending on how the samples were summarized, the result can be a single such vector, or a list.

For all summarizing operations options sum and mean exists. This allows for normalization by the eg. the number of binding sites, size of the range, number of sample, etc..

If the resulting object does have a dimension that fits to the number of input ranges the result can be directly attached to them. Basically extending the GRanges object (out.format).

### Value

an object of class specified in out.format

### See Also

[BSFDataSet](#), [BSFind](#)

### Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bds = makeBindingSites(bds, bsSize = 7)
# sum of each replicate over each binding site position
c1 = clipCoverage(bds, out.format = "data.frame", positions.merge = TRUE,
  ranges.merge = FALSE, samples.merge = FALSE)
# total signal per binding site from all samples
c2 = clipCoverage(bds, out.format = "granges", positions.merge = FALSE,
  ranges.merge = TRUE, samples.merge = TRUE, samples.group = "all")
# total signal per binding site from all samples - split by condition
c3 = clipCoverage(bds, out.format = "granges", positions.merge = FALSE,
  ranges.merge = TRUE, samples.merge = TRUE, samples.group = "condition")
```

**collapseReplicates**      *Collapse signal from replicates*

### Description

Collapses all replicates merges all samples from a [BSFDataSet](#) object into a single signal stream, only split by minus and plus strand.

### Usage

```
collapseReplicates(object, collapseAll = FALSE)
```

### Arguments

object	a <a href="#">BSFDataSet</a> object
collapseAll	TRUE/FALSE, if all samples should be collapsed (TRUE), or if samples should be kept separate by condition (FALSE)

### Value

object of type [BSFDataSet](#) with updated signal

### See Also

[BSFDataSet](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = collapseReplicates(bds)
```

---

combineBSF

*Combine multiple [BSFDataSet](#) objects*

---

## Description

This function combines all [BSFDataSet](#) objects from the input list into a single [BSFDataSet](#) object.

## Usage

```
combineBSF(
  list,
  overlaps.fix = TRUE,
  combine.bsSize = NULL,
  combine.name = NULL,
  force.reload = FALSE,
  quiet = TRUE,
  veryQuiet = FALSE
)
```

## Arguments

list	list; a list of objects from class <a href="#">BSFDataSet</a> that should be combined
overlaps.fix	logical; if partially overlapping binding sites should be re-centered
combine.bsSize	numeric; the binding site size that the merged sites should have. Default=NULL, then bsSize is taken from the input objects in list.
combine.name	character; meta table name of the combined object. Default=NULL; then name is set to 'combined'
force.reload	logical; whether the signal should be derived from the merge of the input objects given in list or if the signal should be re-loaded from the path given in the meta data.
quiet	logical; whether to print messages or not
veryQuiet	logical; whether to print status messages or not

## Details

Meta-data tables are added to each other by performing a row-wise bind, basically adding all meta data tables underneath each other.

The default way of signal combination is merging all signal lists on the level of the individual samples. One can also force a re-load of the signal list component by using `force.reload=TRUE`. The signal can be combined by

The ranges are combined by adding both granges objects together. With option `overlaps.fix` one can decide if partially overlapping ranges should be combined into a single range or not. If this option is FALSE one is likely to have overlapping binding sites after the merge. If this option is TRUE, then the combined coverage is used to guide the new center point for these cases.

The `combine.bsSize` option allows one to set a unique `bsSize` for all objects that should be combined. Although it is recommended to combine only objects with the same `bsSize` this option can be used to ensure that the merged result has the same `bsSize` for all ranges.

This function is usually used to combine two datasets in the context of a differential testing analysis.

### Value

an object of class [BSFDataSet](#) with ranges, signal and meta data resulting from the merge of the input objects.

### See Also

[processingStepsFlowChart](#), [calculateBsBackground](#)

### Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# make binding sites
bds = makeBindingSites(bds, bsSize = 7)

# split ranges in two groups
allRanges = getRanges(bds)
set.seed(1234)
idx = sample(1:length(allRanges), size = length(allRanges)/2, replace = FALSE)
r1 = allRanges[idx]
r2 = allRanges[-idx]

# split meta data
allMeta = getMeta(bds)
m1 = allMeta[1:2,]
m2 = allMeta[3:4,]

# create new objects
bds1 = setRanges(bds, r1)
bds2 = setRanges(bds, r2)
bds1 = setMeta(bds1, m1)
bds2 = setMeta(bds2, m2)
bds1 = setName(bds1, "test1")
bds2 = setName(bds2, "test2")

# merge two objects with '+' operator
c1 = bds1 + bds2

# merge two objects from list
list = list(bds1, bds2)
c1 = combineBSF(list = list, overlaps.fix = TRUE,
                combine.bsSize = NULL, combine.name = NULL, quiet = TRUE)
```

---

coverageOverRanges      *Coverage function for BSFDataSet objects*

---

## Description

The crosslink coverage is computed for all ranges in the the given BSFDataSet object (see [BSFDataSet](#) for details). Depending on the `returnOptions` the resulting coverage information is summarized, suitable for diverse computation and plotting tasks. The coverage can only be compute for objects with identical ranges.

## Usage

```
coverageOverRanges(
  object,
  returnOptions = c("merge_ranges_keep_positions", "merge_replicates_per_condition",
    "merge_all_replicates", "merge_positions_keep_replicates"),
  method = "sum",
  allowNA = FALSE,
  quiet = TRUE
)
```

## Arguments

<code>object</code>	a BSFDataSet object
<code>returnOptions</code>	one of <code>merge_ranges_keep_positions</code> , <code>merge_replicates_per_condition</code> , <code>merge_all_replicates</code> , <code>merge_positions_keep_replicates</code>
<code>method</code>	<code>sum</code> / <code>mean</code> , select how replicates/ ranges should be summarized
<code>allowNA</code>	<code>TRUE</code> / <code>FALSE</code> , allow NA values in the output if input ranges are of different width
<code>quiet</code>	logical, whether to print messages

## Details

If `returnOptions` is set to `merge_ranges_keep_positions`: Returns a matrix with `ncol` being the nucleotides of the ranges (equal to the width of the input ranges) and `nrow` being the number of replicates in the meta information.

If `returnOptions` is set to `merge_replicates_per_condition`: Returns a list of matrices. Each list corresponds to one condition set in the meta information. The matrix in each entry has `ncols` equal to the ranges width and `nrow` equal to the number of ranges. Counts per ranges and position are summed.

If `returnOptions` is set to `merge_all_replicates`: Returns a matrix with `ncols` equal to the range width and `nrow` equal to the number of ranges. Counts per range and position are summed.

If `returnOptions` is set to `merge_positions_keep_replicates`: Returns a GRanges object where the counts are summed for each replicate and added to the original granges object.

## Value

an object of class specified in `returnOptions`

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

rng = coverageOverRanges(bds, returnOptions = "merge_ranges_keep_positions")
rng = coverageOverRanges(bds, returnOptions = "merge_replicates_per_condition")
rng = coverageOverRanges(bds, returnOptions = "merge_all_replicates")
rng = coverageOverRanges(bds, returnOptions = "merge_positions_keep_replicates")
```

---

duplicatedSitesPlot *Plot the number of overlaps when assigning crosslink sites to genes*

---

## Description

A diagnostic function that plots the number of crosslink sites with their respective overlapping rate. The function [pureClipGeneWiseFilter](#) is expected to be executed prior to calling this plot function.

## Usage

```
duplicatedSitesPlot(object)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object
--------	-------------------------------------

## Value

a plot of type [ggplot](#)

## See Also

[pureClipGeneWiseFilter](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# apply 5% gene-wise filter
bds = pureClipGeneWiseFilter(object = bds, anno.genes = gns, cutoff = 0.5,
  overlaps = "keepSingle")
duplicatedSitesPlot(bds)
```

---

estimateBsWidth	<i>Function to estimate the appropriate binding site width together with the optimal gene-wise filter level.</i>
-----------------	--

---

## Description

This function tests different width of binding sites for different gene-wise filtering steps. For each test the signal-to-score ratio is calculated. The mean over all gene-wise filterings at each binding site width is used to extract the optimal width, which serves as anchor to select the optimal gene-wise filter.

## Usage

```
estimateBsWidth(
  object,
  bsResolution = c("medium", "fine", "coarse"),
  geneResolution = c("medium", "coarse", "fine", "finest"),
  est.maxBsWidth = 13,
  est.minimumStepGain = 0.02,
  est.maxSites = Inf,
  est.subsetChromosome = "chr1",
  est.minLength = 2,
  est.offset = 1,
  sensitive = FALSE,
  sensitive.size = 5,
  sensitive.minLength = 2,
  anno.annoDB = NULL,
  anno.genes = NULL,
  bsResolution.steps = NULL,
  geneResolution.steps = NULL,
  quiet = TRUE,
  veryQuiet = FALSE,
  reportScoresPerBindingSite = FALSE,
  ...
)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored crosslink sites. This means that ranges should have a width = 1.
bsResolution	character; level of resolution at which different binding site width should be tested
geneResolution	character; level of resolution at which gene-wise filtering steps should be tested
est.maxBsWidth	numeric; the largest binding site width which should be considered in the testing
est.minimumStepGain	numeric; the minimum additional gain in the score in percent the next binding site width has to have, to be selected as best option
est.maxSites	numeric; maximum number of PureCLIP sites that are used;

est.subsetChromosome	character; define on which chromosome the estimation should be done in function <a href="#">estimateBsWidth</a>
est.minLength	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
est.offset	constant added to the flanking count in the signal-to-flank ratio calculation to avoid division by Zero
sensitive	logical; whether to enable sensitive pre-filtering before binding site merging or not
sensitive.size	numeric; the size (in nucleotides) of the merged sensitive region
sensitive.minLength	numeric; the minimum size (in nucleoties) of the merged sensitive region
anno.annoDB	an object of class <code>OrganismDbi</code> that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class <code>GenomicRanges</code> that represents the gene ranges directly
bsResolution.steps	numeric vector; option to use a user defined threshold for binding site width directly. Overwrites <code>bsResolution</code>
geneResolution.steps	numeric vector; option to use a user defined threshold vector for gene-wise filtering resolution. Overwrites <code>geneResolution</code>
quiet	logical; whether to print messages
veryQuiet	logical; whether to suppress all messages
reportScoresPerBindingSite	report the ratio score for each binding site separately. Warning! This is for debugging and testing only. Downstream functions can be impaired.
...	additional arguments passed to <a href="#">pureClipGeneWiseFilter</a>

## Details

Parameter estimation is done on a subset of all crosslink sites (`est.subsetChromosome`).

Gene-level filter can be tested with varying levels of accuracy ranging from ‘finest’ to ‘coarse’, representing 1 20

Binding site computation at each step can be done on three different accuracy level (`bsResolution`). Option ‘fine’ is equal to a normal run of the [makeBindingSites](#) function. ‘medium’ will perform a shorter version of the binding site computation, skipping some of the refinement steps. Option ‘coarse’ will approximate binding sites by merged crosslinks regions, aligning the center at the site with the highest score.

For each binding site in each set given the defined resolutions a signal-to- flank score ratio is calculated and the mean of this score per set is returned. Next a mean of means is created which results in a single score for each binding site width that was tested. The width that yielded the highest score is selected as optimal. In addition the `minimumStepGain` option allows control over the minimum additional gain in the score that a tested width has to have to be selected as the best option.

To enhance the sensitivity of the binding site estimation, the sensitivity mode exists. In this mode crosslink sites undergo a pre-filtering and merging step, to exclude potential artificial peaks (experimental-, mapping-biases). If sensitivity mode is activated the `est.minLength` option should be set to 1.

The optimal geneFilter is selected as the first one that passes the merged mean of the selected optimal binding site width.

The function is part of the standard workflow performed by [BSFind](#).

**Value**

an object of class [BSFDataSet](#) with binding sites with the ‘params’ slots ‘bsSize’ and ‘geneFilter’ being filled

**See Also**

[BSFind](#), [estimateBsWidthPlot](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
estimateBsWidth(bds, anno.genes = gns, est.maxBsWidth = 19,
  geneResolution = "coarse", bsResolution = "coarse", est.subsetChromosome = "chr22")
```

---

**estimateBsWidthPlot** *Plot the signal-to-flank score for varying gene-wise filter and binding site width*

---

**Description**

A diagnostic function that plots the the signal-to-flank score as a mean for each binding site width and gene-wise filter as indicated when executing [estimateBsWidth](#). Additionally a mean of means visualizes the overall trend and a red line indicates the suggested optimal binding site width. The function [estimateBsWidth](#) is expected to be executed prior to calling this plot function.

**Usage**

`estimateBsWidthPlot(object)`

**Arguments**

`object` a [BSFDataSet](#) object

**Value**

a plot of type [ggplot](#)

**See Also**

[estimateBsWidth](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = estimateBsWidth(bds, anno.genes = gns, est.maxBsWidth = 19,
  geneResolution = "coarse", bsResolution = "coarse", est.subsetChromosome = "chr22")
estimateBsWidthPlot(bds)
```

exportTargetGenes      *Function to export sorted RBP target genes*

## Description

Genes with binding sites are target genes of the RBP. They can be exported as 'csv' or 'xlsx' file. Genes can be sorted by the sum of the individual binding sites score, or by the number of binding sites per gene.

## Usage

```
exportTargetGenes(
  object,
  path = "./",
  format = c("csv", "xlsx"),
  sort = c("score", "bs"),
  split = c("none", "geneType", "transcriptRegion")
)
```

## Arguments

object	a BSFDataSet object with stored ranges
path	A path to where the output should be stored
format	output file format
sort	sorting rule for genes
split	if and how the output file should be split

## Details

As output option, one can either output all genes in a single file, or split by either gene-type or transcript-region. This options requires that either [BSFind](#) or the individual functions [assignToGenes](#), and [assignToTranscriptRegions](#) were run.

## Value

a file of the type specified in [format](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
## Not run:
# export
# exportTargetGenes(bds)

## End(Not run)
```

---

exportToBED

*Wrapper function to export binding sites as BED files*

---

## Description

Function that serves as a wrapper function for `rtracklayer::export`.

## Usage

```
exportToBED(object, con)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored ranges
con	A path or URL

## Value

a .bed file

## See Also

[BSFind](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
## Not run:
# export
# exportToBED(bds, con = "./myfile.bed")

## End(Not run)
```

---

filterBsBackground	<i>Filter for genes not suitable for differential testing</i>
--------------------	---

---

## Description

This function removes genes where the differential testing protocol can not be applied to, using count coverage information on the binding sites and background regions per gene, through the following steps:

1. Remove genes with overall not enough crosslinks: `minCounts`
2. Remove genes with a disproportion of counts in binding sites vs. the background: `balanceBackground`
3. Remove genes where the expression between conditions is too much off balance: `balanceCondition`

## Usage

```
filterBsBackground(
  object,
  minCounts = TRUE,
  minCounts.cutoff = 100,
  balanceBackground = TRUE,
  balanceBackground.cutoff.bs = 0.3,
  balanceBackground.cutoff.bg = 0.7,
  balanceCondition = TRUE,
  balanceCondition.cutoff = 0.05,
  match.geneID = "geneID",
  flag = FALSE,
  quiet = FALSE,
  veryQuiet = FALSE
)
```

## Arguments

<code>object</code>	a <a href="#">BSFDataSet</a> object with computed count data for binding sites and background regions
<code>minCounts</code>	logical; whether to use the minimum count filter
<code>minCounts.cutoff</code>	numeric; the minimal number of crosslink per gene over all samples for the gene to be retained (default = 100)
<code>balanceBackground</code>	logical; whether to use the counts balancing filter between binding sites and background
<code>balanceBackground.cutoff.bs</code>	numeric; the maximum fraction of the total signal per gene that can be within binding sites (default = 0.2)
<code>balanceBackground.cutoff.bg</code>	numeric; the minimum fraction of the total signal per gene that can be within the background (default = 0.8)
<code>balanceCondition</code>	logical; whether to use the counts balancing filter between conditions

balanceCondition.cutoff	numeric; the maximum fraction of the total signal that can be attributed to only one condition
match.geneID	character; the name of the column with the gene ID in the binding sites meta columns used for matching binding sites to genes
flag	logical; whether to remove or flag binding sites from genes that do not pass any of the filters
quiet	logical; whether to print messages or not
veryQuiet	logical; whether to print messages or not

## Details

To remove genes with overall not enough crosslinks (`minCounts`) all counts are summed up per gene across all samples and compared to the minimal count threshold (`minCounts.cutoff`).

To remove genes with a count disproportion between binding sites and background regions crosslinks are summed up for binding sites and background per gene. These sums are combined in a ratio. Genes where eg. 50% of all counts are within binding sites would be removed (see `balanceBackground.cutoff.bs` and `balanceBackground.cutoff.bg`).

To remove genes with very large expression differences between conditions, crosslinks are summed up per gene for each condition. If now eg. the total number of crosslinks is for 98% in one condition and only 2% of the combined signal is in the second condition, expression levels are too different for a reliable comparison (see `balanceCondition.cutoff`).

This function is intended to be used right after a call of [calculateBsBackground](#).

## Value

an object of class [BSDataSet](#) with biniding sites filtered or flagged by the above filter options

## See Also

[calculateBsBackground](#), [plotBsBackgroundFilter](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
f0 = filterBsBackground(bds)

# do not use the condition balancing filter
f1 = filterBsBackground(bds, balanceCondition = FALSE)

# use only the minimum count filter and flag binding sites instead of
# removing them
```

```
f3 = filterBsBackground(bds, flag = TRUE, balanceCondition = FALSE,
balanceBackground = FALSE)
```

---

geneOverlapsPlot

*UpSet-plot to that shows the gene type overlaps*

---

## Description

A diagnostic function that plots the gene types of binding sites on overlapping loci genes. The function [assignToGenes](#) is expected to be executed prior to calling this plot function.

## Usage

```
geneOverlapsPlot(object, text.size = NULL, show.title = TRUE)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object
text.size	numeric; fontsize of all numbers on axis
show.title	logical; if plot title should be visible

## Value

a plot of type [ggplot](#)

## See Also

[assignToGenes](#) [targetGeneSpectrumPlot](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
geneOverlapsPlot(bds)
```

---

**geneRegulationPlot** *Gene Regulation Plot*

---

**Description**

Display the fold-change of all binding sites from a given gene on a relative per-nucleotide scale. Binding sites are displayed as dots and with increasing log2 fold-change, they deviate stronger from the center line.

**Usage**

```
geneRegulationPlot(  
  object,  
  plot.geneID = NULL,  
  anno.annoDB = NULL,  
  anno.genes = NULL,  
  match.geneID = "gene_id",  
  match.geneName = "gene_name",  
  plot.gene.n.tiles = 100,  
  alpha = 0.05,  
  lfc.cutoff = 2,  
  transcript.regions.outlier.handle = c("first", "second", "both", "remove"),  
  quiet = FALSE  
)
```

**Arguments**

object	object; a <a href="#">BSFDataSet</a> object
plot.geneID	character; the gene id of the gene to display. The id must match with the gene ids given in the annotation object.
anno.annoDB	object; an object of class <code>OrganismDbi</code> that contains the gene annotation (!!! Experimental !!!).
anno.genes	object; an object of class <a href="#">GenomicRanges</a> that represents the gene ranges directly.
match.geneID	character; meta column name of the gene ID
match.geneName	character; meta column name of the gene name
plot.gene.n.tiles	numeric; number of tiles the gene should be split in
alpha	numeric; the alpha value to show significantly regulated binding sites. This should match the alpha value used in <a href="#">calculateBsFoldChange</a> .
lfc.cutoff	numeric; log2 fold-change cutoff to show significantly regulated binding sites. This should match the lfc.cutoff value used in <a href="#">calculateBsFoldChange</a> .
transcript.regions.outlier.handle	character; the option how to handle multiple transcript region annotations being present for the same binding site.
quiet	logical; whether to print messages

## Details

For this function to work, binding sites must be assigned to hosting genes using [assignToGenes](#). It is also recommended to assign binding sites to transcript regions with [assignToTranscriptRegions](#).

It is also necessary to calculate the log2 fold-change of binding sites between two conditions using the differential binding workflow [calculateBsFoldChange](#).

If in addition the transcript regions of the binding sites are given, then shapes are changed accordingly. An edge case can arise from the merging of two [BSFDataSet](#) objects. If binding sites are overlapping and slightly offset close to the end of a particular transcript region annotation, they might be assigned to different regions in both objects. This results in some ambiguity after the merge, where for instance a binding site can be assigned to CDS and 3'UTR. To handle how such edge cases are displayed, the `transcript.regions.outlier.handle` exists. As default, simply the region of the object that was merged first is shown. If one is interested in showing all regions, then the options both displays both annotations at the same time and labels them accordingly.

## Value

an object of class `ggplot2`

## See Also

[BSFind](#), [calculateBsFoldChange](#) [assignToGenes](#) [assignToTranscriptRegions](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make example plot
exampleGeneId = "ENSG00000253352.10"
geneRegulationPlot(bds, plot.geneID = exampleGeneId, anno.genes = gns)
```

---

**getMeta***Accessor method for the meta data of the BSFDataSet object*

---

**Description**

Meta data is stored as a `data.frame` and must contain the columns "condition", "clPlus" and "clMinus".

**Usage**

```
getMeta(object)

## S4 method for signature 'BSFDataSet'
getMeta(object)
```

**Arguments**

`object` a BSFDataSet object

**Value**

returns the meta data `data.frame` with the columns "condition", "clPlus" and "clMinus".

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getMeta(bds)
```

---

**getName***Accessor method for the name of the BSFDataSet object*

---

**Description**

The name slot holds the name of the dataset

**Usage**

```
getName(object)

## S4 method for signature 'BSFDataSet'
getName(object)
```

**Arguments**

object	a BSFDataSet object
--------	---------------------

**Value**

returns the name of the dataset

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getName(bds)
```

getRanges

*Accessor method for the ranges of the BSFDataSet object*

**Description**

The ranges slot holds the genomic ranges information of the sites currently in the object. They are encoded as a GRanges object with each binding site having a single ranges entry.

**Usage**

```
getRanges(object)

## S4 method for signature 'BSFDataSet'
getRanges(object)
```

**Arguments**

object	a BSFDataSet object
--------	---------------------

**Value**

returns the genomic ranges (GRanges) of the associated ranges

**See Also**

[BSFDataSet](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getRanges(bds)
```

---

getSignal

*Accessor method for the signal data of the BSFDataSet object*

---

## Description

Signal data is loaded from the path specified in [getMeta](#) columns "clPlus" and "clMinus" and stored as a list of RLE lists.

## Usage

```
getSignal(object)

## S4 method for signature 'BSFDataSet'
getSignal(object)
```

## Arguments

object a BSFDataSet object

## Value

returns the signal data, as list of RLE list for each strand, named after the meta data columns "clPlus" and "clMinus"

## See Also

[getMeta BSFDataSet](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

getSignal(bds)
```

---

**getSummary***Accessor method for the summary slot of the BSFDataSet object*

---

**Description**

The summary slot is used to track information of the filtering steps applied in the [makeBindingSites](#) function

**Usage**

```
getSummary(object, ...)

## S4 method for signature 'BSFDataSet'
getSummary(object)
```

**Arguments**

object	a BSFDataSet object
...	additional arguments

**Value**

returns the summary information stored in the summary slot after [makeBindingSites](#) was run

**See Also**

[BSFDataSet](#) [makeBindingSites](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1)

getSummary(bds)
```

---

**globalScorePlot***Plot the PureCLIP score distribution after re-assignment*

---

**Description**

A diagnostic function that plots the PureCLIP score distribution on a log2 scale after the re-assignment on binding site level. The function [annotateWithScore](#) is expected to be executed prior to calling this plot function.

**Usage**

```
globalScorePlot(object)
```

**Arguments**

object            a [BSFDataSet](#) object

**Value**

a plot of type [ggplot](#)

**See Also**

[annotateWithScore](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds1 = makeBindingSites(object = bds, bsSize = 9)
bds1 = annotateWithScore(bds1, match.ranges = getRanges(bds))
globalScorePlot(bds1)
```

**imputeBsDifferencesForTestdata**

*Impute artificial differences in the example data set*

**Description**

A function that works only on the test data set provided with the package. It is used for internal testing and the making of examples to showcase the differential binding functions.

**Usage**

```
imputeBsDifferencesForTestdata(object, size = 5, change.per = 0.1)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object; explicitly the test data set from the extdata folder
size	numeric; the number of positions on which signal should be deleted, counting from the start
change.per	numeric; the percentage of ranges that should be effected by the change.

**Details**

Differences between samples are artificially introduced by removing the signal on a random set of binding sites of the input.

**Value**

object a [BSFDataSet](#) object with the signal slot adapted to reflect changes in binding between two artificial conditions

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)

bds = imputeBsDifferencesForTestdata(bds)
```

**makeBindingSites**

*Define equally sized binding sites from peak calling results and iCLIP crosslink events.*

**Description**

This function performs the merging of single nucleotide crosslink sites into binding sites of a user defined width (bsSize). Depending on the desired output width crosslink sites with a distance closer than bsSize -1 are concatenated. Initially all input regions are concatenated and then imperatively merged and extended. Concatenated regions smaller than minWidth are removed prior to the merge and extension routine. This prevents outlier crosslink pileup, eg. mapping artifacts to be integrated into the final binding sites. All remaining regions are further processed and regions larger than the desired output width are interactively split up by setting always the position with the highest number of crosslinks as center. Regions smaller than the desired width are symmetrically extended. Resulting binding sites are then filtered by the defined constraints.

**Usage**

```
makeBindingSites(
  object,
  bsSize = NULL,
  minWidth = 2,
  minCrosslinks = 2,
  minCISites = 1,
  centerIsCISite = TRUE,
  centerIsSummit = TRUE,
  sub.chr = NA,
  quiet = FALSE
)
```

**Arguments**

object	a BSFDataSet object (see <a href="#">BSFDataSet</a> )
bsSize	an odd integer value specifying the size of the output binding sites

<b>minWidth</b>	the minimum size of regions that are subjected to the iterative merging routine, after the initial region concatenation.
<b>minCrosslinks</b>	the minimal number of positions to overlap with at least one crosslink event in the final binding sites
<b>minC1Sites</b>	the minimal number of crosslink sites that have to overlap a final binding site
<b>centerIsC1Site</b>	logical, whether the center of a final binding site must be covered by an initial crosslink site
<b>centerIsSummit</b>	logical, whether the center of a final binding site must exhibit the highest number of crosslink events
<b>sub.chr</b>	chromosome identifier (eg, chr1, chr2) used for subsetting the BSFDataSet object. This option can be used for testing different parameter options
<b>quiet</b>	logical, whether to print info messages

## Details

The `bsSize` argument defines the final output width of the merged binding sites. It has to be an odd number, to ensure that a binding site has a distinct center.

The `minWidth` parameter is used to describe the minimum width a ranges has to be after the initial concatenation step. For example: Consider `bsSize = 9` and `minWidth = 3`. Then all initial crosslink sites that are closer to each other than 8 nucleotides (`bsSize - 1`) will be concatenated. Any of these ranges with less than 3 nucleotides of width will be removed, which reflects about 1/3 of the desired binding site width.

The argument `minCrosslinks` defines how many positions of the binding sites are covered with at least one crosslink event. This threshold has to be defined in conjunction with the binding site width. A default value of 3 with a binding site width of 9 means that 1/3 of all positions in the final binding site must be covered by a crosslink event. Setting this filter to 0 deactivates it.

The `minC1Sites` argument defines how many positions of the binding site must have been covered by the original crosslink site input. If the input was based on the single nucleotide crosslink positions computed by PureCLIP than this filter checks for the number of positions originally identified by PureCLIP in the computed binding sites. The default of `minC1Sites = 1` essentially deactivates this filter. Setting this filter to 0 deactivates it.

The options `centerIsC1Site` and `centerIsSummit` ensure that the center of each binding site is covered by an initial crosslink site and represents the summit of crosslink events in the binding site, respectively.

The option `sub.chr` allows to run the binding site merging on a smaller subset (eg. "chr1") for improved computational speed when testing the effect of various binding site width and filtering options.

## Value

an object of type `BSFDataSet` with modified ranges

## See Also

`BSFDataSet`, `BSFind`, `mergeCrosslinkDiagnosticsPlot`, `makeBsSummaryPlot`

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# standard options, no subsetting
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1)

# standard options, with subsetting
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
```

makeBsSummaryPlot

*Plot binding site filter diagnostics*

## Description

A diagnostic function that plots the number of binding sites retained after each filtering step calculated in [makeBindingSites](#). The function [makeBindingSites](#) is expected to be executed prior to calling this plot function.

## Usage

```
makeBsSummaryPlot(object)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object
--------	-------------------------------------

## Value

a plot of type [ggplot](#)

## See Also

[makeBindingSites](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
makeBsSummaryPlot(bds)
```

---

`mergeCrosslinkDiagnosticsPlot`  
*Plot binding site merging diagnostics*

---

## Description

A diagnostic function that plots the number of regions to merge over the width of these regions for each merging iteration calculated in `makeBindingSites`. The function `makeBindingSites` is expected to be executed prior to calling this plot function.

## Usage

```
mergeCrosslinkDiagnosticsPlot(object)
```

## Arguments

object	a <code>BSFDataSet</code> object
--------	----------------------------------

## Value

a plot of type `ggplot`

## See Also

`makeBindingSites`

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
mergeCrosslinkDiagnosticsPlot(bds)
```

---

`mergeSummaryPlot` *Plot summarized results of the different binding site merging and filtering steps*

---

## Description

Bar charts produced for the different filter steps in the binding site merging routine. Depending on the selected option (`select`) all or only a user defined filter can be shown.

## Usage

```
mergeSummaryPlot(
  object,
  select = c("all", "filter", "inputRanges", "minClSites", "mergeCrosslinkSites",
            "minCrosslinks", "centerIsClSite", "centerIsSummit"),
  ...
)
```

**Arguments**

object	a BSFDataObject, with the makeBindingSites function already run
select	one of "all", "filter", "inputRanges", "minCLSites", "mergeCrosslinkSites", "minCrosslinks", "centerIsCISite" or "centerIsSummit". Defines which parameter is selected for plotting.
...	further arguments passed to ggplot

**Details**

If object is a single BSFDataObject a single coverage plot will be drawn, whereas if it is a list of BSFDataObjects, then faceting is used to make a plot for each list element.

**Value**

a plot of type ggplot after the [makeBindingSites](#) function was run

**See Also**

[makeBindingSites](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# plotting a single object
bds0 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minCLSites = 1)
mergeSummaryPlot(bds0)

# plotting multiple objects
bds1 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minCLSites = 1, sub.chr = "chr22")
bds2 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minCLSites = 3, sub.chr = "chr22")
l = list(`1. bsSize = 3` = bds1, `2. bsSize = 9` = bds2)
mergeSummaryPlot(l, width = 20)
```

---

**plotBsBackgroundFilter**

*Diagnostic plots for the differential binding background*

---

**Description**

To perform differential binding analysis between two conditions the [calculateBsBackground](#) function groups crosslinks per gene into those from binding sites and those from background regions. The [filterBsBackground](#) function performs certain filtering operations on that background to ensure that it's suitable for differential testing. This function visually displays the effect of these filtering operations.

**Usage**

```
plotBsBackgroundFilter(  
  object,  
  filter = c("minCounts", "balanceBackground", "balanceCondition")  
)
```

**Arguments**

object a [BSFDataSet](#) object with background counts filtered by [filterBsBackground](#)  
filter character; which filter to display in the plot (one of: 'minCounts', 'balanceBackground', 'balanceCondition')

**Value**

a plot of type [ggplot](#)

**See Also**

[calculateBsBackground](#)  
[filterBsBackground](#)

**Examples**

```
# load clip data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])  
  
# make testset  
bds = makeBindingSites(bds, bsSize = 7)  
bds = assignToGenes(bds, anno.genes = gns)  
bds = imputeBsDifferencesForTestdata(bds)  
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)  
  
# use all filters and remove binding sites that fail (default settings)  
bds = filterBsBackground(bds)  
  
# display minCount filter  
plotBsBackgroundFilter(bds, filter = "minCounts")  
  
# display balance background filter  
plotBsBackgroundFilter(bds, filter = "balanceBackground")  
  
# display balance condition filter  
plotBsBackgroundFilter(bds, filter = "balanceCondition")
```

---

`plotBsMA`*MA style plot*

---

## Description

Wrapper that plots differential binding results as MA plot. For each binding site the estimated baseMean (log2) is shown on X and the fold-change (log2) is shown on Y.

## Usage

```
plotBsMA(object, what = c("bs", "bg"), sig.threshold = 0.05)
```

## Arguments

<code>object</code>	a <a href="#">BSFDataSet</a> object with results calculated by <a href="#">calculateBsFoldChange</a>
<code>what</code>	character; whether to show results for binding sites or the background (one of: 'bs', 'bg')
<code>sig.threshold</code>	numeric; what P value significance level to use (default = 0.05)

## Value

a plot of type [ggplot](#)

## See Also

[calculateBsFoldChange](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make MA plot
plotBsMA(bds)
```

---

`plotBsVolcano`*Volcano style plot*

---

## Description

Wrapper that plots differential binding results as volcano plot. For each binding site the estimated fold-change (log2) is shown on X and the adjusted P value (-log10) is shown on Y.

## Usage

```
plotBsVolcano(object, what = c("bs", "bg"), sig.threshold = 0.05)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with results calculated by <a href="#">calculateBsFoldChange</a>
what	character; whether to show results for binding sites or the background (one of: 'bs', 'bg')
sig.threshold	numeric; what P value significance level to use (default = 0.05)

## Value

a plot of type [ggplot](#)

## See Also

[calculateBsFoldChange](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])

# make testset
bds = makeBindingSites(bds, bsSize = 7)
bds = assignToGenes(bds, anno.genes = gns)
bds = imputeBsDifferencesForTestdata(bds)
bds = calculateBsBackground(bds, anno.genes = gns, use.offset = FALSE)

# use all filters and remove binding sites that fail (default settings)
bds = filterBsBackground(bds)

# calculate fold-changes
bds = calculateBsFoldChange(bds)

# make volcano plot
plotBsVolcano(bds)
```

---

processingStepsFlowChart  
*Step-wise flowchart plot*

---

## Description

An overview plot that shows all workflow functions that were executed on the current object, with all input and output binding site numbers and major options that were used. The function can be called at any time in the analysis. Most optimal usage is after a full run of the wrapper function [BSFind](#).

## Usage

```
processingStepsFlowChart(object, size.all = 3)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object
size.all	numeric; size of all numbers

## Value

a plot of type [ggplot](#)

## See Also

[BSFind](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,
  est.subsetChromosome = "chr22")
processingStepsFlowChart(bds)
```

---

processingStepsTable *Create a table of all workflow steps for reporting*

---

## Description

Function that creates a printable table with all steps and numbers for each of the workflow steps that were carried out.

## Usage

```
processingStepsTable(object, option = c("reduced", "full", "extended"))
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored ranges
option	character; how detailed the table should be

## Details

If [option](#) is set to ‘reduced’, only the most necessary information are collected. Option ‘full’ contains a full list of all options and parameters that were set in any of the workflow functions. Option ‘extended’ contains extra information about the binding site merging step.

## Value

a [kableExtra](#) table

## See Also

[BSFind](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# apply 5% filter
bds = pureClipGlobalFilter(object = bds, cutoff = 0.05)
processingStepsTable(bds)
```

---

## pureClipGeneWiseFilter

*Filter PureCLIP sites by their score distribution per gene*

---

## Description

Function that applies a filter on the crosslink site score distribution at gene level. This allows to filter for those sites with the strongest signal on each gene. Since scores are tied to the expression level of the hosting transcript this function allows a fair filter for all genes partially independent of the expression level.

## Usage

```
pureClipGeneWiseFilter(
  object,
  cutoff = 0.05,
  overlaps = c("keepSingle", "removeAll", "keepAll"),
  anno.annoDB = NULL,
  anno.genes = NULL,
  match.score = "score",
  match.geneID = "gene_id",
  quiet = FALSE
)
```

## Arguments

object	a <a href="#">BSFDataSet</a> object with stored crosslink ranges of width=1
cutoff	numeric; defines the cutoff for which sites to remove, the smallest step is 1% (0.01). A cutoff of 5% will remove the lowest 5% sites, given their score, on each gene, thus keeping the strongest 95%.
overlaps	character; how overlapping gene loci should be handled.
anno.annoDB	an object of class <a href="#">OrganismDbi</a> that contains the gene annotation (!!! Experimental !!!).
anno.genes	an object of class <a href="#">GenomicRanges</a> that represents the gene ranges directly
match.score	character; meta column name of the crosslink site <a href="#">GenomicRanges</a> object that holds the score which is used for sub-setting
match.geneID	character; meta column name of the genes <a href="#">GenomicRanges</a> object that holds a unique geneID
quiet	logical; whether to print messages

## Details

The [GenomicRanges](#) contained in the [BSFDataSet](#) need to have a meta-column that holds a numeric score value, which is used for filtering. The name of the column can be set with `scoreCol`.

In the case of overlapping gene annotation, a single crosslink site will be attributed to multiple genes. The [overlaps](#) parameter allows to control these cases. Option ‘keepSingle’ will only keep a single instance of the site; ‘removeAll’ will remove both sites; ‘keepAll’ will keep both sites.

The function is part of the standard workflow performed by [BSFind](#).

## Value

an object of class [BSFDataSet](#) with its ranges filtered by those that passed the gene-wise threshold set with `cutoff`

## See Also

[BSFind](#), [estimateBsWidthPlot](#)

## Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# Load GRanges with genes
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
# apply 5% gene-wise filter
pureClipGeneWiseFilter(object = bds, anno.genes = gns, cutoff = 0.5, overlaps = "keepSingle")
```

---

`pureClipGlobalFilter` *Filter PureCLIP sites by their score distribution*

---

## Description

Function that applies a filter on the global crosslink site score distribution. The `GenomicRanges` contained in the `BSFDataSet` need to have a meta-column that holds a numeric score value, which is used for filtering. The name of the column can be set with `match.score`.

## Usage

```
pureClipGlobalFilter(  
  object,  
  cutoff = 0.01,  
  match.score = "score",  
  quiet = FALSE  
)
```

## Arguments

<code>object</code>	a <code>BSFDataSet</code> object with stored crosslink ranges of width=1
<code>cutoff</code>	numeric; defines the cutoff for which sites to keep, the smallest step is 1% (0.01)
<code>match.score</code>	character; meta column name of the crosslink site <code>GenomicRanges</code> object that holds the score which is used for sub-setting
<code>quiet</code>	logical; whether to print messages

## Details

The function is part of the standard workflow performed by `BSFind`.

## Value

an object of class `BSFDataSet` with its ranges filtered by those that passed the threshold set with `cutoff`

## See Also

`BSFind`, `pureClipGlobalFilterPlot`

## Examples

```
# load data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
# apply 5% filter  
pureClipGlobalFilter(object = bds, cutoff = 0.05)
```

---

**pureClipGlobalFilterPlot**

*Plot the PureCLIP score distribution with global cutoff indicator*

---

**Description**

A diagnostic function that plots the PureCLIP score distribution on a log2 scale. The function [pureClipGlobalFilter](#) is expected to be executed prior to calling this plot function.

**Usage**

```
pureClipGlobalFilterPlot(object)
```

**Arguments**

object            a [BSFDataSet](#) object

**Value**

a plot of type [ggplot](#)

**See Also**

[pureClipGlobalFilter](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
# apply 5% filter
bds = pureClipGlobalFilter(object = bds, cutoff = 0.05)
pureClipGlobalFilterPlot(bds)
```

---

**quickFigure**

*Quick figures*

---

**Description**

Summarize all results in a set of quick figures. Depending on how the function is called a different set of analytic plots are arranged into either a 'main' or 'supplementary' type multi-panel figure.

**Usage**

```
quickFigure(  
  object,  
  what = c("main", "supp"),  
  save.filename = NULL,  
  save.width = 10,  
  save.height = 12,  
  save.device = "pdf",  
  quiet = TRUE,  
  ...  
)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object
what	character; the plotting option. One of: 'main', 'supp'
save.filename	File name to create on the disc
save.width	numeric; plot size width
save.height	numeric; plot size height
save.device	character; Device to use. One of: 'pdf', 'png', ...
quiet	whether to print messages
...	further arguments passed to <a href="#">ggsave</a>

**Value**

a plot

**See Also**

[BSFind](#)

**Examples**

```
# load clip data  
files <- system.file("extdata", package="BindingSiteFinder")  
load(list.files(files, pattern = ".rda$", full.names = TRUE))  
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])  
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])  
bds = BSFind(bds, anno.genes = gns, anno.transcriptRegionList = regions,  
  est.subsetChromosome = "chr22")  
quickFigure(bds)
```

---

rangeCoveragePlot	<i>Plot crosslink event coverage over binding site range</i>
-------------------	--

---

## Description

A diagnostic plot function that allows to check the coverage of crosslink events over different merged regions. The coverage is shown as mean over all replicates and conditions, with a standard deviation corridor.

## Usage

```
rangeCoveragePlot(
  object,
  width = 20,
  show.samples = FALSE,
  subset.chromosome = "chr1",
  quiet = TRUE
)
```

## Arguments

object	a BSFDataSet, or a list of BSFDataSet
width	numeric; set the plotting range to show (in nt)
show.samples	logical; to show individual samples as lines
subset.chromosome	character; subset by a all ranges on the indicated chromosome. Can also be a vector with multiple chromosomes. If NULL then all ranges are being used.
quiet	logical; whether to print messages

## Details

If object is a single BSFDataObject a single coverage plot will be drawn, whereas if it is a list of BSFDataObjects, then faceting is used to make a plot for each list element.

## Value

a plot of type ggplot2 displaying the crosslink coverage over the ranges of the given BSFDataSet

## See Also

[BSFDataSet](#), [makeBindingSites](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# plotting a single object
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minC1Sites = 1)
```

```
rangeCoveragePlot(bds, subset.chromosome = "chr22")

# plotting multiple objects
bds1 <- makeBindingSites(object = bds, bsSize = 3, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
bds2 <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1, sub.chr = "chr22")
l = list(`1. bsSize = 3` = bds1, `2. bsSize = 9` = bds2)
rangeCoveragePlot(l, subset.chromosome = "chr22")
```

---

**reproducibilityCutoffPlot**

*Plot to that shows how many replicates support each binding site*

---

**Description**

Plotting function for settings specified in [reproducibilityFilter](#).

**Usage**

```
reproducibilityCutoffPlot(
  object,
  cutoff = 0.05,
  min.crosslinks = 1,
  max.range = 20,
  ...
)
```

**Arguments**

<code>object</code>	a BSFDataSet object
<code>cutoff</code>	a vector of length = 1, or of length = levels(meta\$conditions) with a single number (between 0-1) indicating the quantile cutoff
<code>min.crosslinks</code>	numeric of length = 1, defines the lower boundary for the minimum number of crosslinks a binding site has to be supported by all replicates, regardless of the replicate specific quantile threshold
<code>max.range</code>	maximum number of crosslinks per sites that should be shown
<code>...</code>	further arguments passed to ggplot

**Value**

a plot of type ggplot2 showing the per replicate reproducibility cutoffs based on a given quantile threshold

**See Also**

[reproducibilityFilter](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# merge binding sites
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minClSites = 1)

# use the same cutoff for both conditions
suppressWarnings(reproducibilityCutoffPlot(bds, max.range = 20, cutoff = c(0.05)))

# use different cutoffs for each condition
suppressWarnings(reproducibilityCutoffPlot(bds, max.range = 20, cutoff = c(0.1)))
```

---

reproducibilityFilter *Replicate reproducibility filter function*

---

## Description

For each replicate the number of binding sites with a certain number of crosslinks is calculated. A quantile based threshold (cutoff) is applied to each replicate. This indicates how many of the merged binding sites are supported by crosslinks from the respective replicate. Next, one can specify how many replicates need to pass the defined threshold for a binding site to be considered reproducible.

## Usage

```
reproducibilityFilter(
  object,
  cutoff = NULL,
  nReps = NULL,
  minCrosslinks = 1,
  returnType = c("BSFDataSet", "data.frame"),
  n.reps = lifecycle::deprecated(),
  min.crosslinks = lifecycle::deprecated(),
  quiet = FALSE
)
```

## Arguments

object	a BSFDataSet object
cutoff	numeric; percentage cutoff to be used for the reproducibility quantile filtering
nReps	numeric; number of replicates that must meet the cutoff defined in cutoff for a binding site to be called reproducible. Defaults to N-1.
minCrosslinks	numeric; minimal number of crosslinks a binding site needs to have to be called reproducible. Acts as a lower boundary for cutoff. Defaults to 1.
returnType	one of "BSFDataSet" or "data.frame". "BSFDataSet" is the default and "matrix" can be used for easy plotting.

```

n.reps           deprecated -> use nReps instead
min.crosslinks  deprecated -> use minCrosslinks instead
quiet            logical; whether to print messages

```

## Details

If cutoff is a single number then the indicated cutoff will be applied to all replicates. If it is a vector then each element in the vector is applied to all replicates of the respective condition. The order is hereby given by the levels of the condition column of the meta data (see [BSFDataSet.getMeta](#)). If the condition specific filter is applied, a meta column is added to the GRanges of the BSFDataSet object, indicating the support for each condition.

If nReps is a single number then this number is used as threshold for all binding sites. If it is a vector then it is applied to the replicates of the respective condition (like in cutoff). This allows the application of different thresholds for experiments of different experimental conditions. If the condition specific filter is applied, a meta column is added to the GRanges of the BSFDataSet object, indicating the support for each condition.

The function is part of the standard workflow performed by [BSFind](#).

## Value

an object of type BSFDataSet

## See Also

[BSFind](#), [reproducibilityFilterPlot](#), [reproducibilitySamplesPlot](#), [reproducibilityScatterPlot](#)

## Examples

```

# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

# merge binding sites
bds <- makeBindingSites(object = bds, bsSize = 9)

# use default return with condition specific threshold
bds = reproducibilityFilter(bds, cutoff = 0.1, nReps = 1)

```

---

### reproducibilityFilterPlot

*Plot to that shows the crosslink site distribution per replicate*

---

## Description

A diagnostic function that plots the number of crosslinks sites over the number of crosslink in these sites and highlights the replicate specific reproducibility cutoff that is derived from that distribution. The function [reproducibilityFilter](#) is expected to be executed prior to calling this plot function.

## Usage

```
reproducibilityFilterPlot(object, plotRange = 20)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object
plotRange	numeric; number of crosslinks per sites that should be shown before summing them up

**Value**

a plot of type [ggplot](#)

**See Also**

[reproducibilityFilter](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
bds = reproducibilityFilter(bds)
reproducibilityFilterPlot(bds)
```

**reproducibilitySamplesPlot**

*UpSet-plot to that shows how each replicate supports binding sites*

**Description**

A diagnostic function that plots the set sizes for each replicate, indicating how many binding site the specific replicate supports given its specific threshold. The function [reproducibilityFilter](#) is expected to be executed prior to calling this plot function.

**Usage**

```
reproducibilitySamplesPlot(
  object,
  nIntersections = 20,
  show.title = TRUE,
  text.size = NULL
)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object
nIntersections	numeric; number of intersection to be shown
show.title	logical; if plot title should be visible
text.size	numeric; fontsize of all numbers on axis

**Value**

a plot of type [ggplot](#)

**See Also**

[reproducibilityFilter](#), [reproducibilityFilterPlot](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds = makeBindingSites(object = bds, bsSize = 9)
bds = reproducibilityFilter(bds)
reproducibilitySamplesPlot(bds)
```

---

**reproducibilityScatterPlot**

*Plot that shows binding site reproducibility as scatter*

---

**Description**

Function compute the number of crosslinks per binding site on a log2 scale for each sample. Samples are pairwise correlated as a scatter and pairwise pearson correlation is shown.

**Usage**

```
reproducibilityScatterPlot(object, quiet = FALSE)
```

**Arguments**

object	a BSFDataSet object
quiet	logical; whether to print messages

**Details**

Unlike most plotting functions, this function is actively calculating the values to plot.

**Value**

an object of class [ggplot2](#)

**See Also**

[BSFind](#), [reproducibilityFilter](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
bds <- makeBindingSites(object = bds, bsSize = 9, minWidth = 2,
minCrosslinks = 2, minCISites = 3, sub.chr = "chr22")
reproducibilityScatterPlot(bds)
```

**setMeta**

*Setter method for the meta data of the BSFDataSet object*

## Description

Meta data is stored as a `data.frame` and must contain the columns "condition", "clPlus" and "clMinus".

## Usage

```
setMeta(object, ...)
## S4 method for signature 'BSFDataSet'
setMeta(object, newMeta)
```

## Arguments

<code>object</code>	a BSFDataSet object
<code>...</code>	additional arguments
<code>newMeta</code>	the replacement meta data table

## Value

an object of type `BSFDataSet` with updated meta data

## See Also

[BSFDataSet](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

nMeta = getMeta(bds)
setMeta(bds, nMeta)
```

---

setName	<i>Setter method for the names of the BSFDataSet object The name slot holds the name information of the dataset</i>
---------	---

---

## Description

Setter method for the names of the BSFDataSet object The name slot holds the name information of the dataset

## Usage

```
setName(object, ...)
## S4 method for signature 'BSFDataSet'
setName(object, newName)
```

## Arguments

object	a BSFDataSet object
...	additional arguments
newName	a character that is the name

## Value

object of type [BSFDataSet](#) with updated name

## See Also

[BSFDataSet](#)

## Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = setName(bds, "test01")
```

---

setRanges	<i>Setter method for the ranges of the BSFDataSet object The GRanges object that holds the genomic ranges information can be replaced.</i>
-----------	--

---

## Description

Setter method for the ranges of the BSFDataSet object The GRanges object that holds the genomic ranges information can be replaced.

**Usage**

```
setRanges(object, ...)

## S4 method for signature 'BSFDataSet'
setRanges(object, newRanges, dropSeqlevels = TRUE, quiet = FALSE)
```

**Arguments**

object	a BSFDataSet object
...	additional arguments
newRanges	an object of type GRanges
dropSeqlevels	enforce seqnames to be the same in ranges and signal, by dropping unused seqlevels which is required for most downstream functions such as coverageOverRanges
quiet	logical; whether to print messages

**Value**

object of type [BSFDataSet](#) with updated ranges

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

rng = getRanges(bds)
rng = rng + 10
bdsNew = setRanges(bds, rng)
```

**setSignal**

*Setter method for the signal data of the BSFDataSet object*

**Description**

Signal data is loaded from the path specified in [getMeta](#) columns "clPlus" and "clMinus" and stored as a list of RLE lists.

**Usage**

```
setSignal(object, ...)

## S4 method for signature 'BSFDataSet'
setSignal(object, newSignal, dropSeqlevels = TRUE, quiet = FALSE)
```

**Arguments**

object	a BSFDataSet object
...	additional arguments
newSignal	list of RLE lists
dropSeqlevels	enforce seqnames to be the same in ranges and signal, by dropping unused seqlevels which is required for most downstream functions such as coverageOverRanges
quiet	logical; whether to print messages

**Value**

an object of type [BSFDataSet](#) with updated signal

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

sgn = getSignal(bds)
sgn = lapply(sgn, function(selStrand){
  lapply(selStrand, function(chrList){
    chrList[names(chrList) == "chr22"]
  })
})
bdsNew = setSignal(bds, sgn)
```

**setSummary**

*Setter method for the summary slot of the BSFDataSet object*

**Description**

The summary slot is used to track information of the filtering steps applied in the [makeBindingSites](#) function

**Usage**

```
setSummary(object, ...)
## S4 method for signature 'BSFDataSet'
setSummary(object, summary)
```

**Arguments**

object	a BSFDataSet object
...	additional arguments
summary	a data.frame with the summary information to be stored in BSFDataSet

**Value**

an object of type [BSFDataSet](#) with updated summary info

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

df = data.frame(processingStep = c(1,2),
parameter = c(3,4))
bds = setSummary(bds, df)
```

show

*Show method to for the BSFDataSet*

**Description**

Prints the information for each of the input data slots in the [BSFDataSet](#) object.

**Usage**

```
## S4 method for signature 'BSFDataSet'
show(object)
```

**Arguments**

object a BSFDataSet object

**Value**

shows the current object state

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

show(bds)
```

---

subset-BSFDataSet	<i>Subset a BSFDataSet object</i>
-------------------	-----------------------------------

---

### Description

You can subset [BSFDataSet](#) by identifier or by position using the `[]` operator. Empty seqlevels are being dropped after the subset.

### Usage

```
## S4 method for signature 'BSFDataSet,ANY,ANY,ANY'
x[i, j, ... , drop = FALSE]
```

### Arguments

x	A <a href="#">BSFDataSet</a> object.
i	Position of the identifier or the name of the identifier itself.
j	Not used.
...	Additional arguments not used here.
drop	if the signal not covered by the subsetted ranges should be dropped or not

### Value

A [BSFDataSet](#) object.

### Examples

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

bdsNew = bds[1:10]
```

---

summary	<i>Summary method to for the BSFDataSet</i>
---------	---

---

### Description

Prints the summaryinformation for the [BSFDataSet](#) object. This includes information on samples, conditions and crosslinks.

### Usage

```
## S4 method for signature 'BSFDataSet'
summary(object)
```

### Arguments

object	a <a href="#">BSFDataSet</a> object
--------	-------------------------------------

**Value**

summary of the current object

**See Also**

[BSFDataSet](#)

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

summary(bds)
```

---

supportRatio

*Support ratio function for BSFDataSet objects*

---

**Description**

Functions that computes a ratio to determine how well a given binding site with is supported by the crosslink coverage of the data. For a given BSFDataSet object binding sites are computed for each width indicated in the `bsWidths` vector (using the [coverageOverRanges](#) function). These coverages are compared to the coverage of regions flanking the binding sites. If not indicated in `bsFlank` these regions are of the same width as the binding sites.

**Usage**

```
supportRatio(object, bsWidths, bsFlank = NA, sub.chr = NA, ...)
```

**Arguments**

object	a BSFDataSet object
bsWidths	a numeric vector indicating the different binding site width to compute the ratio for
bsFlank	optional; a numeric vector of the same length as <code>bsWidth</code> used to specify the width of the flanking regions
sub.chr	chromosome identifier (eg, chr1, chr2) used for subsetting the BSFDataSet object.
...	further arguments passed to <code>makeBindingSites</code>

**Details**

Testing the width of 3nt for example, would result in a coverage within all 3nt wide binding sites (`c1`) and a coverage computed on the adjacent 3nt flanking the binding sites up- and downstream (`f1, f2`). Based on these numbers the ratio is computed by:  $c1/(1/2(f1+f2))$ .

The median over all ratios is reported as representative value.

**Value**

an object of class `data.frame`

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

suppressWarnings(supportRatio(bds, bsWidths = c(3,7)))
```

`supportRatioPlot`

*Plot that shows the binding site support ratio*

**Description**

Function that shows a ratio to determine how well a given binding site with is supported by the crosslink coverage of the data. Ratios are computed using the `supportRatio` function.

**Usage**

```
supportRatioPlot(object, bsWidths, bsFlank = NA, ...)
```

**Arguments**

<code>object</code>	a BSFDataSet object
<code>bsWidths</code>	a numeric vector indicating the different binding site width to compute the ratio for
<code>bsFlank</code>	optional; a numeric vector of the same length as <code>bsWidth</code> used to specify the width of the flanking regions
<code>...</code>	further arguments passed to <code>makeBindingSites</code>

**Details**

The higher the ratio, the more does the given binding site width captures the enrichment of crosslinks compared the the local surrounding. A ratio equal to 1 would mean no enrichment at all.

**Value**

an object of class `ggplot2`

**Examples**

```
# load data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))

suppressWarnings(supportRatioPlot(bds, bsWidths = c(3,7),
minWidth = 1, minClSites = 1, minCrosslinks = 2))
```

---

**targetGeneSpectrumPlot**

*Bar-chart to show the hosting gene types of binding sites*

---

**Description**

A diagnostic function that plots the gene type of the hosting gene for each binding site. The function [assignToGenes](#) is expected to be executed prior to calling this plot function.

**Usage**

```
targetGeneSpectrumPlot(object, showNGroups = 5, text.size = 4)
```

**Arguments**

object	a <a href="#">BSFDataSet</a> object
showNGroups	numeric; the number of different gene types to show
text.size	numeric; the size of the text elements on the plot

**Value**

a plot of type [ggplot](#)

**See Also**

[assignToGenes](#) [geneOverlapsPlot](#)

**Examples**

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
targetGeneSpectrumPlot(bds)
```

---

**transcriptRegionOverlapsPlot**

*UpSet-plot to that shows the transcript region overlaps*

---

**Description**

A diagnostic function that plots the transcript regions of binding sites on overlapping loci. The function [assignToTranscriptRegions](#) is expected to be executed prior to calling this plot function.

**Usage**

```
transcriptRegionOverlapsPlot(object, text.size = NULL, show.title = TRUE)
```

### Arguments

object	a <a href="#">BSFDataSet</a> object
text.size	numeric; fontsize of all numbers on axis
show.title	logical; if plot title should be visible

### Value

a plot of type [ggplot](#)

### See Also

[assignToTranscriptRegions](#) [transcriptRegionSpectrumPlot](#)

### Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
transcriptRegionOverlapsPlot(bds)
```

---

### transcriptRegionSpectrumPlot

*Bar-chart to show the hosting transcript regions of binding sites*

---

### Description

A diagnostic function that plots the transcript regions of the hosting gene for each binding site. The function [assignToTranscriptRegions](#) is expected to be executed prior to calling this plot function.

### Usage

```
transcriptRegionSpectrumPlot(
  object,
  values = c("asis", "percentage"),
  normalize = FALSE,
  normalize.factor = c("sum", "median", "mean"),
  show.others = FALSE,
  text.size = 4
)
```

### Arguments

object	a <a href="#">BSFDataSet</a> object
values	character; if values should be presented 'as-is', that means for example as frequencies in case <code>normalization = FALSE</code> , or as percentages
normalize	logical; whether to normalize values
normalize.factor	character; indicate by what factor values should be normalized to region length by
show.others	logical; whether to show 'others' category. Has to be false if <code>normalize = TRUE</code>
text.size	numeric; font size of the numbers to be displayed on each bar

### Details

Count frequencies can be normalized to the length of the hosting region with option `normalize`. The specific factor how the hosting region length is used is given by `normalize.factor`. In the case of `normalize.factor = "sum"` binding site frequencies are divided by the summed length of all regions that host the specific binding site.

Further with option `values` once can indicate whether raw or normalized frequencies should be shown 'as-is' or normalized to 'percentages'.

### Value

a plot of type [ggplot](#)

### See Also

[assignToTranscriptRegions](#) [transcriptRegionOverlapsPlot](#)

### Examples

```
# load clip data
files <- system.file("extdata", package="BindingSiteFinder")
load(list.files(files, pattern = ".rda$", full.names = TRUE))
load(list.files(files, pattern = ".rds$", full.names = TRUE)[1])
load(list.files(files, pattern = ".rds$", full.names = TRUE)[2])
bds = makeBindingSites(object = bds, bsSize = 9)
bds = assignToGenes(bds, anno.genes = gns)
bds = assignToTranscriptRegions(object = bds, anno.transcriptRegionList = regions)
transcriptRegionSpectrumPlot(bds)
```

# Index

+`,BSFDataSet,BSFDataSet-method`  
  `(add-BSFDataSet), 3`  
[`,BSFDataSet,ANY,ANY,ANY-method`  
  `(subset-BSFDataSet), 69`

`add-BSFDataSet, 3`  
`annotateWithScore, 4, 13, 15, 16, 42, 43`  
`assignToGenes, 6, 13, 15, 16, 18, 32, 36, 38, 72`  
`assignToTranscriptRegions, 7, 13, 15, 16, 32, 38, 72–74`

`bindingSiteCoveragePlot, 9`  
`bindingSiteDefinednessPlot, 10, 22`  
`BSFDataSet, 3, 6–10, 11, 12, 14, 16–18, 20–22, 24–29, 31, 33–47, 49–58, 61, 62, 64–70, 72–74`  
`BSFDataSet, (BSFDataSet), 11`  
`BSFDataSet-class, (BSFDataSet), 11`  
`BSFDataSetFromBigWig(BSFDataSet), 11`  
`BSFind, 5, 7, 8, 10, 11, 12, 18, 22, 24, 30–33, 38, 45, 52–55, 57, 61, 63`

`calculateBsBackground, 16, 21, 26, 35, 48, 49`  
`calculateBsFoldChange, 19, 37, 38, 50, 51`  
`calculateSignalToFlankScore, 11, 13, 16, 21`  
`clipCoverage, 22`  
`collapseReplicates, 24`  
`combineBSF, 3, 18, 25`  
`CompressedGRangesList, 7, 8, 15`  
`coverageOverRanges, 27, 70`

`DESeq, 19–21`  
`duplicatedSitesPlot, 28`

`estimateBsWidth, 13–16, 29, 30, 31`  
`estimateBsWidthPlot, 16, 31, 31, 54`  
`exportTargetGenes, 32`  
`exportToBED, 33`

`filterBsBackground, 18, 21, 34, 48, 49`  
`format, 32`

`geneOverlapsPlot, 7, 36, 72`  
`geneRegulationPlot, 37`  
`GenomicRanges, 5, 6, 15, 17, 30, 37, 54, 55`  
`getMeta, 39, 41, 61, 66`  
`getMeta,BSFDataSet-method (getMeta), 39`  
`getName, 39`  
`getName,BSFDataSet-method (getName), 39`  
`getRanges, 40`  
`getRanges,BSFDataSet-method (getRanges), 40`  
`getSignal, 41`  
`getSignal,BSFDataSet-method (getSignal), 41`  
`getSummary, 42`  
`getSummary,BSFDataSet-method (getSummary), 42`  
`ggplot, 11, 28, 31, 36, 43, 46, 47, 49–52, 56, 62, 63, 72–74`  
`ggsave, 57`  
`globalScorePlot, 5, 42`

`imputeBsDifferencesForTestdata, 43`

`lfcShrink, 20, 21`

`makeBindingSites, 13, 15, 30, 42, 44, 46–48, 58, 67`  
`makeBsSummaryPlot, 45, 46`  
`mergeCrosslinkDiagnosticsPlot, 45, 47`  
`mergeSummaryPlot, 47`

`option, 53`  
`overlaps, 6, 8, 54`

`plotBsBackgroundFilter, 21, 35, 48`  
`plotBsMA, 50`  
`plotBsVolcano, 51`  
`processingStepsFlowChart, 16, 26, 52`  
`processingStepsTable, 52`  
`pureClipGeneWiseFilter, 13–16, 28, 30, 53`  
`pureClipGlobalFilter, 13, 14, 16, 55, 56`  
`pureClipGlobalFilterPlot, 55, 56`

`quickFigure, 56`

rangeCoveragePlot, 58  
reproducibilityCutoffPlot, 59  
reproducibilityFilter, 13, 15, 16, 59, 60,  
    61–63  
reproducibilityFilterPlot, 61, 61, 63  
reproducibilitySamplesPlot, 61, 62  
reproducibilityScatterPlot, 61, 63  
results, 20, 21  
  
setMeta, 64  
setMeta, BSFDataSet-method (setMeta), 64  
setName, 65  
setName, BSFDataSet-method (setName), 65  
setRanges, 65  
setRanges, BSFDataSet-method  
    (setRanges), 65  
setSignal, 66  
setSignal, BSFDataSet-method  
    (setSignal), 66  
setSummary, 67  
setSummary, BSFDataSet-method  
    (setSummary), 67  
show, 68  
show, BSFDataSet-method (show), 68  
subset-BSFDataSet, 69  
summary, 69  
summary, BSFDataSet-method (summary), 69  
supportRatio, 70, 71  
supportRatioPlot, 71  
  
targetGeneSpectrumPlot, 7, 36, 72  
transcriptRegionOverlapsPlot, 8, 72, 74  
transcriptRegionSpectrumPlot, 8, 73, 73