

# Package ‘RBioFormats’

January 23, 2026

**Version** 1.10.0

**BioFormats** 7.3.0

**Title** R interface to Bio-Formats

**Description** An R package which interfaces the OME Bio-Formats Java library to allow reading of proprietary microscopy image data and metadata.

**Encoding** UTF-8

**biocViews** DataImport

**URL** <https://github.com/aoles/RBioFormats>

**BugReports** <https://github.com/aoles/RBioFormats/issues>

**Imports** EBImage, methods, rJava (>= 0.9-6), S4Vectors, stats

**Suggests** BiocStyle, knitr, testthat, xml2

**SystemRequirements** Java (>= 1.7)

**License** GPL-3

**VignetteBuilder** knitr

**Collate** 'ImageMetadata.R' 'AnnotatedImage.R' 'RBioFormats.R'  
'metadataAccessors.R' 'mockFile.R' 'read.image.R'  
'read.metadata.R' 'read.omexml.R' 'utils.R' 'write.image.R'  
'zzz.R'

**RoxygenNote** 7.2.3

**git\_url** <https://git.bioconductor.org/packages/RBioFormats>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 52b73ef

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2026-01-22

**Author** Andrzej Oleś [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-0285-2787>>),  
John Lee [ctb] (ORCID: <<https://orcid.org/0000-0001-5884-4247>>)

**Maintainer** Andrzej Oleś <[andrzej.oles@gmail.com](mailto:andrzej.oles@gmail.com)>

## Contents

|                                    |           |
|------------------------------------|-----------|
| AnnotatedImage-class . . . . .     | 2         |
| AnnotatedImageList-class . . . . . | 3         |
| checkJavaMemory . . . . .          | 4         |
| coreMetadata . . . . .             | 4         |
| dimorder . . . . .                 | 6         |
| FormatTools . . . . .              | 7         |
| ImageMetadata-class . . . . .      | 7         |
| mockFile . . . . .                 | 8         |
| RBioFormats . . . . .              | 9         |
| read.image . . . . .               | 10        |
| read.metadata . . . . .            | 11        |
| read.omexml . . . . .              | 12        |
| seriesCount . . . . .              | 13        |
| write.image . . . . .              | 14        |
| <b>Index</b>                       | <b>15</b> |

---

AnnotatedImage-class    *AnnotatedImage Class*

---

### Description

Extends the [Image](#) class from the **EBImage** package.

### Usage

```
AnnotatedImage(..., metadata = ImageMetadata())
```

```
## S3 method for class 'AnnotatedImage'
print(x, short = FALSE, ...)
```

```
## S4 method for signature 'AnnotatedImage'
show(object)
```

```
## S3 method for class 'AnnotatedImage'
as.Image(x)
```

### Arguments

|          |                                                                   |
|----------|-------------------------------------------------------------------|
| ...      | arguments passed to the <a href="#">Image</a> constructor.        |
| metadata | an <a href="#">ImageMetadata</a> object containing image metadata |
| x        | an <a href="#">AnnotatedImage</a> object.                         |
| short    | logical, turns off image data preview.                            |
| object   | an <a href="#">AnnotatedImage</a> object                          |

### Value

AnnotatedImage returns a new [AnnotatedImage](#) object.  
as.Image returns an [Image](#) object.

**Slots**

metadata an [ImageMetadata](#) object containing image metadata

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**See Also**

[AnnotatedImageList](#)

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256)
img = read.image(f)
img
```

---

AnnotatedImageList-class

*AnnotatedImageList Class*

---

**Description**

A list of [AnnotatedImage](#) objects.

**Usage**

```
AnnotatedImageList(...)
```

**Arguments**

... a list of [AnnotatedImage](#) objects to include in the new object.

**Value**

AnnotatedImageList returns a new [AnnotatedImageList](#) object.

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256, series = 2)
img = read.image(f)
img
```

---

|                 |                             |
|-----------------|-----------------------------|
| checkJavaMemory | <i>Java Memory Settings</i> |
|-----------------|-----------------------------|

---

**Description**

Information about the Java heap space usage.

**Usage**

```
checkJavaMemory(units = "m")
```

**Arguments**

|       |                                              |
|-------|----------------------------------------------|
| units | Units to return the size in: "k", "m" or "g" |
|-------|----------------------------------------------|

**Value**

The maximum amount of memory that the JVM will attempt to use, measured in units.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
## Not run:
## assign 4 gigabytes of heap space to the Java environment.
options( java.parameters = "-Xmx4g" )
library( "RBioFormats" )

## End(Not run)

checkJavaMemory()
```

---

|              |                           |
|--------------|---------------------------|
| coreMetadata | <i>Metadata Accessors</i> |
|--------------|---------------------------|

---

**Description**

Get and set image metadata.

**Usage**

```
coreMetadata(x, series, ...)

globalMetadata(x, series, ...)

seriesMetadata(x, series, ...)

## S4 method for signature 'ANY'
metadata(x)
```

```

## S4 method for signature 'AnnotatedImage'
metadata(x)

## S4 method for signature 'AnnotatedImageList'
metadata(x)

## S4 method for signature 'ImageMetadata'
metadata(x)

## S4 method for signature 'ImageMetadataList'
metadata(x)

## S4 replacement method for signature 'AnnotatedImage'
metadata(x) <- value

coreMetadata(y) <- value

## S4 replacement method for signature 'AnnotatedImage'
coreMetadata(y) <- value

## S4 replacement method for signature 'ImageMetadata'
coreMetadata(y) <- value

globalMetadata(y) <- value

## S4 replacement method for signature 'AnnotatedImage'
globalMetadata(y) <- value

## S4 replacement method for signature 'ImageMetadata'
globalMetadata(y) <- value

seriesMetadata(y) <- value

## S4 replacement method for signature 'AnnotatedImage'
seriesMetadata(y) <- value

## S4 replacement method for signature 'ImageMetadata'
seriesMetadata(y) <- value

```

## Arguments

|        |                                                                                                                                                      |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| x      | an <a href="#">AnnotatedImage</a> , <a href="#">AnnotatedImageList</a> , <a href="#">ImageMetadata</a> , or <a href="#">ImageMetadataList</a> object |
| series | series ID                                                                                                                                            |
| ...    | arguments passed to <a href="#">grep</a>                                                                                                             |
| value  | depending on the context, an <a href="#">ImageMetadata</a> object or a list                                                                          |
| y      | an <a href="#">AnnotatedImage</a> or <a href="#">ImageMetadata</a> object                                                                            |

## Details

The ... arguments are passed to [grep](#) called on metadata names allowing for convenient subsetting.

**Value**

Named list consisting of key value pairs.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
img = read.image(system.file("images", "nuclei.tif", package="EBImage"))  
  
coreMetadata(img)  
  
# subset for specific names  
  
globalMetadata(img, pattern="Image")
```

---

dimorder

*Image Frames Order*

---

**Description**

Get the ordering of image frames.

**Usage**

```
dimorder(x)
```

**Arguments**

x                      An [Image](#) object or an array

**Value**

A character vector giving the dimension names.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
# sample timelapse image  
f = mockFile(sizeC=2, sizeT=10)  
img = read.image(f)  
  
dimorder(img)
```

---

FormatTools

*Bio-Formats FormatTools Class*


---

**Description**

A utility class for format reader and writer implementations.

**Usage**

```
FormatTools
```

**Format**

An object of class `jclassName` of length 1.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
# List available pixel types
sapply(0:7, FormatTools$getPixelTypeString)
```

---

ImageMetadata-class

*ImageMetadata and ImageMetadataList Class*


---

**Description**

Formal representation of image metadata.

**Usage**

```
ImageMetadata(
  coreMetadata = NULL,
  globalMetadata = NULL,
  seriesMetadata = NULL
)

ImageMetadataList(...)

## S3 method for class 'ImageMetadata'
print(x, list.len = 5L, ...)

## S4 method for signature 'ImageMetadata'
show(object)

## S4 method for signature 'ImageMetadataList'
show(object)

## S3 method for class 'ImageMetadataList'
print(x, ...)
```

**Arguments**

|                |                                                        |
|----------------|--------------------------------------------------------|
| coreMetadata   | a list of core metadata entries                        |
| globalMetadata | a list of global metadata entries                      |
| seriesMetadata | a list of series metadata entries                      |
| ...            | further arguments to be passed to other methods        |
| x              | An ImageMetadata object                                |
| list.len       | numeric; maximum number of metadata entries to display |
| object         | an ImageMetadata object                                |

**Value**

ImageMetadata returns a new [ImageMetadata](#) object.

ImageMetadataList returns a new [ImageMetadataList](#) object.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256)
img = read.image(f)
metadata(img)
```

---

mockFile

*Generate Test Images*


---

**Description**

Create a mock image of specific parameters for testing.

**Usage**

```
mockFile(name = "mockfile", ...)
```

**Arguments**

|      |                                                         |
|------|---------------------------------------------------------|
| name | File name.                                              |
| ...  | File parameters; available parameters are listed below. |

**Details**

Generates mock files of specific size or pixel type containing gradient images. The desired parameters can be provided as key value pairs to the mockFile function. For a list of available parameters see below.

**Value**

A character string.



**Parameters**

| Name         | Default | Description                                                                            |
|--------------|---------|----------------------------------------------------------------------------------------|
| sizeX        | 512     | horizontal size in pixels                                                              |
| sizeY        | 512     | vertical size in pixels                                                                |
| sizeZ        | 1       | number of Z sections                                                                   |
| sizeC        | 1       | number of channels                                                                     |
| sizeT        | 1       | number of time points                                                                  |
| pixelType    | uint8   | string specifying pixel type: int8, uint8, int16, uint16, int32, uint32, float, double |
| bitsPerPixel | 0       | number of valid bits (<= number of bits implied by pixel type)                         |
| rgb          | 1       | number of channels that are merged together                                            |
| dimOrder     | XYZCT   | string describing dimension order                                                      |
| orderCertain | true    |                                                                                        |
| little       | true    | whether or not the pixel data should be little-endian                                  |
| interleaved  | true    | whether or not merged channels are interleaved                                         |
| indexed      | false   | whether or not a color lookup table is present                                         |
| falseColor   | false   | whether or not the color lookup table is just for making the image look pretty         |
| series       | 1       | number of series (Images)                                                              |
| lutLength    | 3       | number of entries in the color lookup table                                            |

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256)
img = read.image(f)
img
```

---

RBioFormats

*R Interface to Bio-Formats*


---

**Description**

Interfaces the **Bio-Formats** Java library.

**Usage**

```
BioFormats.version()
```

**Value**

A character string containing the Bio-Formats library version.

**Functions**

- `BioFormats.version()`: Provides the version of the Bio-Formats library embedded in the package.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**References**

[Bio-Formats website](#)

**Examples**

```
BioFormats.version()
```

---

|            |                    |
|------------|--------------------|
| read.image | <i>Read Images</i> |
|------------|--------------------|

---

**Description**

Read image files using the Bio-Formats library. A list of supported formats can be found on the [Bio-Formats website](#).

**Usage**

```
read.image(
  file,
  filter.metadata = FALSE,
  proprietary.metadata = TRUE,
  normalize = TRUE,
  series,
  resolution,
  subset,
  read.metadata = TRUE
)
```

**Arguments**

|                      |                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| file                 | character, file name                                                                                                                                    |
| filter.metadata      | logical, specifies whether ugly metadata (entries with unprintable characters, and extremely large entries) should be discarded from the metadata table |
| proprietary.metadata | logical, should proprietary metadata be populated to OME-XML                                                                                            |
| normalize            | logical, should the original image data be mapped to the [0,1] range                                                                                    |
| series               | integer vector specifying series to read; if missing all series included in the file are read                                                           |
| resolution           | integer vector specifying resolution levels to read; if missing all levels read                                                                         |
| subset               | named list specifying image subsetting                                                                                                                  |
| read.metadata        | logical, should image metadata be read                                                                                                                  |

**Value**

An [AnnotatedImage](#) object or an [AnnotatedImageList](#) object in case of multi-series data.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**See Also**

[read.metadata](#) for reading image metadata, [read.omexml](#) for reading image metadata as OME-XML

**Examples**

```
require(EBImage)
f = system.file("images", "sample-color.png", package="EBImage")

img = read.image(f)
img
```

---

|               |                            |
|---------------|----------------------------|
| read.metadata | <i>Read Image Metadata</i> |
|---------------|----------------------------|

---

**Description**

Read image metadata using the Bio-Formats library. The list of supported file formats can be found on the [Bio-Formats website](#).

**Usage**

```
read.metadata(file, filter.metadata = FALSE, proprietary.metadata = TRUE)
```

**Arguments**

|                      |                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| file                 | character, file name                                                                                                                                    |
| filter.metadata      | logical, specifies whether ugly metadata (entries with unprintable characters, and extremely large entries) should be discarded from the metadata table |
| proprietary.metadata | logical, should proprietary metadata be populated to OME-XML                                                                                            |

**Value**

An [ImageMetadata](#) or [ImageMetadataList](#) object.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**See Also**

[read.omexml](#) for reading image metadata as OME-XML, [read.image](#) for reading image data

**Examples**

```
require(EBImage)
f = system.file("images", "nuclei.tif", package="EBImage")

metadata = read.metadata(f)
str(metadata)
```

read.omexml

*Read OME-XML Metadata***Description**

Read the OME-XML DOM tree.

**Usage**

```
read.omexml(file, filter.metadata = FALSE, proprietary.metadata = TRUE)
```

**Arguments**

|                      |                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| file                 | character, file name                                                                                                                                    |
| filter.metadata      | logical, specifies whether ugly metadata (entries with unprintable characters, and extremely large entries) should be discarded from the metadata table |
| proprietary.metadata | logical, should proprietary metadata be populated to OME-XML                                                                                            |

**Value**

A string containing a dumped OME-XML DOM tree.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**See Also**

[read.metadata](#) for reading image metadata, [read.image](#) for reading image data

**Examples**

```
require(EBImage)
f = system.file("images", "nuclei.tif", package="EBImage")

omexml = read.omexml(f)
omexml
```

---

|             |                               |
|-------------|-------------------------------|
| seriesCount | <i>Number of Image Series</i> |
|-------------|-------------------------------|

---

**Description**

Get the number of image series contained in an object.

**Usage**

```
seriesCount(x)

## S4 method for signature 'ANY'
seriesCount(x)

## S4 method for signature 'matrix'
seriesCount(x)

## S4 method for signature 'array'
seriesCount(x)

## S4 method for signature 'ImageMetadata'
seriesCount(x)

## S4 method for signature 'AnnotatedImageList'
seriesCount(x)

## S4 method for signature 'ImageMetadataList'
seriesCount(x)
```

**Arguments**

x                      an images object.

**Details**

Image series are encoded by [AnnotatedImageList](#) or [ImageMetadataList](#) objects. Therefore, only these objects can possibly yield image series count higher than 1 while for all the rest of image objects this number is expected to be 1.

**Value**

The number of image series the object contains, see Details.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256, series = 2)
img = read.image(f)
seriesCount(img)

meta <- metadata(img)
seriesCount(meta)
```

write.image

*Write Images***Description**

Save image files using the Bio-Formats library. A list of supported formats can be found on the [Bio-Formats website](#).

**Usage**

```
write.image(x, file, force = FALSE, pixelType, littleEndian)
```

**Arguments**

|              |                                                   |
|--------------|---------------------------------------------------|
| x            | an Image or <a href="#">AnnotatedImage</a> object |
| file         | character, file name                              |
| force        | logical(1), if TRUE overwrite existing file       |
| pixelType    | character(1), data type to store pixel values     |
| littleEndian | boolean(1), pixel data endianness                 |

**Value**

File path to file is returned invisibly.

**Author(s)**

Andrzej Oleś <<andrzej.oles@gmail.com>>, 2014-2023

**See Also**

[read.image](#) for reading images.

**Examples**

```
f = mockFile(sizeX = 256, sizeY = 256)
img = read.image(f)

tempfile = tempfile("", , ".png")
write.image(img, tempfile)
```

# Index

## \* datasets

FormatTools, 7  
.AnnotatedImage (AnnotatedImage-class), 2  
.AnnotatedImageList  
(AnnotatedImageList-class), 3  
.ImageMetadata (ImageMetadata-class), 7  
.ImageMetadataList  
(ImageMetadata-class), 7  
  
AnnotatedImage, 2, 3, 5, 10, 14  
AnnotatedImage (AnnotatedImage-class), 2  
AnnotatedImage-class, 2  
AnnotatedImageList, 3, 5, 10, 13  
AnnotatedImageList  
(AnnotatedImageList-class), 3  
AnnotatedImageList-class, 3  
as.Image.AnnotatedImage  
(AnnotatedImage-class), 2  
  
BioFormats.version (RBioFormats), 9  
  
checkJavaMemory, 4  
coreMetadata, 4  
coreMetadata<- (coreMetadata), 4  
coreMetadata<- ,AnnotatedImage-method  
(coreMetadata), 4  
coreMetadata<- ,ImageMetadata-method  
(coreMetadata), 4  
  
dimorder, 6  
  
FormatTools, 7  
  
globalMetadata (coreMetadata), 4  
globalMetadata<- (coreMetadata), 4  
globalMetadata<- ,AnnotatedImage-method  
(coreMetadata), 4  
globalMetadata<- ,ImageMetadata-method  
(coreMetadata), 4  
grep, 5  
  
Image, 2, 6  
ImageMetadata, 2, 3, 5, 8, 11  
ImageMetadata (ImageMetadata-class), 7

ImageMetadata-class, 7  
ImageMetadataList, 5, 8, 11, 13  
ImageMetadataList  
(ImageMetadata-class), 7  
ImageMetadataList-class  
(ImageMetadata-class), 7  
  
metadata,AnnotatedImage-method  
(coreMetadata), 4  
metadata,AnnotatedImageList-method  
(coreMetadata), 4  
metadata,ANY-method (coreMetadata), 4  
metadata,ImageMetadata-method  
(coreMetadata), 4  
metadata,ImageMetadataList-method  
(coreMetadata), 4  
metadata<- ,AnnotatedImage-method  
(coreMetadata), 4  
mockFile, 8  
  
print.AnnotatedImage  
(AnnotatedImage-class), 2  
print.ImageMetadata  
(ImageMetadata-class), 7  
print.ImageMetadataList  
(ImageMetadata-class), 7  
  
RBioFormats, 9  
read.image, 10, 11, 12, 14  
read.metadata, 11, 11, 12  
read.omexml, 11, 12  
  
seriesCount, 13  
seriesCount,AnnotatedImageList-method  
(seriesCount), 13  
seriesCount,ANY-method (seriesCount), 13  
seriesCount,array-method (seriesCount), 13  
seriesCount,ImageMetadata-method  
(seriesCount), 13  
seriesCount,ImageMetadataList-method  
(seriesCount), 13  
seriesCount,matrix-method  
(seriesCount), 13

`seriesMetadata (coreMetadata)`, [4](#)  
`seriesMetadata<- (coreMetadata)`, [4](#)  
`seriesMetadata<- ,AnnotatedImage-method`  
    (`coreMetadata`), [4](#)  
`seriesMetadata<- ,ImageMetadata-method`  
    (`coreMetadata`), [4](#)  
`show,AnnotatedImage-method`  
    (`AnnotatedImage-class`), [2](#)  
`show,ImageMetadata-method`  
    (`ImageMetadata-class`), [7](#)  
`show,ImageMetadataList-method`  
    (`ImageMetadata-class`), [7](#)  
  
`write.image`, [14](#)