

Package ‘iSEEid’

June 24, 2026

Title iSEE extension to assist in identifying sets of samples/cells

Version 0.99.1

Description This package provides a dedicated panel to assist the sample identification within a single iSEE web-application. The main functionality of this package can be adopted to efficiently select samples (e.g. cells) that need to be identified and annotated in the analysis workflow. With iSEEid, the iSEE framework fully qualifies to be an ideal companion for assigning appropriate labels to large omics datasets.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends iSEE, SummarizedExperiment

Imports methods, shiny, shinyAce

Suggests scRNAseq, scater, knitr, rmarkdown, BiocStyle, testthat (>= 3.0.0), scrapper

URL <https://github.com/iSEE/iSEEid>

BugReports <https://github.com/iSEE/iSEEid/issues>

VignetteBuilder knitr

biocViews CellBasedAssays, Clustering, DimensionReduction, FeatureExtraction, GeneExpression, GUI, ImmunoOncology, ShinyApps, SingleCell, Transcription, Transcriptomics, Visualization

Config/testthat/edition 3

Config/roxygen2/version 8.0.0

git_url <https://git.bioconductor.org/packages/iSEEid>

git_branch devel

git_last_commit 2acbe15

git_last_commit_date 2026-06-16

Repository Bioconductor 3.24

Date/Publication 2026-06-23

Author Federico Marini [aut, cre] (ORCID:
 <<https://orcid.org/0000-0003-3252-7758>>),
 Kevin Rue-Albrecht [aut] (ORCID:
 <<https://orcid.org/0000-0003-3899-3872>>),
 Charlotte Soneson [aut] (ORCID:
 <<https://orcid.org/0000-0003-3833-2169>>)

Maintainer Federico Marini <marinif@uni-mainz.de>

Contents

iSEEid-pkg	2
SampleIdentificationCenter-class	3
Index	5

iSEEid-pkg

iSEEid

Description

This package provides a dedicated panel to assist the sample identification within a single iSEE web-application. The main functionality of this package can be adopted to efficiently select samples (e.g. cells) that need to be identified and annotated in the analysis workflow. With iSEEid, the iSEE framework fully qualifies to be an ideal companion for assigning appropriate labels to large omics datasets.

Author(s)

Maintainer: Federico Marini <marinif@uni-mainz.de> (ORCID)

Authors:

- Federico Marini <marinif@uni-mainz.de> (ORCID)
- Kevin Rue-Albrecht <kevinrue67@gmail.com> (ORCID)
- Charlotte Soneson <charlottesoneson@gmail.com> (ORCID)

See Also

Useful links:

- <https://github.com/iSEE/iSEEid>
- Report bugs at <https://github.com/iSEE/iSEEid/issues>

SampleIdentificationCenter-class

The SampleIdentificationCenter class

Description

The SampleIdentificationCenter is a [iSEE::Panel](#) subclass that is dedicated to generating ready-to-use R code for assigning a sample label to samples received by a selection from another panel.

Value

A panel designed to work within the iSEE framework

Slot overview

The following slots control the behavior of the panel:

- EditorUsageMode, a logical scalar determining whether to show the full R command for making the sample label assignments (if FALSE, displays the sample id list as plain text).
- AnnotationRationale, a string specifying the rationale for the sample label assignment.
- CellTypeLabel, a string providing the label to assign to the selected samples.
- ColDataColumn, a string indicating the name of the colData column to store the assigned labels.

In addition, this class inherits all slots from its parent [iSEE::Panel](#) class.

Constructor

SampleIdentificationCenter(...) creates an instance of a SampleIdentificationCenter class, where any slot and its value can be passed to ... as a named argument.

Supported methods

In the following code snippets, x is an instance of a [SampleIdentificationCenter](#) class.

Author(s)

Federico Marini

See Also

[iSEE::Panel](#), for the base class.

Examples

```
library(iSEE)
library(scRNAseq)

# Example data ----
sce <- ReprocessedAllenData(assays = "tophat_counts")
class(sce)
```

```
library(scater)
library(scrapper)
sce <- normalizeRnaCounts.se(sce, assay.type = "tophat_counts", size.factors = NULL)

sce <- runPCA(sce, ncomponents=4)
sce <- runTSNE(sce)
rowData(sce)$ave_count <- rowMeans(assay(sce, "tophat_counts"))
rowData(sce)$n_cells <- rowSums(assay(sce, "tophat_counts") > 0)

# launch the app itself ----

if (interactive()) {
  iSEE(sce, initial = list(
    ReducedDimensionPlot(),
    SampleIdentificationCenter(
      ColumnSelectionSource = "ReducedDimensionPlot1"
    )
  )
)
}
```

Index

*** internal** 3

- iSEEd-pkg, [2](#) SampleIdentificationCenter-class, [3](#)
- .createObservers, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .defineDataInterface, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .defineOutput, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .definePanelTour, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .fullName, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .generateOutput, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .hideInterface, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .multiSelectionResponsive, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .panelColor, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- .renderOutput, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)

- initialize, SampleIdentificationCenter-method
(SampleIdentificationCenter-class),
[3](#)
- iSEE::Panel, [3](#)
- iSEEd(iSEEd-pkg), [2](#)
- iSEEd-package(iSEEd-pkg), [2](#)
- iSEEd-pkg, [2](#)

- SampleIdentificationCenter, [3](#)
- SampleIdentificationCenter
(SampleIdentificationCenter-class),