

Package ‘STAN’

October 12, 2016

Version 2.0.3

Date 2016-05-30

Title The genomic STate ANnotation package

Author Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

Maintainer Benedikt Zacher <zacher@genzentrum.lmu.de>

Imports GenomicRanges, IRanges, S4Vectors, BiocGenerics, GenomeInfoDb, Gviz, Rsolnp

Depends methods, poilog, parallel

VignetteBuilder knitr

Suggests BiocStyle, gplots, knitr

Description Genome segmentation with hidden Markov models has become a useful tool to annotate genomic elements, such as promoters and enhancers. STAN (genomic STate ANnotation) implements (bidirectional) hidden Markov models (HMMs) using a variety of different probability distributions, which can model a wide range of current genomic data (e.g. continuous, discrete, binary). STAN de novo learns and annotates the genome into a given number of 'genomic states'. The 'genomic states' may for instance reflect distinct genome-associated protein complexes (e.g. 'transcription states') or describe recurring patterns of chromatin features (referred to as 'chromatin states'). Unlike other tools, STAN also allows for the integration of strand-specific (e.g. RNA) and non-strand-specific data (e.g. CHIP).

License GPL (>= 2)

biocViews HiddenMarkovModel, GenomeAnnotation, Microarray, Sequencing, ChIPSeq, RNASeq, ChipOnChip, Transcription

LazyLoad yes

NeedsCompilation yes

R topics documented:

STAN-package	2
bdHMM	3
bdHMM-class	4
binarizeData	5

c2optimize	6
call_dpolog	6
data2Gviz	7
DimNames	7
DirScore	8
Emission	9
EmissionParams	9
example	10
fitHMM	10
flags	11
getAvgSignal	12
getLogLik	12
getPosterior	13
getSizeFactors	14
getViterbi	15
HMM	16
HMM-class	17
HMMemission	18
HMMemission-class	18
initBdHMM	19
initHMM	20
InitProb	20
LogLik	21
observations	22
pilot.hg19	22
runningMean	22
StateNames	23
trainRegions	24
Transitions	24
ucscGenes	25
viterbi2GRanges	25
viterbi2Gviz	26
yeastTF_databychrom_ex	26
yeastTF_SGDGenes	26
[,bdHMM,ANY,ANY-method	27
[,HMM,ANY,ANY-method	27
Index	28

STAN-package

The genomic STate ANnotation package

Description

The genomic STate ANnotation package

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

References

Zacher, B. and Lidschreiber, M. and Cramer, P. and Gagneur, J. and Tresch, A. (2014): Annotation of genomics data using bidirectional hidden Markov models unveils variations in Pol II transcription cycle Mol. Syst. Biol. 10:768

 bdHMM

Create a bdHMM object

Description

This function creates a bdHMM function.

Usage

```
bdHMM(initProb = numeric(), transMat = matrix(numeric(), ncol = 0, nrow =
  0), emission, nStates = numeric(), status = character(),
  stateNames = character(), dimNames = character(),
  transitionsOptim = "analytical", directedObs = integer(),
  dirScore = numeric())
```

Arguments

initProb	Initial state probabilities.
transMat	Transition probabilities
emission	Emission parameters as an HMM Emission object.
nStates	Number of states.
status	Status of the bdHMM. 'Initial' means that the model was not fitted yet. 'EM' means that the model was optimized using Expectation maximization.
stateNames	Indicates directinality of states. States can be forward (F1, F2, ..., Fn), reverse (R1, R2, ..., Rn) or unidirectional (U1, U2, ..., Um). Number of F and R states must be equal and twin states are indicated by integers in id (e.g. F1 and R1 and twins).
dimNames	Names of data tracks.
transitionsOptim	There are three methods to choose from for fitting the transitions. Bidirectional transition matrices (invariant under reversal of time and direction) can be fitted using c('rsolnp', 'analytical'). 'None' uses standard update formulas and the resulting matrix is not constrained to be bidirectional.
directedObs	An integer indicating which dimensions are directed. Undirected dimensions are 0. Directed observations must be marked as unique integer pairs. For instance c(0,0,0,0,0,1,1,2,2,3,3) contains 5 undirected observations, and three pairs (one for each direction) of directed observations.
dirScore	Directionality score of states of a fitted bdHMM.

See Also[HMMEmission](#)**Examples**

```

nStates = 5
stateNames = c('F1', 'F2', 'R1', 'R2', 'U1')
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
myEmission = list(d1=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means)))

bdhmm = bdHMM(initProb=initProb, transMat=transMat, emission=myEmission, nStates=nStates, status='initial', sta

```

bdHMM-class

This class is a generic container for bidirectional Hidden Markov Models.

Description

This class is a generic container for bidirectional Hidden Markov Models.

Slots

`initProb` Initial state probabilities.

`transMat` Transition probabilities

`emission` Emission parameters as an HMMEmission object.

`nStates` Number of states.

`status` of the HMM. On of c('initial', 'EM').

`stateNames` State names.

`dimNames` Names of data tracks.

`LogLik` Log likelihood of a fitted HMM.

`transitionsOptim` There are three methods to choose from for fitting the transitions. Bidirectional transition matrices (invariant under reversal of time and direction) can be fitted using c('rsolnp', 'ipopt'). 'None' uses standard update formulas and the resulting matrix is not constrained to be bidirectional.

`directedObs` An integer indicating which dimensions are directed. Undirected dimensions are 0. Directed observations must be marked as unique integer pairs. For instance c(0,0,0,0,0,1,1,2,2,3,3) contains 5 undirected observations, and three pairs (one for each direction) of directed observations.

`dirScore` Directionality score of states of a fitted bdHMM.

Methods

[get elements from the bdHMM

See Also

[HMMEmission](#)

Examples

```
nStates = 5
stateNames = c('F1', 'F2', 'R1', 'R2', 'U1')
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
myEmission = list(d1=HMMEmission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means)))

bdhmm = bdHMM(initProb=initProb, transMat=transMat, emission=myEmission, nStates=nStates, status='initial', sta
```

binarizeData

Binarize Sequencing data with the default ChromHMM binarization

Description

Binarize Sequencing data with the default ChromHMM binarization

Usage

```
binarizeData(obs)
```

Arguments

obs The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).

Value

Binarized observation sequences as a list.

Examples

```
data(trainRegions)
binData = binarizeData(trainRegions)
```

c2optimize

Optimize transitions

Description

The function is called from C++ to optimize transitions.

Usage

```
c2optimize(pars)
```

Arguments

pars Parameters for optimization.

Value

optimized transitions

call_dpoilog

Calculate density of the Poisson-Log-Normal distribution.

Description

Calculate density of the Poisson-Log-Normal distribution.

Usage

```
call_dpoilog(x)
```

Arguments

x A vector $c(n, \mu, \sigma)$, where n is the number of observed counts, μ the mean of the Log-Normal distribution and σ its variance.

Value

Density of the Poisson-Log-Normal distribution.

Examples

```
call_dpoilog(c(5, 2, 1))
```

data2Gviz	<i>Convert data for plotting with Gviz</i>
-----------	--

Description

Convert data for plotting with Gviz

Usage

```
data2Gviz(obs, regions, binSize, gen, col = "black")
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
regions	GRanges object of the regions (e.g. chromosomes) stored in the viterbi path.
binSize	The bin size of the viterbi path.
gen	The genome id, e.g. hg19, hg38 for human.
col	The color of the data tracks.

Value

A list containing the data tracks converted to Gviz objects for plotting.

DimNames	<i>Get dimNames of a (bd)HMM</i>
----------	----------------------------------

Description

This function returns the names of dimensions (data tracks).

Usage

```
DimNames(hmm)
```

Arguments

hmm	An object of class HMM or bdHMM.
-----	----------------------------------

Value

A character vector

Examples

```

nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(dimNames="1", initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=
DimNames(hmm)

```

DirScore

Get directionality score of a bdHMM

Description

This function returns the directionality score of a bdHMM.

Usage

```
DirScore(bdhmm)
```

Arguments

bdhmm An object of class bdHMM.

Value

Directionality score of the bdHMM after model fitting.

Examples

```

data(example)
bdhmm_ex = initBdHMM(observations, nStates=3, method="Gaussian", directedObs=0)

# without flags
bdhmm_fitted_noFlags = fitHMM(observations, bdhmm_ex)
DirScore(bdhmm_fitted_noFlags)

# with flags
bdhmm_fitted_flags = fitHMM(observations, bdhmm_ex, dirFlags=flags)
DirScore(bdhmm_fitted_flags)

```

Emission	<i>Get Emission functions of a (bd)HMM</i>
----------	--

Description

This function returns the Emission functions of a (bd)HMM.

Usage

```
Emission(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

An object of class HMM Emission

See Also

[HMMEmission](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means,
Emission(hmm)
```

EmissionParams	<i>Get Emission parameters of a (bd)HMM.</i>
----------------	--

Description

This function returns the parameters of emission functions of a (bd)HMM object.

Usage

```
EmissionParams(hmm)
```

Arguments

hmm An object of class (bd)HMM.

Value

A list containing the parameters of the Emission functions.

See Also

[HMMEmission](#), [HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussian', parameters=list(mu=means,
EmissionParams(hmm))
```

example	<i>The data for the bdHMM example in the vignette and examples in the manual</i>
---------	--

Description

The data for the bdHMM example in the vignette and examples in the manual

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

fitHMM	<i>Fit a Hidden Markov Model</i>
--------	----------------------------------

Description

The function is used to fit (bidirectional) Hidden Markov Models, given one or more observation sequence.

Usage

```
fitHMM(obs=list(), hmm, convergence=1e-6, maxIters=1000, dirFlags=list(), emissionProbs=list(), effe
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
hmm	The initial Hidden Markov Model. This is a HMM .
convergence	Convergence cutoff for EM-algorithm (default: 1e-6).
maxIters	Maximum number of iterations.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
effectiveZero	Transitions below this cutoff are analytically set to 0 to speed up computations.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
incrementalEM	When TRUE, the incremental EM is used to fit the model, where parameters are updated after each iteration over a single observation sequence.
updateTransMat	Whether transitions should be updated during model learning, default: TRUE.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containing the trace of the log-likelihood during EM learning and the fitted HMM model.

See Also

[HMM](#)

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
```

flags

Pre-computed flag sequence for the 'example' data.

Description

Pre-computed flag sequence for the 'example' data.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

getAvgSignal *Compute average signal in state segmentation*

Description

Compute average signal in state segmentation

Usage

```
getAvgSignal(viterbi, obs, fct=mean)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from getViterbi.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
fct	The averaging function, default: mean.

Value

A state x data track matrix containing the average signal.

Examples

```
data(yeastTF_databychrom_ex)
nStates = 6
dirobs = as.integer(c(rep(0,10), 1, 1))
bdhmm_gauss = initBdHMM(yeastTF_databychrom_ex, nStates, "Gaussian", directedObs=dirobs)
bdhmm_fitted_gauss = fitHMM(yeastTF_databychrom_ex, bdhmm_gauss)
viterbi_bdhmm_gauss = getViterbi(bdhmm_fitted_gauss, yeastTF_databychrom_ex)
avg_signal = getAvgSignal(viterbi_bdhmm_gauss, yeastTF_databychrom_ex)
```

getLogLik *Calculate log likelihood state distribution.*

Description

The function calculates log likelihood for one or more observation sequence.

Usage

```
getLogLik(hmm, obs = list(), emissionProbs = list(), dirFlags = list(), verbose = FALSE, nCores = 1, s
```

Arguments

hmm	The Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

The log likelihood of the observations sequences, given the model.

See Also

[HMM](#)

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
loglik = getLogLik(hmm_fitted, observations)
loglik
```

getPosterior

Calculate posterior state distribution.

Description

The function calculates posterior state probabilities for one or more observation sequence.

Usage

```
getPosterior(hmm, obs=list(), emissionProbs=list(), dirFlags=list(), verbose=FALSE, nCores=1, sizeFactors=list())
```

Arguments

hmm	The Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
dirFlags	The flag sequence is needed when a bdHMM is fitted on undirected data (e.g.) ChIP only. It is a list of character vectors indication for each position its known directionality. U allows all states. F allows undirected states and states in forward direction. R allows undirected states and states in reverse direction.
verbose	logical for printing algorithm status or not.
nCores	Number of cores to use for computations.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containing for the observation sequences the posterior state (col) distribution at each position (row).

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
posterior = getPosterior(hmm_fitted, observations)
```

getSizeFactors	<i>Compute size factors</i>
----------------	-----------------------------

Description

Compute size factors

Usage

```
getSizeFactors(obs, celltypes)
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
celltypes	Indicates the cell type/tissue for each entry in obs.

Value

A celltype/tissue x data tracks matrix containing the size factors.

Examples

```
data(trainRegions)
celltypes = list("E123"=grep("E123", names(trainRegions)),
                "E116"=grep("E116", names(trainRegions)))
sizeFactors = getSizeFactors(trainRegions, celltypes)
sizeFactors
```

getViterbi

Calculate the most likely state path

Description

Given a Hidden Markov Model, the function calculates the most likely state path (viterbi) for one or more observation sequence.

Usage

```
getViterbi(hmm, obs=list(), NAtol=5, emissionProbs=list(), verbose=FALSE, sizeFactors=matrix(1, nrow=
```

Arguments

hmm	The initial Hidden Markov Model.
obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
NAtol	Successive positions having NAs longer than this threshold are masked in the viterbi path.
emissionProbs	List of precalculated emission probabilities of emission function is of type 'null'.
verbose	logical for printing algorithm status or not.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.

Value

A list containint the vterbi paths.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
viterbi = getViterbi(hmm_fitted, observations)
```

HMM*Create a HMM object*

Description

This function creates a HMM object.

Usage

```
HMM(initProb = numeric(), transMat = matrix(numeric(), ncol = 1, nrow = 1),
     emission, nStates = numeric(), status = character(),
     stateNames = character(), dimNames = character(), LogLik = numeric())
```

Arguments

<code>initProb</code>	Initial state probabilities.
<code>transMat</code>	Transition probabilities
<code>emission</code>	Emission parameters as an <code>HMM Emission</code> object.
<code>nStates</code>	Number of states.
<code>status</code>	of the HMM. On of <code>c('initial', 'EM')</code> .
<code>stateNames</code>	State names.
<code>dimNames</code>	Names of data tracks.
<code>LogLik</code>	Log likelihood of a fitted HMM.

See Also

[HMM Emission](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMM(initProb=initProb, transMat=transMat, emission=HMM Emission(type='Gaussian', parameters=list(mu=means, cov=Sigma)))
```

HMM-class

This class is a generic container for Hidden Markov Models.

Description

This class is a generic container for Hidden Markov Models.

Slots

initProb Initial state probabilities.

transMat Transition probabilities

emission Emission parameters as an HMMemission object.

nStates Number of states.

status of the HMM. One of c('initial', 'EM').

stateNames State names.

dimNames Names of data tracks.

LogLik Log likelihood of a fitted HMM.

Methods

[get elements from the HMM

See Also

[HMMemission](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
```

```
HMM(initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian', parameters=list(mu=means, cov=Sigma)))
```

HMMemission	<i>Create a HMMemission object</i>
-------------	------------------------------------

Description

This function creates a HMMemission object.

Usage

```
HMMemission(type = character(), parameters = list(), nStates = numeric())
```

Arguments

type	The type of emission function c('Gaussian').
parameters	A list containing the the parameters for each state.
nStates	The number of states.

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMMemission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means))
```

HMMemission-class	<i>This class is a generic container for different emission functions of Hidden Markov Models.</i>
-------------------	--

Description

This class is a generic container for different emission functions of Hidden Markov Models.

Slots

type	The type of emission function c('Gaussian').
parameters	A list containing the the parameters for each state.
dim	Number of dimensions.
nStates	The number of states.

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
HMMemission(type='Gaussian', parameters=list(mu=means, cov=Sigma), nStates=length(means))
```

initBdHMM

Initialization of bidirectional hidden Markov models

Description

Initialization of bidirectional hidden Markov models

Usage

```
initBdHMM(obs, nStates, method, directedObs = rep(0, ncol(obs[[1]])), sizeFactors = matrix(1, nrow = 1,
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
nStates	The number of states.
method	Emission distribution of the model. One out of c("NegativeBinomial", "Poisson-LogNormal", "NegativeMultinomial", "ZINegativeBinomial", "Poisson", "Bernoulli", "Gaussian", "IndependentGaussian")
directedObs	Integer vector defining the directionality (or strand-specificity) of the data tracks. Undirected (non-strand-specific) data tracks (e.g. ChIP) are indicated by '0'. Directed (strand-specific) data tracks are indicated by increasing pairs of integers. For instance c(0,0,0,1,1,2,2): The first three data tracks are undirected, followed by two pairs of directed measurements.
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.
sharedCov	If TRUE, (co-)variance of (Independent)Gaussian is shared over states. Only applicable to 'Gaussian' or 'IndependentGaussian' emissions. Default: FALSE.

Value

A HMM object.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
```

initHMM *Initialization of hidden Markov models*

Description

Initialization of hidden Markov models

Usage

```
initHMM(obs, nStates, method, sizeFactors = matrix(1, nrow = length(obs), ncol = ncol(obs[[1]])), sharedCov = FALSE)
```

Arguments

obs	The observations. A list of one or more entries containing the observation matrix (numeric) for the samples (e.g. chromosomes).
nStates	The number of states.
method	Emission distribution of the model. One out of c("NegativeBinomial", "Poisson-LogNormal", "NegativeMultinomial", "ZINegativeBinomial", "Poisson", "Bernoulli", "Gaussian", "IndependentGaussian")
sizeFactors	Library size factors for Emissions PoissonLogNormal or NegativeBinomial as a length(obs) x ncol(obs[[1]]) matrix.
sharedCov	If TRUE, (co-)variance of (Independent)Gaussian is shared over states. Only applicable to 'Gaussian' or 'IndependentGaussian' emissions. Default: FALSE.

Value

A HMM object.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
```

InitProb *Get initial state probabilities of a (bd)HMM*

Description

This function returns the initial state probabilities of a (bd)HMM.

Usage

```
InitProb(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

The initial state probabilities as a numeric vector.

See Also

[HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian', parameters=list(mu=means,
InitProb(hmm)
```

LogLik

Get stateNames of a (bd)HMM

Description

This function returns the Log-Likelihood of a (bd)HMM.

Usage

```
LogLik(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

Log likelihood during model fitting.

Examples

```
data(example)
hmm_ex = initHMM(observations, nStates=3, method="Gaussian")
hmm_fitted = fitHMM(observations, hmm_ex)
LogLik(hmm_fitted)
```

observations	<i>Observation sequence for the 'example' data.</i>
--------------	---

Description

Observation sequence for the 'example' data.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

pilot.hg19	<i>Genomic positions of processed signal for the Roadmap Epigenomics data set. Regions from the ENCODE pilot phase.</i>
------------	---

Description

Genomic positions of processed signal for the Roadmap Epigenomics data set. Regions from the ENCODE pilot phase.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

runningMean	<i>Smooth data with running mean</i>
-------------	--------------------------------------

Description

Smooth data with running mean

Usage

```
runningMean(x, winHalfSize = 2)
```

Arguments

x	A vector with the data.
winHalfSize	The smoothing window half size.

Value

A vector containing the smoothed data.

Examples

```
data(trainRegions)
celltypes = list("E123"=grep("E123", names(trainRegions)),
                 "E116"=grep("E116", names(trainRegions)))
sizeFactors = getSizeFactors(trainRegions, celltypes)
sizeFactors
```

StateNames

Get stateNames of a (bd)HMM

Description

This function returns the names of states.

Usage

```
StateNames(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

A character vector

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(stateNames=as.character(1:5), initProb=initProb, transMat=transMat, emission=HMMEmission(type='Gaussi
StateNames(hmm)
```

trainRegions	<i>Training regions for the Roadmap Epigenomics data set. Three ENCODE pilot regions with data from two cell lines.</i>
--------------	---

Description

Training regions for the Roadmap Epigenomics data set. Three ENCODE pilot regions with data from two cell lines.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

Transitions	<i>Get transitions of a (bd)HMM</i>
-------------	-------------------------------------

Description

This function returns the transition matrix of a (bd)HMM.

Usage

```
Transitions(hmm)
```

Arguments

hmm An object of class HMM or bdHMM.

Value

The transitions as a nStates x nStates matrix.

See Also

[HMM](#), [bdHMM](#)

Examples

```
nStates = 5
means = list(4,11,4,11,-1)
Sigma = lapply(list(4,4,4,4,4), as.matrix)
transMat = matrix(1/nStates, nrow=nStates, ncol=nStates)
initProb = rep(1/nStates, nStates)
hmm = HMM(initProb=initProb, transMat=transMat, emission=HMMemission(type='Gaussian', parameters=list(mu=means,
Transitions(hmm)
```


ucscGenes

*UCSC gene annotation for the Roadmap Epigenomics data set.***Description**

UCSC gene annotation for the Roadmap Epigenomics data set.

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

viterbi2GRanges

*Convert the viterbi path to a GRanges object***Description**

Convert the viterbi path to a GRanges object

Usage

```
viterbi2GRanges(viterbi, regions, binSize)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from <code>getViterbi</code> .
regions	GRanges object of the regions (e.g. chromosomes) stored in the viterbi path.
binSize	The bin size of the viterbi path.

Value

The viterbi path as GRanges object.

Examples

```
library(GenomicRanges)
data(yeastTF_databychrom_ex)
nStates = 6
dirobs = as.integer(c(rep(0,10), 1, 1))
bdhmm_gauss = initBdHMM(yeastTF_databychrom_ex, nStates, "Gaussian", directedObs=dirobs)
bdhmm_fitted_gauss = fitHMM(yeastTF_databychrom_ex, bdhmm_gauss)
viterbi_bdhmm_gauss = getViterbi(bdhmm_fitted_gauss, yeastTF_databychrom_ex)
yeastGRanges = GRanges(IRanges(start=1214616, end=1225008), seqnames="chrIV")
names(viterbi_bdhmm_gauss) = "chrIV"
viterbi_bdhmm_gauss_gr = viterbi2GRanges(viterbi_bdhmm_gauss, yeastGRanges, 8)
```

viterbi2Gviz *Convert state segmentation for plotting with Gviz*

Description

Convert state segmentation for plotting with Gviz

Usage

```
viterbi2Gviz(viterbi, chrom, gen, from, to, statecols)
```

Arguments

viterbi	A list containing the viterbi paths as factors. The output from getViterbi.
chrom	The chromosome/sequence if to convert.
gen	The geome id, e.g. hg19, hg38 for human.
from	Genomic start poistion.
to	Genomic end poistion.
statecols	Named vector with state colors.

Value

A list containing the viterbi path converted to Gviz objects for plotting.

yeastTF_databychrom_ex

Processed ChIP-on-chip data for yeast TF example

Description

Processed ChIP-on-chip data for yeast TF example

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

yeastTF_SGDGenes

SGD annotation for the yeast TF example

Description

SGD annotation for the yeast TF example

Author(s)

Benedikt Zacher, Julia Ertl, Julien Gagneur, Achim Tresch

[,bdHMM,ANY,ANY-method

This function subsets a bdHMM object. Rows are interpreted as states, columns as dimensions of emissions.

Description

This function subsets a bdHMM object. Rows are interpreted as states, columns as dimensions of emissions.

Usage

```
## S4 method for signature 'bdHMM,ANY,ANY'
x[i, j, ..., drop = "missing"]
```

Arguments

x	A bidirectional hidden Markov model.
i	State ids to extract.
j	Emissions to extract.
...	...
drop	...

[,HMM,ANY,ANY-method *This function subsets an HMM object. Rows are interpreted as states, columns as dimensions of emissions.*

Description

This function subsets an HMM object. Rows are interpreted as states, columns as dimensions of emissions.

Usage

```
## S4 method for signature 'HMM,ANY,ANY'
x[i, j, ..., drop = "missing"]
```

Arguments

x	A hidden Markov model.
i	State ids to extract.
j	Emissions to extract.
...	...
drop	...

Index

*Topic **data**

- example, [10](#)
- flags, [11](#)
- observations, [22](#)
- pilot.hg19, [22](#)
- trainRegions, [24](#)
- ucscGenes, [25](#)
- yeastTF_databychrom_ex, [26](#)
- yeastTF_SGDGenes, [26](#)

*Topic **package**

- STAN-package, [2](#)
- .HMM (HMM-class), [17](#)
- .HMMemission (HMMemission-class), [18](#)
- .bdHMM (bdHMM-class), [4](#)
- [,HMM,ANY,ANY,ANY-method (HMM-class), [17](#)
- [,HMM,ANY,ANY-method, [27](#)
- [,bdHMM,ANY,ANY,ANY-method (bdHMM-class), [4](#)
- [,bdHMM,ANY,ANY-method, [27](#)

- bdHMM, [3](#), [10](#), [21](#), [24](#)
- bdHMM-class, [4](#)
- binarizeData, [5](#)

- c2optimize, [6](#)
- call_dpoilog, [6](#)

- data2Gviz, [7](#)
- DimNames, [7](#)
- DirScore, [8](#)

- Emission, [9](#)
- EmissionParams, [9](#)
- example, [10](#)

- fitHMM, [10](#)
- flags, [11](#)

- getAvgSignal, [12](#)
- getLogLik, [12](#)
- getPosterior, [13](#)

- getSizeFactors, [14](#)
- getViterbi, [15](#)

- HMM, [10](#), [11](#), [13](#), [16](#), [21](#), [24](#)
- HMM-class, [17](#)
- HMMemission, [4](#), [5](#), [9](#), [10](#), [16](#), [17](#), [18](#)
- HMMemission-class, [18](#)

- initBdHMM, [19](#)
- initHMM, [20](#)
- InitProb, [20](#)

- LogLik, [21](#)

- observations, [22](#)

- pilot.hg19, [22](#)

- runningMean, [22](#)

- STAN-package, [2](#)
- StateNames, [23](#)

- trainRegions, [24](#)
- Transitions, [24](#)

- ucscGenes, [25](#)

- viterbi2GRanges, [25](#)
- viterbi2Gviz, [26](#)

- yeastTF_databychrom_ex, [26](#)
- yeastTF_SGDGenes, [26](#)