

NAME**libxdot** – parsing and deparsing of xdot operations**SYNOPSIS**

```
#include <graphviz/xdot.h>
```

```
typedef enum {
    xd_left, xd_center, xd_right
} xdot_align;
```

```
typedef struct {
    double x, y, z;
} xdot_point;
```

```
typedef struct {
    double x, y, w, h;
} xdot_rect;
```

```
typedef struct {
    int cnt;
    xdot_point* pts;
} xdot_polyline;
```

```
typedef struct {
    double x, y;
    xdot_align align;
    double width;
    char* text;
} xdot_text;
```

```
typedef struct {
    xdot_rect pos;
    char* name;
} xdot_image;
```

```
typedef struct {
    double size;
    char* name;
} xdot_font;
```

```
typedef enum {
    xd_filled_ellipse, xd_unfilled_ellipse,
    xd_filled_polygon, xd_unfilled_polygon,
    xd_filled_bezier, xd_unfilled_bezier,
    xd_polyline,    xd_text,
    xd_fill_color,  xd_pen_color, xd_font, xd_style, xd_image
} xdot_kind;
```

```
typedef enum {
    xop_ellipse,
    xop_polygon,
    xop_bezier,
    xop_polyline,    xop_text,
    xop_fill_color,  xop_pen_color, xop_font, xop_style, xop_image
} xop_kind;
```

```

typedef struct _xdot_op xdot_op;
typedef void (*drawfunc_t)(xdot_op*, int);
typedef void (*freefunc_t)(xdot_op*);

struct _xdot_op {
    xdot_kind kind;
    union {
        xdot_rect ellipse; /* xd_filled_ellipse, xd_unfilled_ellipse */
        xdot_polyline polygon; /* xd_filled_polygon, xd_unfilled_polygon */
        xdot_polyline polyline; /* xd_polyline */
        xdot_polyline bezier; /* xd_filled_bezier, xd_unfilled_bezier */
        xdot_text text; /* xd_text */
        xdot_image image; /* xd_image */
        char* color; /* xd_fill_color, xd_pen_color */
        xdot_font font; /* xd_font */
        char* style; /* xd_style */
    } u;
    drawfunc_t drawfunc;
};

#define XDOT_PARSE_ERROR 1

typedef struct {
    int cnt;
    int sz;
    xdot_op* ops;
    freefunc_t freefunc;
    int flags;
} xdot;

xdot* parseXDotF (char*, drawfunc_t opfns[], int sz);
xdot* parseXDot (char*);
char* sprintXDot (xdot*);
void fprintfXDot (FILE*, xdot*);
void freeXDot (xdot*);

```

DESCRIPTION

libxdot provides support for parsing and deparsing graphical operations specified by the *xdot* language.

Types

xdot

This encapsulates a series of *cnt* *xdot* operations, stored in the array pointed to by *ops*. The *sz* indicates the size of each item stored in *ops*. If the user sets the *freefunc* field, this function will be called on each item in *ops* during *freeXDot* before the library does its own clean up of the item. This allows the user to free any resources stored in the item by using an expansion of the *xdot_op* structure.

xdot_op

A value of this type represents one *xdot* operation. The operation is specified by the *kind* field. The corresponding data is stored in the union *u*, with the subfield associated with a given *kind* indicated by the comments.

The *drawfunc* field allows the user to attach a drawing-specific function to the operation, providing an object-based interface. These functions can be automatically attached during parsing by providing a non-NULL second argument to *parseXDotF*.

xop_kind

This type provides an enumeration of the allowed xdot operations. See <http://www.graphviz.org/doc/info/output.html#d:xdot> for the specific semantics associated with each operation.

xdot_rect

This represents a rectangle. For ellipses, the x and x fields represent the center of the rectangle, and w and h give the half-width and half-height, respectively. For images, (x,y) gives the lower left corner of the rectangle, and w and h give the width and height, respectively.

xdot_polyline

This type encapsulates a series of *cnt* points.

xdot_text

A value of this type corresponds to printing the string *text* using the baseline point (x,y) . The *width* field gives an approximation of how wide the printed string will be using the current font and font size. The *align* field indicates how the text should be horizontally aligned with the point (x,y) .

xdot_image

This denotes the insertion of an image. The image source is given by *name*. The images is to be placed into the rectangle *pos*.

xdot_font

The fields give the name and size, in points, of a font.

xdot_align

This enumeration type corresponds to the xdot alignment values -1, 0 and 1 used with the text operator, or '\l', '\n' and '\r' used in dot text.

Functions**xdot* parseXDotF (char *str, drawfunc_t* opfns, int sz)**

Parses the string *str* as a sequence of xdot operations and returns a pointer to the resulting *xdot* structure. The function parses as many xdot operations as it can. If some unknown or incorrect input was encountered in *str*, the *ops* and *cnt* fields will reflect the operations parsed before the error, and the *XDOT_PARSE_ERROR* bit will be set in the *flags* field. The function returns NULL if it cannot parse anything.

If *sz* is non-zero, it is assumed to be the size of some structure type containing *xdot_op* as a prefix. In this case, the elements in the array pointed to by *ops* will each have size *sz*.

If *opfns* is non-zero, it is taken to be any array of functions indexed by *xop_kind*. During parsing, the *drawfunc* member of *xdot_op* will be set to the corresponding function in *opfns*.

xdot* parseXDot (char *str)

This is equivalent to *parseXDotF(str, 0, 0)*.

void freeXDot (xdot* xp)

This frees the resources associated with the argument. If *xp* is NULL, nothing happens.

extern char* sprintXDot (xdot* xp)**extern void fprintfXDot (FILE* fp, xdot* xp)**

These two functions deparse the argument xdot structure, producing a string representation. *fprintXDot* writes the output onto the open stream *fp*; *sprintXDot* returns a heap-allocated string.

BUGS

Although some small checking is done on the *sz* argument to *parseXDotF*, it is assumed it is a valid value from *sizeof* applied to some structure type containing *xdot_op* as its first field. There can be no validation of the *opfns* argument.

AUTHORS

Emden R. Gansner (erg@research.att.com).