

Analyzing Thermal Proteome Profiling experiments by NPARC (Non-Parametric Analysis of Response Curves)

Dorothee Childs, Nils Kurzawa

European Molecular Biology Laboratory (EMBL),
Heidelberg, Germany
`dorothee.childs@embl.de`

TPP version 3.10.1

Abstract

This document demonstrates how to analyze TPP-TR (temperature range) experiments by the NPARC approach. NPARC is a recent extension to the *TPP* package. It offers a novel methodology to model the temperature dependent melting behaviour of each protein, and to detect significant changes in this behavior due to changes in experimental conditions like drug treatment [1].

In brief, the melting curve of each protein is represented by natural splines, either once for all conditions (null model), or separately for different experimental conditions (alternative model). Condition specific effects are then detected by testing for significant improvements in goodness-of-fit of the alternative model relative to the null model.

Contents

1	Installation and input data	1
2	Getting started	1

1 Installation and input data

This document describes the analysis of TPP-TR data by the NPARC approach. General information regarding package installation and format of the input data is provided in the complementary [introductory vignette](#).

2 Getting started

To install the package, type the following commands into the *R* console

TPP

```
## Warning in mutate_impl(.data, dots): binding character and factor vector, coercing
into character vector

## Warning in mutate_impl(.data, dots): binding character and factor vector, coercing
into character vector

## Warning in mutate_impl(.data, dots): binding character and factor vector, coercing
into character vector
```

Here, the new methodology is activated by the argument `method = "splinefit"` (available since package version 3.0.0) This performs the spline fitting procedure in parallel on a maximum of two CPUs (requirement for package vignettes). Without specifying the `nCores` argument, fitting is performed by default on the maximum number of CPUs on your device.

References

- [1] Mikhail M Savitski, Friedrich BM Reinhard, Holger Franken, Thilo Werner, Maria Falth Savitski, Dirk Eberhard, Daniel Martinez Molina, Rozbeh Jafari, Rebecca Bakszt Dovega, Susan Klaeger, et al. Tracking cancer drugs in living cells by thermal profiling of the proteome. *Science*, 346(6205):1255784, 2014.
- [2] Holger Franken, Toby Mathieson, Dorothee Childs, Gavain Sweetman, Thilo Werner, Wolfgang Huber, and Mikhail M Savitski. Thermal proteome profiling for unbiased identification of drug targets and detection of downstream effectors. *Nature protocols*, 10(10):1567 – 1593, 2015.